

ONLEVEL
ADVANCED RAILING TECHNOLOGY
EUROGLAS.
PRODUCT PROGRAM
2026 | 2027

ONLEVEL

ADVANCED RAILING TECHNOLOGY

EXPERT SUPPORT STARTS HERE



ONLEVEL GmbH
Budberger Straße 5
46446 Emmerich am Rhein
Germany
Tel: +49 (0)2822 975 14-0
www.onlevel.com
info@onlevel.com

ONLEVEL Nordic Aps
Gunnar Clausens Vej 26B
DK-8260 Viby J
Denmark
Tel: +45 69 14 38 00
www.onlevel.com
sales@onlevel-nordic.com

ONLEVEL Ltd.
Unit 7, Alexandria Court
Alexandria Drive | Ashton Commerce Park
Ashton-under-Lyne | Lancashire OL7 OQN
United Kingdom
Tel: +44 0161 804 9500
www.onlevel-uk.com
info@onlevel-uk.com

Niels Wildschut
Sales manager
niels@onlevel.com
Tel: +49 151 14 16 26 56

Erwin Stegenga
Field sales
erwin@onlevel.com
Tel: +31 62 23 44 169

Sales area:

Christophe Bardet
Field sales
christophe@onlevel.com
Tel: +33 64 24 23 652

Sales area:



Marco Bleffert
Field sales
marco@onlevel.com
Tel: +49 151 14 16 23 99

Sales area:



Frederik Vennemann
Field sales
frederik@onlevel.com
Tel: +49 171 7234678

Sales area:



Manuel Zant
Field sales
manuel@onlevel.com
Tel: +43 676 3640481

Sales area:

and the Balkans.

Welcome to the world of ONLEVEL.

OUR world.

Together, we see that the construction industry is changing. Skilled professionals are becoming increasingly scarce, while the pressure on quality, safety and efficiency continues to grow. On the one hand, modern technology is helping to ease the burden on the construction industry. On the other hand, the work that people continue to do is becoming increasingly valuable.

Every action counts. Every minute makes a difference. That is the principle behind ONLEVEL.

ONLEVEL develops and supplies advanced railing systems that make the work easier, faster and safer. We immerse ourselves in the daily reality of installers, planners and contractors to make the entire process as clear and straightforward as possible. From preparation to installation and final completion.

ONLEVEL combines cutting-edge technology with practical innovation.
Step by step, we are raising the standard for railing systems. So you can deliver better projects with greater confidence, less effort and higher returns.

ONLEVEL
Advanced Railing Technology

A clear change



Iwan Oude Luttikhuis
CEO ONLEVEL




ONLEVEL
ADVANCED RAILING TECHNOLOGY

Which profile fits your project?

NEW

TURBOFLEX® PUBLIC USE (medium crowd)

Model		Mounting type	Glass thickness	Anchor distance	Bent profile available	Page
	TF-3620	Top mount	12 - 21,52 mm	200 / 400 mm *		12
	TF-6620			200 / 400 mm *	✓	16
	TF-3621	Side mount		200 / 400 mm *		22
	TF-6621			200 / 400 mm *	✓	28

TRANSLEVEL® PRIVATE / PARTITION USE

Model		Mounting type	Glass thickness	Anchor distance	Bent profile available	Page
	TL-6500	Top mount	10 - 17,52 mm	250 mm	✓	70
	TL-6501	Side mount		250 mm	✓	102

TRANSLEVEL® PUBLIC USE (medium crowd)

Model		Mounting type	Glass thickness	Anchor distance	Bent profile available	Page
	TL-3010	Top mount	12 - 21,52 mm	360 mm		34
	TL-3080			200 mm		38
	TL-3120			360 mm		42
	TL-4010			200 / 400 mm *		46
	TL-5010			3 in 2,5 m		50
	TL-6020			200 / 400 mm *	✓	58
	TL-6080			250 mm		66
	TL-3011	Side mount		370 mm	✓	74
	TL-3121			250 mm		84
	TL-6021			200 / 400 mm *	✓	90
	TL-6081			250 mm		96
	TL-1010	In floor				108

TRANSLEVEL® PUBLIC USE (large crowd)

Model		Mounting type	Glass thickness	Anchor distance	Bent profile available	Page
	TL-6030	Top mount	21,52 - 31,52 mm	100 mm		62
	TL-3031	Side mount		250 mm		80

* Final anchor distance depending on use case (see proof of conformity).

1. FULL GLASS BALUSTRADES — 9

Glass-supporting components

Profiles | parts – TURBOFLEX® NEW — 9
Top mount
Side mount

Profiles | parts – TRANSLEVEL® — 33
Top mount
Side mount
In floor mount

Point fixings — 114

Connection profiles — 122
Top Cover
Floor connect

Glass components

Glass edge protection — 130

Handrail components

U-profiles | parts — 134
Mounted on top of glass
Mounted against glass or wall

U-profiles with led | parts – LAZORTRACK® — 146
Mounted on top of glass
Mounted against glass or wall

Handrail tubes | parts — 152

Accessories | additionals — 155

2. POST GLASS BALUSTRADES — 174

Glass-supporting components

Posts | parts – GUARDIAN OF THE UNIVERSE® — 174
Top mount
Side mount

Glass components

Glass edge protection — 188

Handrail components

Handrails | parts — 190

Accessories | additionals 194

Mounting examples 198

3. GLASS WALLS 200

Glass-supporting components

Profiles | parts – KAZIWALL® 200
KAZIWALL Top
KAZIWALL Side

Accessories | additionals 205

4. JULIET BALCONIES 208

Glass-supporting components

Profile sets – SKYFORCE® 208
SKYFORCE Top
SKYFORCE Slim
SKYFORCE Side

Mounting examples 221

Glass components

Glass edge protection 231

Accessories | additionals 233

5. GLASS CANOPY 236

Glass-supporting components

System – AIRFORCE® 236

Accessories | additionals 239

Mounting examples 241

6. GENERAL TERMS AND CONDITIONS 247

Standard finishes and colours

ONLEVEL surface finish codes

ALUMINIUM

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL*



Your preferred colour?
We will of course deliver your desired RAL colour.



.10 Aluminium mill finish



.11 Aluminium anodised


*Pre-anodising before the profiles are coated.



.13 RAL glossy



.16 RAL structured matt



.18 RAL matt



.19 Armor RAL*

STAINLESS STEEL

10.2030.200.**21** → **.21** AISI 304 brushed
10.2030.200.**31** → **.31** AISI 316 brushed



.21 AISI 304 brushed



.31 AISI 316 brushed

Powder coated profiles (.13/.16/.18/.19) Warranty: The current ONLEVEL General Warranty Conditions apply. Please refer to these conditions for the applicable warranty periods.

1

FULL GLASS BALUSTRADES

Profiles | parts

TURBOFLEX®

ONLEVEL

ADVANCED RAILING TECHNOLOGY


STEP ON
THE GAS IN
MOUNTING
GLASS
NEW
CONCEPT
TURBOFLEX
Watch installation video

TURBOFLEX

GLASS FIXATION ADJUSTS
TO THE GLASS POSITION

Key benefits at a glance:

1. **Completely new concept:** The glass is adjusted exactly where needed – directly at the glass! This ensures instant precision and saves time.
2. **No subsequent corrections:** Installation takes approximately half the time of conventional systems. A true efficient booster for any construction site.
3. **Perfect alignment:** TURBOFLEX® allows for precise horizontal adjustment as well as secure vertical stability – for an absolutely stable result.
4. **Optimal tolerance compensation:** Whether minor deviations or major differences – TURBOFLEX perfectly compensates for all glass production tolerances.
5. **Safe installation:** The entire installation is done from the user side, ensuring maximum safety and eliminating scaffold or powered access costs.
6. **Precise fit:** The glass pivot point in TURBOFLEX lies directly beneath the rubber gaskets, ensuring a seamless fit – even with varying glass angles.
7. **Maximum safety:** TURBOFLEX uses stainless steel components for glass fixation, ensuring extremely high tested safety and stability.
8. **Full-surface glass clamping:** The contact surfaces follow the glass angle, avoiding stress concentrations and ensuring functionality even under high loads.
9. **Optional:** The height adjuster allows vertical glass adjustment of up to 3 mm.

TURBOFLEX

HOW DOES IT WORK?

1 ADJUST THE GLASS BY HAND



2 FIX THE GLASS WEDGE



3 DONE

The glass fixing adapts to the position of the glass and is tightened.

TURBOFLEX®

TF-3620



Top mount

equipped with

TURBOFLEX®
GLASS FIXATION ADJUSTS
TO THE GLASS POSITION

ENGINEERED IN GERMANY

Top mount | **TF-3620** – Public use (medium crowd)

TURBOFLEX is an innovative glass railing system engineered to accelerate installation while ensuring uncompromised safety, precise alignment, and refined aesthetics. It overturns the conventional method: instead of adjusting the fixation to suit the glass, TURBOFLEX adapts directly to the glass itself –at the point of contact.

TF-3620 has been specifically developed for top mounted installations and can be easily secured to concrete, especially at floor edges, creating additional valuable terrace space. Thanks to its intelligent design, installation is completed quickly and with perfect alignment in just a few steps. The result is not only visually impressive but also reliably meets all technical requirements.

Essential features


- Slim, elegant design and low maintenance
- Uses TURBOFLEX mounting technology
- Extension pin location holes
- Built-in drainage
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknessess 12-21,52 mm
- Easy installation with the TURBOFLEX Torque Tool
- Align glass by hand
- Screw fastening
- Available in 2,5 and 5 m


Country-specific approvals for TF-3620


Region		Line load	Certification / calculated / tested / pending
	CH	0,8 kN/m	SIA261 calculated
	DE	1,0 kN/m	AbP / DIN18008 calculated
	FR	1,0 kN/m	AVIS Technique pending / CCFAT tested
	NL	1,0 kN/m	NEN2608 calculated
	UK	1,50 kN/m	BS6180 tested
World wide:			On request


Watch Installation Video:

Online manual: Model TF-3620









In some use cases mounting distances of 400 mm are allowed (see calculation / test report).


For details see corresponding proof of conformity documents.

Top mount | **TF-3620** – Public use (medium crowd)

Glass profile



- Length: 2,5 and 5 m
- 4 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
200 mm	13 (2,5 m) | 25 (5 m)
400 mm	7 (2,5 m) | 13 (5 m)
Anchor distances: see calculation / test report	

Model 3620	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	10.3620.002.10	10.3620.002.11	10.3620.002.13/16/18/19
5 m	10.3620.005.10	10.3620.005.11	10.3620.005.13/16/18/19

Inside corner 90°



- Side length inside 40 mm
- Side length outside 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3620	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3620.300.10	10.3620.300.11	10.3620.300.13/16/18/19

Outside corner 90°




- Side length inside 40 mm
- Side length outside 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3620	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3620.350.10	10.3620.350.11	10.3620.350.13/16/18/19

End caps



Left* Right*

- Self-adhesive
- Sales unit: 1 piece



Model 3620	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3620.400.10	10.3620.400.11	10.3620.400.13/16/18/19
Right	10.3620.450.10	10.3620.450.11	10.3620.450.13/16/18/19

*The end caps are 'left' or 'right' when viewed from outside the balcony.


Top mount | **TF-3620** – Public use (medium crowd)

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

- Outlet Ø 14 mm
- Sales unit: 13 pieces




Profile length	Number of spacers needed
2,5 m	13
5 m	25

Model 3620	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3620.500.10	10.3620.500.11	10.3620.500.13/16/18/19

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces




Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Glass mounting set



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Length: 2,5 m, 5 m and 25 m
- Pay attention to the right glass thickness!



Model 3502 / 3505 / 3525	12 mm	6/6/2 (12,76 mm)	15 mm	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	19 mm	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	90.3502.112.00	90.3502.113.00	90.3502.115.00	90.3502.117.00	90.3502.118.00	90.3502.119.00	90.3502.121.00	90.3502.122.00
5 m	90.3505.112.00	90.3505.113.00	90.3505.115.00	90.3505.117.00	90.3505.118.00	90.3505.119.00	90.3505.121.00	90.3505.122.00
25 m	90.3525.112.00	90.3525.113.00	90.3525.115.00	90.3525.117.00	90.3525.118.00	90.3525.119.00	90.3525.121.00	90.3525.122.00

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

TURBOFLEX®

TF-6620



CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

Top mount

equipped with

TURBOFLEX®
GLASS FIXATION ADJUSTS
TO THE GLASS POSITION

ENGINEERED IN GERMANY

Top mount | **TF-6620** – Public use (medium crowd)

New concept for installing frameless glass balustrades
Easily and precisely position the glass exactly where it matters - directly at the glass itself! The TURBOFLEX system allows for maximum adjustment accuracy and significantly reduces installation time.

TF-6620 has been specifically developed for top mounted installations and can be easily secured to concrete and steel substrates. Thanks to its intelligent design, installation is completed quickly and with perfect alignment in just a few steps. The result is not only visually impressive but also reliably meets all technical requirements.


Essential features
- Slim, elegant design and low maintenance
- Uses TURBOFLEX mounting technology
- Extension pin location holes
- Built-in drainage
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknessess 12-21,52 mm
- Easy installation with the TURBOFLEX Torque Tool
- Align glass by hand
- Screw fastening
- Available in 2,5 and 5 m


Country-specific approvals for TF-6620


Region		Line load	Certification / calculated / tested / pending
	CH	0,8 kN/m	SIA261 calculated
	DE	1,0 kN/m	AbP / DIN18008 calculated
	FR	1,0 kN/m	AVIS Technique pending / CCFAT tested
	NL	1,0 kN/m	NEN2608 calculated
	UK	1,50 kN/m	BS6180 tested
World wide:			On request


Watch Installation Video:

Online manual: Model TF-6620









In some use cases mounting distances of 400 mm are allowed (see calculation / test report).


For further details, see the certification/calculations (table above).

Top mount | **TF-6620** – Public use (medium crowd)

Glass profile



- Length: 2,5 and 5 m
- 4 extension pins needed per connection
- Bent version available: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
200 mm	13 (2,5 m) | 25 (5 m)
400 mm	7 (2,5 m) | 13 (5 m)
Anchor distances: see calculation / test report	

Model 6620	Mill finish	Aluminium natural anod.	Aluminum satined	RAL coloured
Length	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	10.6620.002.10	10.6620.002.11	–	10.6620.002.13/16/18/19
5 m	10.6620.005.10	10.6620.005.11	–	10.6620.005.13/16/18/19
BendFit 6 m (bent)	–	–	10.6620.006.14	

Inside corner / outside corner 90°



- Side length inside 125 mm
- Side length outside 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6620	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6620.390.10	10.6620.390.11	10.6620.390.13/16/18/19

End cap, left/right



- For use on the left and right
- Sales unit: 1 piece
- Self-adhesive




Model 6620	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left/right	10.6620.490.10	10.6620.490.11	10.6620.490.13/16/18/19

End cap for staircase, left/right




- For use on the left and right
- Can be cut to size
- Sales unit: 1 piece
- Self-adhesive



Model 6620	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left/right	10.6620.491.10	10.6620.491.11	10.6620.491.13/16/18/19

CUTTING DRILLING BENDING POWDER COATING



ONLY YOU

LESS WORK. LESS WASTE. READY TO INSTALL.

With ONLY YOU, we customize ONLEVEL products to your exact project requirements – precisely, efficiently and ready to install. From cutting and drilling to bending and powder coating, we deliver exactly what you need, reducing work and waste on site and giving you more time for what matters: installation.

HOW IT WORKS

Use **ONLEVEL Studio** to create your project configuration. We will review your configuration, check the feasibility and provide you with a quote and delivery time.

WE NEED FROM YOU

A sketch, your **ONLEVEL Studio** configuration, dimensions, quantities, finish (e.g. RAL colour) and delivery deadline.

studio.onlevel.com

FROM STANDARD PROFILE TO YOUR PROJECT-READY PRODUCT

1 → 2 → 3 → 4

1 STANDARD ONLEVEL PROFILE

High quality standard profile from our range.

2 ONLY YOU CUSTOMIZATION



CUT TO SIZE
Profiles cut to the lengths your project requires.



DRILLING
Additional or project-specific machining according to your requirements.



BENDING
Profiles shaped to suit bent and individual designs.



POWDER COATING
In the RAL colour you specify.

3 FINISHED ACCORDING TO YOUR SPECIFICATIONS

Customized, finished and checked to your specifications.

4 READY FOR INSTALLATION

Delivered ready to install. Less work on site, more time for what matters.


Top mount | **TF-6620** – Public use (medium crowd)

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

| Outlet Ø 14 mm
| Sales unit: 13 pieces




Profile length	Number of spacers needed
2,5 m	13
5 m	25

Model 6620	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6620.500.10	10.6620.500.11	10.6620.500.13/16/18/19

Extension pin



| Length 40 mm
| Diameter Ø 6 mm
| Sales unit: 8 pieces




Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Glass mounting set



| Fine adjustment of glass panes
| For glass thicknesses between 12 - 21,52 mm
| Length: 2,5 m, 5 m and 25 m
| Pay attention to the right glass thickness!



Model 3502 / 3505 / 3525	12 mm	6/6/2 (12,76 mm)	15 mm	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	19 mm	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	90.3502.112.00	90.3502.113.00	90.3502.115.00	90.3502.117.00	90.3502.118.00	90.3502.119.00	90.3502.121.00	90.3502.122.00
5 m	90.3505.112.00	90.3505.113.00	90.3505.115.00	90.3505.117.00	90.3505.118.00	90.3505.119.00	90.3505.121.00	90.3505.122.00
25 m	90.3525.112.00	90.3525.113.00	90.3525.115.00	90.3525.117.00	90.3525.118.00	90.3525.119.00	90.3525.121.00	90.3525.122.00


Optional height adjustabilty for glass panels

| See product 90.3500.100.00 on page 157



TAKE A LITTLE DISTANCE – WITH OUR SPACER.

Hoover Dam is a thing of the past. There is more water on balconies than in the legendary dammed Colorado River. We have the suitable spacer for every profile to keep your feet dry. In addition, our spacers are constructed such as to adapt themselves to all static conditions.



10.6620.500.xx



TURBOFLEX®

TF-3621



Side mount

equipped with

TURBOFLEX®
GLASS FIXATION ADJUSTS TO THE GLASS POSITION

ENGINEERED IN GERMANY

Side mount | **TF-3621** – Public use (medium crowd)

TURBOFLEX is an innovative glass railing system engineered to accelerate installation while ensuring uncompromised safety, precise alignment, and refined aesthetics. It overturns the conventional method: instead of adjusting the fixation to suit the glass, TURBOFLEX adapts directly to the glass itself—- at the point of contact

TF-3621 has been specifically developed for side-mounted installations and can be easily secured to concrete and steel substrates. Thanks to its intelligent design, installation is completed quickly and with perfect alignment in just a few steps. The result is not only visually impressive but also reliably meets all technical requirements.

Essential features


- Slim, elegant design and low maintenance
- Uses TURBOFLEX mounting technology
- Extension pin location holes
- Built-in drainage
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses 12-21,52 mm
- Easy installation with the TURBOFLEX Torque Tool
- Align glass by hand
- Screw fastening
- Available in 2,5 and 5 m

Country-specific approvals for TF-3621

Region	Line load	Certification / calculated / tested / pending
CH	0,8 kN/m	SIA261 calculated
DE	1,0 kN/m	AbP / DIN18008 calculated
FR	1,0 kN/m	AVIS Technique pending / CCFAT tested
NL	1,0 kN/m	NEN2608 calculated
UK	1,50 kN/m	BS6180 tested
World wide:		On request

Watch Installation Video:

Online manual: Model TF-3621



In some use cases mounting distances of 400 mm are allowed (see calculation / test report).


For further details, see the certification/calculations (table above).

Side mount | **TF-3621** – Public use (medium crowd)

Glass profile



- Length: 2,5 and 5 m
- 4 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
200 mm	13 (2,5 m) | 25 (5 m)
400 mm	7 (2,5 m) | 13 (5 m)
Anchor distances: see calculation / test report	

Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	10.3621.002.10	10.3621.002.11	10.3621.002.13/16/18/19
5 m	10.3621.005.10	10.3621.005.11	10.3621.005.13/16/18/19

Inside corner 90°



- Inside length 125 mm
- Outside length 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3621.300.10	10.3621.300.11	10.3621.300.13/16/18/19

Outside corner 90°



- Inside length 125 mm
- Outside length 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3621.350.10	10.3621.350.11	10.3621.350.13/16/18/19

Cover cap



- With mounting strips
- Sales unit: 1 piece



Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	10.3621.202.10	10.3621.202.11	10.3621.202.13/16/18/19
5 m	10.3621.205.10	10.3621.205.11	10.3621.205.13/16/18/19


Side mount | **TF-3621** – Public use (medium crowd)

End caps for use without cover cap


Left*


Right*

| Self-adhesive
| Sales unit: 1 piece




Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3621.400.10	10.3621.400.11	10.3621.400.13/16/18/19
Right	10.3621.450.10	10.3621.450.11	10.3621.450.13/16/18/19

End caps for use with cover cap


Left*


Right*

| Self-adhesive
| Sales unit: 1 piece




Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3621.410.10	10.3621.410.11	10.3621.410.13/16/18/19
Right	10.3621.460.10	10.3621.460.11	10.3621.460.13/16/18/19

End caps for staircase for use with cover cap


Left*


Right*

| Self-adhesive
| Cut-to-size
| Sales unit: 1 piece




Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3621.411.10	10.3621.411.11	10.3621.411.13/16/18/19
Right	10.3621.461.10	10.3621.461.11	10.3621.461.13/16/18/19

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

| Thickness: 15 mm
| Sales unit: 13 pieces



Profile length	Number of spacers needed
2,5 m	13
5 m	25

Model 3621	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3621.500.10	10.3621.500.11	10.3621.500.13/16/18/19


*The end caps are 'left' or 'right' when viewed from outside the balcony.

Side mount | **TF-3621** – Public use (medium crowd)

Extension pin



| Length 40 mm
| Diameter Ø 6 mm
| Sales unit: 8 pieces




Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Glass mounting set



| Fine adjustment of glass panes
| For glass thicknesses between 12 - 21,52 mm
| Length: 2,5 m, 5 m and 25 m
| Pay attention to the right glass thickness!



Model 3502 / 3505 / 3525	12 mm	6/6/2 (12,76 mm)	15 mm	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	19 mm	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	90.3502.112.00	90.3502.113.00	90.3502.115.00	90.3502.117.00	90.3502.118.00	90.3502.119.00	90.3502.121.00	90.3502.122.00
5 m	90.3505.112.00	90.3505.113.00	90.3505.115.00	90.3505.117.00	90.3505.118.00	90.3505.119.00	90.3505.121.00	90.3505.122.00
25 m	90.3525.112.00	90.3525.113.00	90.3525.115.00	90.3525.117.00	90.3525.118.00	90.3525.119.00	90.3525.121.00	90.3525.122.00

Optional height adjustabilty for glass panels

| See product 90.3500.100.00 on page 157



ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

ONLEVEL
STUDIO

SMART DESIGN AND ORDERING



How it works

studio.onlevel.com

PDF DXF IFC STEP

ONLEVEL Studio is our online configurator. It lets you design and organise the installation of your glass balustrade free of charge. Available 24/7, whenever it suits you best.

Design your project. Visualise it in 3D. Configure different system setups. Compare product options. Automatically calculate which materials you need and how much, as well as the total costs, including transport. Create technical drawings and quotations. And order your materials directly.

Less calculating. Fewer mistakes. More control.

ONLEVEL Studio helps you automate complex work preparation. Get from idea to installation faster.

TURBOFLEX®

TF-6621



CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

Side mount

equipped with

TURBOFLEX®
GLASS FIXATION ADJUSTS
TO THE GLASS POSITION

ENGINEERED IN GERMANY

Side mount | **TF-6621** – Public use (medium crowd)

New concept for installing frameless glass balustrades
Easily and precisely position the glass exactly where it matters - directly at the glass itself! The TURBOFLEX system allows for maximum adjustment accuracy and significantly reduces installation time.

TF-6621 has been specifically developed for side mounted installations and can be easily secured to concrete and steel substrates. Thanks to its intelligent design, installation is completed quickly and with perfect alignment in just a few steps. The result is not only visually impressive but also reliably meets all technical requirements.


Essential features
- Slim, elegant design and low maintenance
- Uses TURBOFLEX mounting technology
- Extension pin location holes
- Built-in drainage
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses 12-21,52 mm
- Easy installation with the TURBOFLEX Torque Tool
- Align glass by hand
- Screw fastening


Country-specific approvals for TF-6621


Region		Line load	Certification / calculated / tested / pending
	CH	0,8 kN/m	SIA261 calculated
	DE	1,0 kN/m	AbP / DIN18008 calculated
	FR	1,0 kN/m	AVIS Technique pending / CCFAT tested
	NL	1,0 kN/m	NEN2608 calculated
	UK	1,50 kN/m	BS6180 tested
World wide:			On request

Watch Installation Video:


Online manual: Model TF-6621







In some use cases mounting distances of 400 mm are allowed (see calculation / test report).




For further details, see the certification/calculations (table above).

Side mount | **TF-6621** – Public use (medium crowd)

Glass profile



- Length: 2,5 and 5 m
- 4 extension pins needed per connection
- Bent version available: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
200 mm	13 (2,5 m) | 25 (5 m)
400 mm	7 (2,5 m) | 13 (5 m)
Anchor distances: see calculation / test report	

	Model 6621	Mill finish	Aluminium natural anod.	Aluminum satined	RAL coloured
	Length	Art. no.	Art. no.	Art. no.	Art. no.
	2,5 m	10.6621.002.10	10.6621.002.11	–	10.6621.002.13/16/18/19
	5 m	10.6621.005.10	10.6621.005.11	–	10.6621.005.13/16/18/19
BendFit	6 m (bent)	–	–	10.6621.006.14	

Inside corner 90°



- Inside length 125 mm
- Outside length 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6621	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6621.300.10	10.6621.300.11	10.6621.300.13/16/18/19

Outside corner 90°



- Inside length 125 mm
- Outside length 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6621	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6621.350.10	10.6621.350.11	10.6621.350.13/16/18/19

Cover cap



- With mounting strips
- Sales unit: 1 piece



Model 6621	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	10.6621.202.10	10.6621.202.11	10.6621.202.13/16/18/19
5 m	10.6621.205.10	10.6621.205.11	10.6621.205.13/16/18/19

Side mount | **TF-6621** – Public use (medium crowd)

End caps for use without cover cap




Left*



Right*

| Self-adhesive
| Sales unit: 1 piece



Model 6621	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6621.400.10	10.6621.400.11	10.6621.400.13/16/18/19
Right	10.6621.450.10	10.6621.450.11	10.6621.450.13/16/18/19

End caps for use with cover cap




Left*



Right*

| Self-adhesive
| Sales unit: 1 piece



Model 6621	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6621.410.10	10.6621.410.11	10.6621.410.13/16/18/19
Right	10.6621.460.10	10.6621.460.11	10.6621.460.13/16/18/19

End caps for staircase for use with cover cap




Left*



Right*

| Cut-to-size
| Self-adhesive
| Sales unit: 1 piece



Model 6621	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6621.411.10	10.6621.411.11	10.6621.411.13/16/18/19
Right	10.6621.461.10	10.6621.461.11	10.6621.461.13/16/18/19

Optional height adjustabilty for glass panels

| See product 90.3500.100.00 on page 157



*The end caps are 'left' or 'right' when viewed from outside the balcony.


Side mount | **TF-6621** – Public use (medium crowd)

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

| Thickness: 15 mm
| Sales unit: 13 pieces




Profile length	Number of spacers needed
2,5 m	13
5 m	25

Model 6621	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6621.500.10	10.6621.500.11	10.6621.500.13/16/18/19

Extension pin



| Length 40 mm
| Diameter Ø 6 mm
| Sales unit: 8 pieces




Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Glass mounting set



| Fine adjustment of glass panes
| For glass thicknesses between 12 - 21,52 mm
| Length: 2,5 m, 5 m and 25 m
| Pay attention to the right glass thickness!



Model 3502 / 3505 / 3525	12 mm	6/6/2 (12,76 mm)	15 mm	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	19 mm	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	90.3502.112.00	90.3502.113.00	90.3502.115.00	90.3502.117.00	90.3502.118.00	90.3502.119.00	90.3502.121.00	90.3502.122.00
5 m	90.3505.112.00	90.3505.113.00	90.3505.115.00	90.3505.117.00	90.3505.118.00	90.3505.119.00	90.3505.121.00	90.3505.122.00
25 m	90.3525.112.00	90.3525.113.00	90.3525.115.00	90.3525.117.00	90.3525.118.00	90.3525.119.00	90.3525.121.00	90.3525.122.00

FULL GLASS BALUSTRADES

Profiles | parts

TRANSLEVEL®

ONLEVEL

ADVANCED RAILING TECHNOLOGY

TRANSLEVEL®

TL-3010

Small edge distance

F-shape



CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

Ideally suited for installations under screed and on the facade

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-3010** – Public use (medium crowd)

Your Choice. Our Power.


The TL-3010 F-profile is one of the most powerful glass profiles. The model is very well suited for balconies and terraces – it enables an especially small edge distance and therefore gains valuable additional space on the deck itself. Moreover, this system is ideally suited for new installations under screed. Of course, the relevant distances between drill holes have been taken into account.


Essential features


- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Drainage holes
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 12 - 21,52 mm


Country-specific approvals for TL-3010

Region		Line load	Certification / calculated / tested / pending
	CH	1,6 kN/m	SIA261 calculated
	DE	1,0 kN/m	AbP / DIN18008 calculated
	FR	1,0 kN/m	AVIS Technique / CCFAT tested
	NL	1,0 kN/m	KOMO / NEN2608 calculated
	UK	0,74 kN/m	BS6180 tested
World wide:			On request










For further details, see the certification/calculations (table above).

Top mount | **TL-3010** – Public use (medium crowd)

Glass profile



- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
360 mm	7 (2,5 m) | 14 (5 m)

Model 3010	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	10.3010.002.10	10.3010.002.11	10.3010.002.13/16/18/19
5 m	10.3010.005.10	10.3010.005.11	10.3010.005.13/16/18/19

Inside corner 90°



- Side length inside: 60 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3010	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3010.300.10	10.3010.300.11	10.3010.300.13/16/18/19

Outside corner 90°



- Side length inside: 60 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3010	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3010.350.10	10.3010.350.11	10.3010.350.13/16/18/19

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

- Inner drill hole: Ø 14 mm
- Sales unit: 7 pieces



Profile length	Number of spacers needed
2,5 m	7
5 m	14

Model 3010	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3010.500.10	10.3010.500.11	10.3010.500.13/16/18/19


Top mount | **TL-3010** – Public use (medium crowd)

End caps



Left* Right*

- Self-adhesive
- Sales unit: 1 piece




Model 3010	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3010.400.10	10.3010.400.11	10.3010.400.13/16/18/19
Right	10.3010.450.10	10.3010.450.11	10.3010.450.13/16/18/19

End caps for staircase



Left* Right*

- Self-adhesive
- Cut-to-size
- Sales unit: 1 piece



Model 3010	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3010.401.10	10.3010.401.11	10.3010.401.13/16/18/19
Right	10.3010.451.10	10.3010.451.11	10.3010.451.13/16/18/19

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!


Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

*The end caps are 'left' or 'right' when viewed from outside the balcony.

TRANSLEVEL®

TL-3080

Lightweight profile –
therefore more economic



The glass can be adjusted via the
Flex-Fit system

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-3080** – Public use (medium crowd)

Welcome to the era of lightness with the brand new Profile 3080! This piece is so light it almost floats - and it has more power than your morning coffee!
This model is the rebellious version of the popular 3010. It's not only lighter, but also cooler. The design is so fresh that it even amazes robots. And yes, we didn't just think about the outer beauty, but also about the inner values.
Specially developed to meet a wide range of requirements in the private sector:


- For fall protection indoors with a max. railing height of 1100 mm.
- The ideal solution for fall protection in private indoor areas.
- As a separating system for railings without fall protection to ensure maximum design flexibility.


Essential features


| Slimline, elegant design and low-maintenance
| FlexFit Glass Adjustment Tool
| Cover (optional)
| Extension pin channels
| Suited for Top Cover and Floor Connect connection profiles
| For glass thicknesses between 12 - 21,52 mm
| Not suitable for mounting on wood

Country-specific approvals for TL-3080

Region	Line load	Certification / calculated / tested / pending
CH		
DE	1,0 kN/m	AbP / DIN18008 calculated
FR		
NL	1,0 kN/m	NEN2608 calculated
UK		
World wide:		On request








For further details, see the certification/calculations (table above).

Top mount | **TL-3080** – Public use (medium crowd)

Glass profile



- Height: 124 mm
- Width: 120 mm
- 4 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity	Model 3080	Mill finish	Aluminium natural anodised	RAL coloured
		Length	Art. no.	Art. no.	Art. no.
200 mm	25 (5 m)	5 m	10.3080.005.10	10.3080.005.11	10.3080.005.13/16/18/19

Inside corner 90°



- Side length inside: 80 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3080	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3080.300.10	10.3080.300.11	10.3080.300.13/16/18/19

Outside corner 90°



- Side length inside: 80 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece



Model 3080	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3080.350.10	10.3080.350.11	10.3080.350.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

Top mount | **TL-3080** – Public use (medium crowd)

End caps




Left*



Right*

- Self-adhesive
- Sales unit: 1 piece




Model 3080	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3080.400.10	10.3080.400.11	10.3080.400.13/16/18/19
Right	10.3080.450.10	10.3080.450.11	10.3080.450.13/16/18/19

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

Quick & easy


For further helpful information, please see our ONLEVEL website. Here you will find explanatory and installation videos, photos and downloads, as well as a configurator to help you with the glass calculations.

*The end caps are 'left' or 'right' when viewed from outside the balcony.

TRANSLEVEL®

TL-3120

For higher floor structures
of up tp 180 mm



Hollow profile, therefore
more lightweight and
more economic

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-3120** – Public use (medium crowd)


At eye Level.
If your floor includes insulation, water heating, and or tiles, and you need a taller top-mounted glass profile to cover the full build-up height, system TL-3120 is the ideal choice.


With a profile height of 180 mm, it allows you to cover the entire floor construction in one go.

Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Cover (optional)
- Extension pin channels
- Suited for Top Cover and Floor Connect connection profiles
- Integrated multifunctional sophisticated chamber
- For higher floor structures
- For glass thicknesses between 12 - 21,52 mm

Country-specific approvals for TL-3120

Region	Line load	Certification / calculated / tested / pending
CH		
DE	1,0 kN/m	AbP / DIN18008 calculated
FR		
NL	1,0 kN/m	NEN2608 calculated
UK	0,74 kN/m	BS6180 tested
World wide:		On request






For further details, see the certification/calculations (table above).

Top mount | **TL-3120** – Public use (medium crowd)

Glass profile



- Height: 180 mm
- Width 200 mm
- Suitable for higher floor structures of up to 180 mm
- 3 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
360 mm	6 (2,5 m) | 13 (5 m)

Model 3120	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	-	10.3120.002.11	-
5 m	10.3120.005.10	10.3120.005.11	10.3120.005.13/16/18/19

Inside corner 90°



- Side length inside: 50 mm
- Side length outside: 250 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3120	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3120.300.10	10.3120.300.11	10.3120.300.13/16/18/19

Outside corner 90°



- Side length inside: 50 mm
- Side length outside: 250 mm
- 2 anchor holes
- Sales unit: 1 piece



Model 3120	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3120.350.10	10.3120.350.11	10.3120.350.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

Top mount | **TL-3120** – Public use (medium crowd)

End caps





Left*



Right*

- Self-adhesive
- Sales unit: 1 piece






Model 3120	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3120.400.10	10.3120.400.11	10.3120.400.13/16/18/19
Right	10.3120.450.10	10.3120.450.11	10.3120.450.13/16/18/19

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

*The end caps are 'left' or 'right' when viewed from outside the balcony.

TRANSLEVEL®

TL-4010

Cost reduction –
larger drilling distances

Suitable for use as
wind shield



High stability

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-4010** – Public use (medium crowd)

Innovations Connected.
With the TL-4010 profile we have created a product which is suitable for the most diverse ends. It cannot only be used as a balustrade system, but also as a wind shield or a room partition.


As a matter of fact, the profile is suited both for indoor and outdoor applications. It withstands a linear load of 1,0 kN and is suitable for glazed units with laminated safety glass made of 2 x 8 mm tempered glass and/or laminated safety glass made of 2 x 10 mm tempered glass.


Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Drainage holes
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 12 - 21,52 mm


Country-specific approvals for TL-4010

Region	Line load	Certification / calculated / tested / pending
CH		
DE	1,0 kN/m	AbP / DIN18008 calculated
FR		
NL	1,5 kN/m	NEN2608 calculated
UK	1,5 kN/m	BS6180 tested
World wide:		On request

Partition wall glazing:







In some use cases mounting distances of 400 mm are allowed (see calculation / test report).


For further details, see the certification/calculations (table above).

Top mount | **TL-4010** – Public use (medium crowd)

Glass profile



- Outdoor application
- Height: 145 mm
- Width: 120 mm
- 2 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
200 mm	25 (5 m)
400 mm	13 (5 m)
Anchor distances: see calculation / test report	

Model 4010	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	10.4010.005.10	10.4010.005.11	10.4010.005.13/16/18/19

Inside corner / outside corner 90°



- Side length inside: 80 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 4010	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.4010.390.10	10.4010.390.11	10.4010.390.13/16/18/19

End cap, left/right



- Sales unit: 1 piece
- Self-adhesive




Model 4010	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.4010.490.10	10.4010.490.11	10.4010.490.13/16/18/19

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Top mount | **TL-4010** – Public use (medium crowd)

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	**12 mm**	**6/6/2 (12,76 mm)**	**6/6/4 (13,52 mm)**	**8/8/2 (16,76 mm)**	**8/8/4 (17,52 mm)**	**10/10/2 (20,76 mm)**	**10/10/4 (21,52 mm)**
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

Quick & easy

For further helpful information, please see our ONLEVEL website. Here you will find explanatory and installation videos, photos and downloads, as well as a configurator to help you with the glass calculations.

TRANSLEVEL®

TL-5010

Ideally suited for use on insulated flat roofs

Integrated multifunctional sophisticated chamber



Only 3 fixing points required on 2,5 m

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-5010** – Public use (medium crowd)


The One and Only.
The TL-5010 glass balustrade system is ideal for installation on insulated surfaces, both on roofs and façades.


Thanks to its integrated torsion box, the system requires only three mounting posts per 2.5 metres, ensuring both strength and efficiency. The positioning of the mounting posts can be freely adjusted along the length of the profile for maximum flexibility.

Essential features
- Only 3 fixing points required on 2,5 m
- FlexFit Glass Adjustment Tool
- Extension pin holes
- Drainage holes
- Suitable for roof installation
- Integrated multifunctional sophisticated chamber
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 12 - 21,52 mm

Country-specific approvals for TL-5010

Region	Line load	Certification / calculated / tested / pending
CH		
DE	1,0 kN/m	AbP / DIN18008 calculated
FR		
NL	1,0 kN/m	KOMO / NEN2608 calculated
UK	1,50 kN/m	BS6180 tested
World wide:		On request






For further details, see the certification/calculations (table above).

Top mount | **TL-5010** – Public use (medium crowd)

Glass profile



- Height: 147 mm
- Width 65 mm
- 2 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Model 5010	Aluminium natural anodised
Length	Art. no.
5 m	10.5010.005.11

Inside corner 90°



- Side length inside: 135 mm
- Exterior side length 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 5010	Aluminium natural anodised
	Art. no.
	10.5010.300.11

Outside corner 90°



- Side length inside: 135 mm
- Exterior side length 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 5010	Aluminium natural anodised
	Art. no.
	10.5010.350.11

Posts



- Length: 300 mm
- Width 170 mm
- Required number per 2,5 m: 3 pieces
- Sales unit: 2 pieces



Model 9002	Zinc-plated steel
Height:	Art. no.
200 mm	90.9002.200.81
300 mm	90.9002.300.81


Top mount | **TL-5010** – Public use (medium crowd)

End caps



Left* Right*

| Self-adhesive
| Sales unit: 1 piece




Model 5010	Aluminium natural anodised
Application	Art. no.
Left	10.5010.400.11
Right	10.5010.450.11

Drainage cover for post



| Length: 264 mm
| Width 154 mm
| Required number per 2,5 m: 3 pieces
| Sales unit: 4 pieces




Model 9003	Zinc-plated steel (indoor)
	Art. no.
	90.9003.170.81

Mounting block.



| Length: 170 mm
| Height: 15 mm
| Width 40 mm
| M16
| Required number per 2,5 m: 3 pieces
| Sales unit: 2 pieces




Model 7004	Aluminium natural anodised
	Art. no.
	90.7004.170.11

Extension pin



| Length 40 mm
| Diameter Ø 6 mm
| Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

*The end caps are 'left' or 'right' when viewed from outside the balcony.

Top mount | **TL-5010** – Public use (medium crowd)

FlexFit glass mounting set for straight profiles





- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!


Model 0502 / 0505 / 0525	**12 mm**	**6/6/2 (12,76 mm)**	**6/6/4 (13,52 mm)**	**8/8/2 (16,76 mm)**	**8/8/4 (17,52 mm)**	**10/10/2 (20,76 mm)**	**10/10/4 (21,52 mm)**
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00


Application examples

(subject to proof of conformity)










Top mount | **TL-5010** – Public use (medium crowd)

Mounting bracket – top mount



- Dimensions: U 80 x 60 x 6 mm
- Length: 300 mm
- Sales unit: 2 pieces




Model 9006	Zinc-plated steel (indoor)
	Art. no.
	90.9006.300.81


Mounting bracket – side mount




- Dimensions: L 100 x 150 x 15 mm
- Length 210 mm
- Sales unit: 2 pieces



Model 9005	Zinc-plated steel (indoor)
	Art. no.
	90.9005.075.81






ONLEVEL
ADVANCED RAILING TECHNOLOGY

ONLEVEL GLASS STOP.

The first effective solution against glass slippage while mounting staircases

Wow...another innovative solution from ONLEVEL. So far, there was no standardised protection against glass slippage when mounting the staircase glass profiles. Until now, elaborate auxiliary devices needed to be constructed or even several installers needed to hold the glass in the profile, adjust it, protect it against slippage and fix it simultaneously.

With the glass stop, ONLEVEL has once again developed a solution to simplify installation on stairs and gradients which is simple and ingenious at a time.
Simply screw the glass stop into the profile and insert the glass. The glass can now no longer slip downwards. Depending on glass dimensions, the installation effort may be reduced by up to 80%. Less installers, increased safety and a well-conceived system behind.



PUBLIC USE (medium crowd)
90.7009.001.41

PUBLIC USE (large crowd)
90.7009.003.41





TRANSLEVEL®

TL-6020

Increased stability with the same looks



CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

Integrated multifunctional sophisticated chamber for enabling larger drilling distances

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-6020** – Public use (medium crowd)

Level Up.
The TL-6020 glass balustrade system features a simple U-shaped design, making it the most straightforward solution in our range.


It is characterised by an anchor spacing of up to 400 mm (subject to proof of conformity). The 25 mm anchor chamber height provides sufficient space to accommodate a wide variety of anchor types.


Suitable for both indoor and outdoor applications, the system supports glass thicknesses ranging from 12 mm to 21,52 mm.


Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Extension pin holes
- Drainage holes
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 12 - 21,52 mm


Country-specific approvals for TL-6020

Region		Line load	Certification / calculated / tested / pending
	CH	1,6 kN/m	SIA261 calculated
	DE	1,0 kN/m	AbP / DIN18008 calculated
	FR	1,0 kN/m	AVIS Technique / CCFAT tested
	NL	1,5 kN/m	NEN2608 calculated
	UK	1,5 kN/m	BS6180 tested
World wide:			On request










In some use cases mounting distances of 400 mm are allowed (see proof of conformity for more information).


For further details, see the certification/calculations (table above).

Top mount | **TL-6020** – Public use (medium crowd)

Glass profile



- Height: 140 mm
- Width 60 mm
- 4 extension pins needed per connection
- Bent version available: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
200 mm	25 (5 m)
400 mm	13 (5 m)
Anchor distances: see calculation / test report	

	Model 6020	Mill finish	Aluminium natural anod.	Aluminum satined	RAL coloured
	Length	Art. no.	Art. no.	Art. no.	Art. no.
	2,5 m	10.6020.002.10	10.6020.002.11	–	10.6020.002.13/16/18/19
	5 m	10.6020.005.10	10.6020.005.11	–	10.6020.005.13/16/18/19
BendFit	6 m (bent)	–	–	10.6020.006.14	

Inside corner / outside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6020	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6020.390.10	10.6020.390.11	10.6020.390.13/16/18/19

End cap, left/right



- For use on the left and right
- Sales unit: 1 piece
- Self-adhesive



Model 6020	Mill finish	Aluminium natural anodised	RAL coloured
Application	Art. no.	Art. no.	Art. no.
left/right	10.6020.490.10	10.6020.490.11	10.6020.490.13/16/18/19

End cap for staircase, left/right



- For use on the left and right
- cut-to-size
- Sales unit: 1 piece
- Self-adhesive



Model 6020	Mill finish	Aluminium natural anodised	RAL coloured
Application	Art. no.	Art. no.	Art. no.
left/right	10.6020.491.10	10.6020.491.11	10.6020.491.13/16/18/19


Top mount | **TL-6020** – Public use (medium crowd)

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

- Inner drill hole: Ø 14 mm
- Sales unit: 13 pieces




Profile length	Number of spacers needed
2,5 m	13
5 m	25

Model 6020	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6020.500.10	10.6020.500.11	10.6020.500.13/16/18/19

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

BendFit glass mounting set for bent profiles



- For glass thicknesses between 12 - 21,52 mm
- Minimum radius 1,5 m

Model 0202/0205	5 m
Glass thickness	Art. no.
12 - 13,5 mm	90.0205.112.00
15 - 17,5 mm	90.0205.116.00
19 - 21,5 mm	90.0205.120.00

TRANSLEVEL®

TL-6030

Unlimited application versatility



Especially for applications in the public area

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-6030** – Public use (large crowd)


Fat Sister.
When it comes to top-mounted glass balustrades in large crowd public environments such as train stations and football stadiums, the TL-6030 delivers uncompromising performance.


Engineered for maximum strength and reliability, this system is perfectly suited for both indoor and outdoor applications. It supports glass thicknesses from 21,52 mm up to 31,52 mm, providing the safety, durability, and confidence required in the most demanding settings.


Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Drainage holes
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 21,52 - 31,52 mm
- For applications in the public area with large crowd

Country-specific approvals for TL-6030

Region	Line load	Certification / calculated / tested / pending
CH		
DE	2,0 kN/m	AbP / DIN18008 calculated
FR	3,0 kN/m	AVIS Technique / CCFAT tested
NL	3,0 kN/m	KOMO / NEN2608 calculated
UK	3,0 kN/m	BS6180 tested
World wide:		On request








For further details, see the certification/calculations (table above).

Top mount | **TL-6030** – Public use (large crowd)

Glass profile



- Height: 125 mm
- Width 69 mm
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
100 mm	25 (2,5 m)

Model 6030	Aluminium natural anodised
Length	Art. no.
2,5 m	10.6030.002.11

Inside corner / outside corner 90°



- Side length inside: 131 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6030	Aluminium natural anodised
	Art. no.
	10.6030.390.11

End cap, left/right



- For use on the left and right
- Sales unit: 1 piece
- Self-adhesive



Model 6030	Aluminium natural anodised
Application	Art. no.
left/right	10.6030.490.11

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 21,52 - 31,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502	10/10/4 (21,52 mm)	12/12/4 (25,52 mm)	15/15/4 (31,52 mm)
Wedge colour	Blue	Red	Green
Length	Art. no.	Art. no.	Art. no.
2,5 m	90.0502.322.00	90.0502.326.00	90.0502.332.00

PERFECT FIT.
PERFECT PRICE.

FLEXFIT is the perfect system for the fine adjustment of glass panes. With FLEXFIT you can adjust any glass pane individually while positioning it up to 34 mm in relation to the vertical axis.

Ready.
With only one simple sliding movement, you can adjust the glass that precisely that 30% less mounting time is required.
FLEXFIT is optionally available in all TRANSLEVEL® glass support profiles for thicknesses between 12 mm and 31,52 mm.

Steady.
Standard systems often require installation on both the fall and the balcony sides. FLEXFIT can be handled exclusively from the balcony side. This applies for the entire installation process, by the way, which is not only much safer but also saves you unnecessary expenditures for a scaffold or lifting platform.


Go.
ONLEVEL has developed the practical FLEXFIT system for quickly and perfectly adjusting glass panels: With one single move of your hand, you can adjust the glass with millimetric precision.



Installation only from the balcony side

For glass thicknesses between 12 mm and 31,52 mm

Saves 30% of installation time



		Glass height 1000 mm	Glass height 1100 mm	Glass height 1200 mm
Glass thickness	**Angle**	**Adjustment**	**Adjustment**	**Adjustment**
12 mm	3,2°	28 mm	30 mm	34 mm
12,76 mm (6/6/2)	3,2°	28 mm	30 mm	34 mm
13,52 mm (6/6/4)	3,2°	28 mm	30 mm	34 mm
15 mm	3,2°	28 mm	30 mm	34 mm
16,76 mm (8/8/2)	2,0°	28 mm	30 mm	34 mm
17,52 mm (8(8/4)	3,2°	28 mm	30 mm	34 mm
19 mm	2,0°	18 mm	20 mm	22 mm
20,76 mm (10/10/2)	2,0°	18 mm	20 mm	22 mm
21,52 mm (10/10/4)	2,0° / 3,2°	18 / 28 mm	20 / 30 mm	22 / 34 mm
25,52 mm (12/12/4)	3,2°	28 mm	30 mm	34 mm
31,52 (15/15/4)	2,0°	18 mm	20 mm	22 mm

TRANSLEVEL®

TL-6080

Extra low profile height
of only 125 mm



CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

Hollow profile, therefore
more lightweight and more
economic

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-6080** – Public use (medium crowd)

Glass profile on diet.
For projects with lower load requirements, the TL-6080 glass balustrade system offers a smart, cost-efficient alternative to the larger TL-6020—without compromising on quality.


Lightweight, versatile, and easy to install, the TL-6080 is perfectly suited for indoor applications where wind loads are not a factor, as well as outdoor situations with reduced wind loads. Its 14 mm anchor chamber height provides flexibility to accommodate a wide range of anchor types.


Designed to support glass thicknesses from 12 mm up to 21,52 mm, the TL-6080 delivers an ideal balance of efficiency, reliability, and value for modern projects.

Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Extension pin holes
- Suited for Top Cover and Floor Connect connection profiles
- Extra low profile height of only 125 mm
- For glass thicknesses between 12 - 21,52 mm

Country-specific approvals for TL-6080

Region	Line load	Certification / calculated / tested / pending
CH		
DE	1,0 kN/m	AbP / DIN18008 calculated
FR	0,6 kN/m	AVIS Technique pending / CCFAT tested
NL	1,0 kN/m	NEN2608 calculated
UK		
World wide:		On request






For further details, see the certification/calculations (table above).

Top mount | **TL-6080** – Public use (medium crowd)

Glass profile



- Height: 125 mm
- Width: 60 mm
- 2 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
250 mm	10 (2,5 m) | 20 (5 m)

Model 6080	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	10.6080.002.10	10.6080.002.11	10.6080.002.13/16/18/19
5 m	10.6080.005.10	10.6080.005.11	10.6080.005.13/16/18/19

Inside corner / outside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6080	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6080.390.10	10.6080.390.11	10.6080.390.13/16/18/19

End cap, left/right



- For use on the left and right
- Sales unit: 1 piece
- Self-adhesive




Model 6080	Mill finish	Aluminium natural anodised	RAL coloured
Application	Art. no.	Art. no.	Art. no.
left/right	10.6080.490.10	10.6080.490.11	10.6080.490.13/16/18/19

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

- Inner drill hole: Ø 14 mm
- Sales unit: 10 pieces



Profile length	Number of spacers needed
2,5 m	10
5 m	20


Model 6080	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6080.500.10	10.6080.500.11	10.6020.800.13/16/18/19

Top mount | **TL-6080** – Public use (medium crowd)

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

TRANSLEVEL®

TL-6500

Optimally suited for
concrete upstand

Top Cover and
Floor Connect Slim



Profile dimensions:
85 x 42 mm

Top mount

ENGINEERED IN GERMANY

Top mount | **TL-6500** – Private / partition use


The attika model.
The TL-6500 system offers a sleek, space-efficient solution with its ultra-compact design—just 85 mm in height and 42 mm in width. It is specifically engineered for applications where the full structural performance of a glass balustrade is not required, making it ideal for reduced-height installations such as glass walls mounted on an upstand.


Designed with versatility in mind, the profile accommodates glass thicknesses ranging from 10 mm to 17,52 mm, ensuring flexibility across a wide range of project requirements.


Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Extension pin channel
- Drainage holes
- Optimally suited for concrete upstand
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 10 - 17,52 mm

Country-specific approvals for TL-6500

Region		Line load	Certification / calculated / tested / pending
	CH		
	DE	0,5 kN/m	AbP / DIN18008 calculated
	FR	0,6 kN/m	AVIS Technique / CCFAT tested
	NL	0,5 kN/m	NEN2608 calculated
	UK	0,74 kN/m	BS6180 tested
World wide:			On request








For further details, see the certification/calculations (table above).

Top mount | **TL-6500** – Private / partition use

Glass profile



- Height: 85 mm
- Width 42 mm
- 2 extension pins needed per connection
- Bent version available: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
250 mm	20 (5 m)

	Model 6500	Mill finish	Aluminium natural anod.	Aluminum satined	RAL coloured
	Length	Art. no.	Art. no.	Art. no.	Art. no.
	5 m	10.6500.005.10	10.6500.005.11	–	10.6500.005.13/16/18/19
BendFit	6 m (bent)	–	–	10.6500.006.14	

Inside corner / outside corner 90°



- Side length inside: 158 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6500	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6500.390.10	10.6500.390.11	10.6500.390.13/16/18/19

End cap, left/right



- For use on the left and right
- Sales unit: 1 piece
- Self-adhesive




Model 6500	Mill finish	Aluminium natural anodised	RAL coloured
Application	Art. no.	Art. no.	Art. no.
left/right	10.6500.490.10	10.6500.490.11	10.6500.490.13/16/18/19

Extension pin



- Length 40 mm
- Diameter Ø 4 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.440.31

Top mount | **TL-6500** – Private / partition use

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 10 - 17,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	**10 mm**	**5/5/2 (10,76 mm)**	**12 mm**	**6/6/2 (12,76 mm)**	**8/8/2 (16,76 mm)**	**8/8/4 (17,52 mm)**
Wedge colour	Black	Black	Black	Red	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.0505.010.00	90.0505.011.00	90.0505.012.00	90.0505.013.00	90.0505.017.00	90.0505.018.00

BendFit glass mounting set for bent profiles



- For glass thicknesses between 12 - 21,52 mm
- Minimum radius 1,5 m

Model 0202/0205	**5 m**
Glass thickness	Art. no.
12,76 - 13,52 mm	90.0205.012.00
16,76 - 17,52 mm	90.0205.016.00

BendFit

Features of bent profiles

- Minimum radius 1,5 m, smaller radii on request
- Bend loss 500 mm on each end
- Profiles can also be used for your own bending procedure

ONLEVEL has a range of special accessories available for bent profiles. You can find them on page 168.

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

TRANSLEVEL®

TL-3011

Enables concealed application



CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

Side mount

ENGINEERED IN GERMANY

Side mount | **TL-3011** – Public use (medium crowd)


Intelligent Advantage.
The TL-3011 system - one of many intelligent applications by ONLEVEL which brings nothing but benefits. The integrated height adjustment of the profile make the installation child's play.


The system is suited both for interior and exterior applications and can hold glass thicknesseses from 12 mm up to 21,52 mm.


Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Extension pin holes
- Drainage holes
- Suited for Top Cover and Floor Connect connection profiles
- Partial cover caps (optional)
- For glass thicknesses between 12 - 21,52 mm
- Height adjustable with mounting block


Country-specific approvals for TL-3011

Region		Line load	Certification / calculated / tested / pending
	CH	1,6 kN/m	SIA261 calculated
	DE	1,0 kN/m	AbP / DIN18008 calculated
	FR	1,0 kN/m	AVIS Technique / CCFAT tested
	NL	1,0 kN/m	KOMO / NEN2608 calculated
	UK	0,74 kN/m	BS6180 tested
World wide:			On request










For further details, see the certification/calculations (table above).

Side mount | **TL-3011** – Public use (medium crowd)

Glass profile



- Height: 208 mm
- Width 50 mm
- 1 extension pin needed per connection
- Bent version available: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity		Model 3011	Mill finish	Aluminium natural anod.	Aluminum satined	RAL coloured
			Length	Art. no.	Art. no.	Art. no.	Art. no.
			2,5 m	-	10.3011.002.11	–	–
			5 m	10.3011.005.10	10.3011.005.11	–	10.3011.005.13/16/18/19
370 mm	7 (2,5 m) | 14 (5 m)	BendFit	6 m (bent)	–	–	10.3011.006.14	

Inside corner 90°



- Side length inside: 150 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3011	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3011.300.10	10.3011.300.11	10.3011.300.13/16/18/19

Outside corner 90°



- Side length inside: 150 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3011	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3011.350.10	10.3011.350.11	10.3011.350.13/16/18/19

Lower part cover cap



- Sales unit: 1 piece




Model 3011	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	-	10.3011.202.11	-
5 m	10.3011.205.10	10.3011.205.11	10.3011.205.13/16/18/19

Side mount | **TL-3011** – Public use (medium crowd)

Full height cover cap



| Heigth: 216 mm
| Sales unit: 1 piece



Model 3011	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	-	10.3011.212.11	-
5 m	10.3011.215.10	10.3011.215.11	10.3011.215.13/16/18/19

End caps for lower cover cap





Left



Right

| Self-adhesive
| Sales unit: 1 piece





Model 3011	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3011.410.10	10.3011.410.11	10.3011.410.13/16/18/19
Right	10.3011.460.10	10.3011.460.11	10.3011.460.13/16/18/19

End caps for high cover cap





Left



Right

| Self-adhesive
| Sales unit: 1 piece





Model 3011	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3011.415.10	10.3011.415.11	10.3011.415.13/16/18/19
Right	10.3011.465.10	10.3011.465.11	10.3011.465.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

*The end caps are 'left' or 'right' when viewed from outside the balcony.

Side mount | **TL-3011** – Public use (medium crowd)

End caps for staircase for high cover cap




Left*



Right*

- Self-adhesive
- Cut-to-size
- Sales unit: 1 piece




Model 3011	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3011.411.10	10.3011.411.11	10.3011.411.13/16/18/19
Right	10.3011.461.10	10.3011.461.11	10.3011.461.13/16/18/19

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile. Don't forget to choose 20 mm longer anchors/screws when using this spacer!

- Inner drill hole: Ø 14 mm
- Sales unit: 10 pieces




Profile length	Number of spacers needed
2,5 m	7
5 m	14

Model 3011	Aluminium natural anodised
	Art. no.
	10.3011.500.11

Mounting block



- Required number per 2,5 m: 7 pieces
- Sales unit: 8 pieces




Model 7002	Aluminium natural anodised
Inner drill hole	Art. no.
Ø 11 mm	90.7002.010.11
Ø 13 mm	90.7002.012.11

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

*The end caps are 'left' or 'right' when viewed from outside the balcony.

Side mount | **TL-3011** – Public use (medium crowd)

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	**12 mm**	**6/6/2 (12,76 mm)**	**6/6/4 (13,52 mm)**	**8/8/2 (16,76 mm)**	**8/8/4 (17,52 mm)**	**10/10/2 (20,76 mm)**	**10/10/4 (21,52 mm)**
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

BendFit glass mounting set for bent profiles



- For glass thicknesses between 12 - 21,52 mm
- Minimum radius 1,5 m

Model 0202/0205	**5 m**
Glass thickness	Art. no.
12 - 13,5 mm	90.0205.112.00
15 - 17,5 mm	90.0205.116.00
19 - 21,5 mm	90.0205.120.00

BendFit

Features of bent profiles

- Minimum radius 1,5 m, smaller radii on request
- Bend loss 500 mm on each end
- Profiles can also be used for your own bending procedure

ONLEVEL has a range of special accessories available for bent profiles. You can find them on page 168.

TRANSLEVEL®

TL-3031



For highly frequented construction projects

Side mount

ENGINEERED IN GERMANY

Side mount | **TL-3031** – Public use (large crowd)


The Power of Improvement.
The powerhouse of all-glass balustrade systems. Designed for maximum strength and reliability, this profile is the preferred choice for side-mounted glass balustrades in high-traffic environments such as train stations and football stadiums.


The TL-3031 is suitable for both indoor and outdoor applications and accommodates glass thicknesses from 21,52 mm to 31,52 mm.

Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Extension pin holes
- Drainage holes
- Suited for Top Cover and Floor Connect connection profiles
- Partial Cover Caps (optional)
- For glass thicknesses between 21,52 - 31,52 mm
- Height adjustable with mounting block

Country-specific approvals for TL-3031

Region	Line load	Certification / calculated / tested / pending
CH		
DE	2,0 kN/m	AbP / DIN18008 calculated
FR	3,0 kN/m	AVIS Technique / CCFAT tested
NL	3,0 kN/m	KOMO / NEN2608 calculated
UK	1,5 kN/m	BS6180 tested
World wide:		On request






For further details, see the certification/calculations (table above).

Side mount | **TL-3031** – Public use (large crowd)

Glass profile



- Height: 250 mm
- Width 69 mm
- 2 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
250 mm	10 (2,5 m)

Model 3031	Aluminium natural anodised
Length	Art. no.
2,5 m	10.3031.002.11

Inside corner 90°



- Side length inside: 131 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3031	Aluminium natural anodised
	Art. no.
	10.3031.300.11

Outside corner 90°



- Side length inside: 131 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3031	Aluminium natural anodised
	Art. no.
	10.3031.350.11

Cover cap



- Sales unit: 1 piece



Model 3031	Aluminium natural anodised
Length	Art. no.
2,5 m	10.3031.202.11
5 m	10.3031.205.11

Side mount | **TL-3031** – Public use (large crowd)

End caps




Left*



Right*

- Self-adhesive
- Sales unit: 1 piece






Model 3031	Aluminium natural anod.
Application	Art. no.
Left	10.3031.410.11
Right	10.3031.460.11

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces




Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Mounting block



- Required number per 2,5 m: 10 pieces
- Sales unit: 8 pieces



Model 7002	Aluminium natural anodised
Inner drill hole	Art. no.
Ø 11 mm	90.7002.010.11
Ø 13 mm	90.7002.012.11

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 21,52 - 31,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502	10/10/4 (21,52 mm)	12/12/4 (25,52 mm)	15/15/4 (31,52 mm)
Wedge colour	Blue	Red	Green
Length	Art. no.	Art. no.	Art. no.
2,5 m	90.0502.322.00	90.0502.326.00	90.0502.332.00

*The end caps are 'left' or 'right' when viewed from outside the balcony.

TRANSLEVEL®

TL-3121

For higher floor structures
of up tp 150 mm



Hollow profile, therefore
more lightweight and
more economic

Side mount

Diagonal connector as load
support

CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

ENGINEERED IN GERMANY

Side mount | **TL-3121** – Public use (medium crowd)


The higher level.
If you plan to aim even higher, the TL-3121 is the right solution for you: Thanks to its diagonal connector as load support, the TL-3121 Y-profile with its profile height of 300 mm for higher floor structures is especially suited for the lateral mounting of staircases. In addition, the TL-3121 profile can optimally conceal thicker screed or insulation layers, as well as stair steps completely.


System TL-3121 can hold glass thicknesses from 12 mm up to 21,52 mm.


Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Drainage holes
- Extension pin channels
- Suited for Top Cover and Floor Connect connection profiles
- Diagonal connector as load support
- Integrated multifunctional sophisticated chamber
- For higher floor structures and/or insulation
- For glass thicknesses between 12 - 21,52 mm

Country-specific approvals for TL-3121

Region	Line load	Certification / calculated / tested / pending
CH		
DE	1,0 kN/m	AbP / DIN18008 calculated
FR		
NL	1,0 kN/m	NEN2608 calculated
UK	0,74 kN/m	BS6180 tested
World wide:		On request








For further details, see the certification/calculations (table above).

Side mount | **TL-3121** – Public use (medium crowd)

Glass profile



- Height: 300 mm
- Width 60 mm
- Suitable for higher floor structures of up to 150 mm
- 4 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
250 mm	10 (2,5 m) | 20 (5 m)

Model 3121	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	10.3121.002.10	10.3121.002.11	10.3121.002.13/16/18/19
5 m	10.3121.005.10	10.3121.005.11	10.3121.005.13/16/18/19

Inside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3121	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3121.300.10	10.3121.300.11	10.3121.300.13/16/18/19

Outside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 3121	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.3121.350.10	10.3121.350.11	10.3121.350.13/16/18/19

Lower part cover cap



- For using the TL3121 profile in indoor fit-out applications
- For use with a cover cap, end caps must be ordered separately.
- Sales unit: 1 piece




Model 3121	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	-	10.3121.202.11	-
5 m	10.3121.205.10	10.3121.205.11	10.3121.205.13/16/18/19

Side mount | **TL-3121** – Public use (medium crowd)

Full height cover cap



- For using the TL3121 profile in outdoor applications
- For use with a cover cap, end caps must be ordered separately.
- Sales unit: 1 piece



Model 3121	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	-	10.3121.212.11	-
5 m	10.3121.215.10	10.3121.215.11	10.3121.215.13/16/18/19

End caps for lower cover cap





Left*



Right*

- Self-adhesive
- Sales unit: 1 piece





Model 3121	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3121.410.10	10.3121.410.11	10.3121.410.13/16/18/19
Right	10.3121.460.10	10.3121.460.11	10.3121.460.13/16/18/19

End caps for high cover cap




Left*



Right*

- Self-adhesive
- Sales unit: 1 piece





Model 3121	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3121.415.10	10.3121.415.11	10.3121.415.13/16/18/19
Right	10.3121.465.10	10.3121.465.11	10.3121.465.13/16/18/19

*The end caps are 'left' or 'right' when viewed from outside the balcony.


Side mount | **TL-3121** – Public use (medium crowd)

End caps for staircase for high cover cap



Left* Right*

- Self-adhesive
- Cut-to-size
- Sales unit: 1 piece




Model 3121	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.3121.411.10	10.3121.411.11	10.3121.411.13/16/18/19
Right	10.3121.461.10	10.3121.461.11	10.3121.461.13/16/18/19

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces




Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Mounting block



- Required number per 2,5 m: 10 pieces
- Sales unit: 8 pieces



Model 7022	Aluminium natural anodised
Inner drill hole	Art. no.
Ø 11 mm	90.7022.010.11
Ø 13 mm	90.7022.012.11

FlexFit glass mounting set for straight profiles




- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!


Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00


HEIGHT ADJUSTABLE MOUNTING BLOCK.

The Steady and Flexible Body.
We wouldn´t be ONLEVEL, if we didn´t work permanently for the further development of our products: We have enabled a more significant compensation of construction and mounting tolerances by taking optimum advantage of the opportunities provided by aluminium extrusions.
Therefore, the drill hole for fixing our glass support profiles does not need to be completely accurate any more, but has a tolerance of approx. 5 mm in each direction. In order to guarantee that the glass balustrade remains in place, the mounting block is equipped with teeth. In this way, a force-locked connection is achieved. Therefore always pay attention to the logo indicating the suitable application types.

Mounting block with teeth
for optimum side mount







TRANSLEVEL®

TL-6021

Improved statics

Can be anchored universally depending on the application



CARBON FOOTPRINT VERIFIED

EPD INTERNATIONAL EPD SYSTEM

Side mount

Integrated multifunctional sophisticated chamber for enabling larger drilling distances

ENGINEERED IN GERMANY

Side mount | **TL-6021** – Public use (medium crowd)


The Evolution Goes On.
The TL-6021 U-profile features increased fixing distances, allowing the profile to be installed using anchor bolts without countersunk heads. This not only makes installation significantly faster and more cost-effective but also considerably improves its structural performance.


The TL-6021 U-profile can be used for outdoor applications. It is appropriate for glass thicknesses between 12 mm and 21,52 mm.

Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Drainage holes
- Extension pin channels
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 12 - 21,52 mm
- For applications in private areas, the mounting distance amounts to 40 cm


Country-specific approvals for TL-6021


Region		Line load	Certification / calculated / tested / pending
	CH	1,6 kN/m	SIA261 calculated
	DE	1,0 kN/m	AbP / DIN18008 calculated
	FR	1,0 kN/m	AVIS Technique / CCFAT tested
	NL	1,5 kN/m	NEN2608 calculated
	UK	1,5 kN/m	BS6180 tested
World wide:			On request





In some use cases mounting distances of 400 mm are allowed (see calculation / test report).







For further details, see the certification/calculations (table above).

Side mount | **TL-6021** – Public use (medium crowd)

Glass profile



- Height: 140 mm
- Width 60 mm
- 4 extension pins needed per connection
- Bent version available: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
200 mm	13 (2,5 m) | 25 (5 m)
400 mm	7 (2,5 m) | 13 (5 m)
Anchor distances: see calculation / test report	

	Model 6021	Mill finish	Aluminium natural anod.	Aluminum satined	RAL coloured
	Length	Art. no.	Art. no.	Art. no.	Art. no.
	2,5 m	-	10.6021.002.11	–	–
	5 m	10.6021.005.10	10.6021.005.11	–	10.6021.005.13/16/18/19
BendFit	6 m (bent)	–	–	10.6021.006.14	

Inside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6021	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6021.300.10	10.6021.300.11	10.6021.300.13/16/18/19

Outside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6021	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6021.350.10	10.6021.350.11	10.6021.350.13/16/18/19

Cover cap



- With mounting strips
- For use with a cover cap, end caps must be ordered separately
- Sales unit: 1 piece



Model 6021	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	-	10.6021.202.11	-
5 m	10.6021.205.10	10.6021.205.11	10.6021.205.13/16/18/19


Side mount | **TL-6021** – Public use (medium crowd)

End caps for use without cover cap



Left* Right*

- Self-adhesive
- Sales unit: 1 piece




Model 6021	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6021.400.10	10.6021.400.11	10.6021.400.13/16/18/19
Right	10.6021.450.10	10.6021.450.11	10.6021.450.13/16/18/19

End caps for use with cover cap



Left* Right*

- Self-adhesive
- Sales unit: 1 piece




Model 6021	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6021.410.10	10.6021.410.11	10.6021.410.13/16/18/19
Right	10.6021.460.10	10.6021.460.11	10.6021.460.13/16/18/19

End caps for staircase for use with cover cap



Left* Right*

- Cut-to-size
- Self-adhesive
- Sales unit: 1 piece



Model 6021	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6021.411.10	10.6021.411.11	10.6021.411.13/16/18/19
Right	10.6021.461.10	10.6021.461.11	10.6021.461.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

*The end caps are 'left' or 'right' when viewed from outside the balcony.


Side mount | **TL-6021** – Public use (medium crowd)

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile.Don't forget to choose 20 mm longer anchors/screws when using this spacer!

- Thickness: 15 mm
- Sales unit: 13 pieces




Profile length	Number of spacers needed
2,5 m	13
5 m	25

Model 6021	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6021.500.10	10.6021.500.11	10.6021.500.13/16/18/19

Blanking plug



- Required number per 2,5 m: 17 pieces
- Sales unit: 10 pieces




Model 7000		Plastic
Colour	Diameter	Art. no.
white	30 mm	90.7000.030.40
black	30 mm	90.7000.030.41
grey	30 mm	90.7000.030.45

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

Side mount | **TL-6021** – Public use (medium crowd)

BendFit glass mounting set for bent profiles



| For glass thicknesses between 12 - 21,52 mm
| Minimum radius 1,5 m

Model 0202/0205	**5 m**
Glass thickness	Art. no.
12 - 13,5 mm	90.0205.112.00
15 - 17,5 mm	90.0205.116.00
19 - 21,5 mm	90.0205.120.00

BendFit

Features of bent profiles

| Minimum radius 1,5 m, smaller radii on request
| Bend loss 500 mm on each end
| Profiles can also be used for your own bending procedure

ONLEVEL has a range of special accessories available for bent profiles. You can find them on page 168.

TRANSLEVEL®

TL-6081



Side mount

ENGINEERED IN GERMANY

Side mount | **TL-6081** – Public use (medium crowd)


Glass profile with slim hips.
The TL-6081 U-profile is the intelligent onward development of the TL-6021 Profile. It is much slimmer and stands out due to its extra low profile height of only 125 mm. What is so special about it is the fact that the mounting distances have been increased. That makes the product much faster and cheaper to mount.


As a matter of fact, the profile is suited both for interior and exterio applications. It can hold glass thicknesses between 12 mm and 21,52 mm.

Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Drainage holes
- Extension pin channels
- Suited for Top Cover and Floor Connect connection profiles
- Extra low profile height of only 125 mm
- For glass thicknesses between 12 - 21,52 mm

Country-specific approvals for TL-6081

Region	Line load	Certification / calculated / tested / pending
CH		
DE	1,0 kN/m	AbP / DIN18008 calculated
FR	0,6 kN/m	AVIS Technique pending / CCFAT tested
NL	1,0 kN/m	NEN2608 calculated
UK		
World wide:		On request






For further details, see the certification/calculations (table above).

Side mount | **TL-6081** – Public use (medium crowd)

Glass profile



- Height: 125 mm
- Width 60 mm
- 2 extension pins needed per connection
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity
250 mm	10 (2,5 m) | 20 (5 m)

Model 6081	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	-	10.6081.002.11	-
5 m	10.6081.005.10	10.6081.005.11	10.6081.005.13/16/18/19

Inside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6081	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6081.300.10	10.6081.300.11	10.6081.300.13/16/18/19

Outside corner 90°



- Side length inside: 140 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6081	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6081.350.10	10.6081.350.11	10.6081.350.13/16/18/19

Cover cap



- With mounting strips
- For use with a cover cap, end caps must be ordered separately.
- Sales unit: 1 piece



Model 6081	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	10.6081.205.10	10.6081.205.11	10.6081.205.13/16/18/19

Side mount | **TL-6081** – Public use (medium crowd)

End caps for use without cover cap





Left*



Right*

| Self-adhesive
| Sales unit: 1 piece





Model 6081	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6081.400.10	10.6081.400.11	10.6081.400.13/16/18/19
Right	10.6081.450.10	10.6081.450.11	10.6081.450.13/16/18/19

End caps for use with cover cap





Left*



Right*

| Self-adhesive
| Sales unit: 1 piece






Model 6081	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6081.410.10	10.6081.410.11	10.6081.410.13/16/18/19
Right	10.6081.460.10	10.6081.460.11	10.6081.460.13/16/18/19

Spacer



For additional drainage solutions on your balcony, simply mount the spacers beneath the profile.Don't forget to choose 20 mm longer anchors/screws when using this spacer!

| Thickness: 15 mm
| Sales unit: 13 pieces



Profile length	Number of spacers needed
2,5 m	10
5 m	20

Model 6081	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6081.500.10	10.6081.500.11	10.6081.500.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.


*The end caps are 'left' or 'right' when viewed from outside the balcony.

Side mount | **TL-6081** – Public use (medium crowd)

Blanking plug



- Required number per 5 m: 20 pieces
- Sales unit: 10 pieces




Model 7000	Plastic
Colour	Diameter	Art. no.
white	30 mm	90.7000.030.40
black	30 mm	90.7000.030.41
grey	30 mm	90.7000.030.45

Extension pin



- Length 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

Quick & easy


For further helpful information, please see our ONLEVEL website. Here you will find explanatory and installation videos, photos and downloads, as well as a configurator to help you with the glass calculations.

DRAINAGE – BUT NOT A RAIN GUTTER.

If water and cold combine, this can lead to problems when using all-glass balustrades. For this purpose, all ONLEVEL glass support profiles are equipped with drainage holes with a distance of 1000 mm between each of them. And we wouldn´t be ONLEVEL, if we hadn´t thought of all sorts of situations. Depending on the season, the balustrade can be subject to the most different influences (e.g.: leaves, sand, dirt).

We offer the only profile of this kind on the market.

ONLEVEL has paid special attention to ensure that the pivot point of the glass is on the same level as the rubber seals – therefore the rubber seals are never directly subjected to an increased or decreased load. As a result, dirt affects the balustrade much less.








TRANSLEVEL®

TL-6501



Side mount

ENGINEERED IN GERMANY

Side mount | **TL-6501** – Private / partition use


The side mounting model.
The TL-6501 is the counterpart to the TL-6500 for side mounting for parapet walls. With its height of 85 mm, it also has model dimensions and is predestined for glass thicknesses between 10 and 17,52 mm in 0,5 kN applications.


The slimline profile is optimally suited for concrete upstand and is equipped with an extension pin channel and drainage holes.


Essential features
- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Extension pin channels
- Drainage holes
- Optimally suited for concrete upstand
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 10 - 17,52 mm

Country-specific approvals for TL-6501

Region	Line load	Certification / calculated / tested / pending
CH		
DE	0,5 kN/m	AbP / DIN18008 calculated
FR	0,6 kN/m	AVIS Technique / CCFAT tested
NL	0,5 kN/m	NEN2608 calculated
UK	0,74 kN/m	BS6180 tested
World wide:		On request








For further details, see the certification/calculations (table above).

Side mount | **TL-6501** – Private / partition use

Glass profile



- Height: 80 mm
- Width 47 mm
- 3 extension pins needed per connection
- Bent version available: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Fitted with dewatering holes
- Sales unit: 1 piece




Anchor distance	Anchor quantity		Model 6501	Mill finish	Aluminium natural anod.	Aluminum satined	RAL coloured
			Length	Art. no.	Art. no.	Art. no.	Art. no.
			5 m	10.6501.005.10	10.6501.005.11	–	10.6501.005.13/16/18/19
250 mm	120 (5 m)	BendFit	6 m (bent)	–	–	10.6501.006.14	

Inside corner 90°



- Side length inside: 153 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6501	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6501.300.10	10.6501.300.11	10.6501.300.13/16/18/19

Outside corner 90°



- Side length inside: 153 mm
- Side length outside: 200 mm
- 2 anchor holes
- Sales unit: 1 piece




Model 6501	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	10.6501.350.10	10.6501.350.11	10.6501.350.13/16/18/19

Cover cap



- With mounting strips
- For use with a cover cap, end caps must be ordered separately.
- Sales unit: 1 piece



Model 6501	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	10.6501.205.10	10.6501.205.11	10.6501.205.13/16/18/19

Side mount | **TL-6501** – Private / partition use

End caps for use without cover cap




Left*



Right*

| Self-adhesive
| Sales unit: 1 piece



Model 6501	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6501.400.10	10.6501.400.11	10.6501.400.13/16/18/19
Right	10.6501.450.10	10.6501.450.11	10.6501.450.13/16/18/19

End caps for use with cover cap




Left*



Right*

| Self-adhesive
| Sales unit: 1 piece




Model 6501	Mill finish	Aluminium natural anod.	RAL coloured
Application	Art. no.	Art. no.	Art. no.
Left	10.6501.410.10	10.6501.410.11	10.6501.410.13/16/18/19
Right	10.6501.460.10	10.6501.460.11	10.6501.460.13/16/18/19

Extension pin



| Length 40 mm
| Diameter Ø 4 mm
| Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.440.31

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

*The end caps are 'left' or 'right' when viewed from outside the balcony.

Side mount | **TL-6501** – Private / partition use

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 10 - 17,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	**10 mm**	**5/5/2 (10,76 mm)**	**12 mm**	**6/6/2 (12,76 mm)**	**8/8/2 (16,76 mm)**	**8/8/4 (17,52 mm)**
Wedge colour	Black	Black	Black	Red	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.0505.010.00	90.0505.011.00	90.0505.012.00	90.0505.013.00	90.0505.017.00	90.0505.018.00

BendFit glass mounting set for bent profiles



- For glass thicknesses between 12 - 21,52 mm
- Minimum radius 1,5 m

Model 0202/0205	**5 m**
Glass thickness	Art. no.
12,76 - 13,52 mm	90.0205.012.00
16,76 - 17,52 mm	90.0205.016.00


BendFit

Features of bent profiles

- Minimum radius 1,5 m, smaller radii on request
- Bend loss 500 mm on each end
- Profiles can also be used for your own bending procedure

ONLEVEL has a range of special accessories available for bent profiles. You can find them on page 168.

CUTTING DRILLING BENDING POWDER COATING



ONLY YOU

LESS WORK. LESS WASTE. READY TO INSTALL.

With ONLY YOU, we customize ONLEVEL products to your exact project requirements – precisely, efficiently and ready to install. From cutting and drilling to bending and powder coating, we deliver exactly what you need, reducing work and waste on site and giving you more time for what matters: installation.

HOW IT WORKS

Use **ONLEVEL Studio** to create your project configuration. We will review your configuration, check the feasibility and provide you with a quote and delivery time.

WE NEED FROM YOU

A sketch, your **ONLEVEL Studio** configuration, dimensions, quantities, finish (e.g. RAL colour) and delivery deadline.

studio.onlevel.com

FROM STANDARD PROFILE TO YOUR PROJECT-READY PRODUCT

1 → 2 → 3 → 4

1 STANDARD ONLEVEL PROFILE

High quality standard profile from our range.

2 ONLY YOU CUSTOMIZATION



CUT TO SIZE
Profiles cut to the lengths your project requires.



DRILLING
Additional or project-specific machining according to your requirements.



BENDING
Profiles shaped to suit bent and individual designs.



POWDER COATING
In the RAL colour you specify.

3 FINISHED ACCORDING TO YOUR SPECIFICATIONS

Customized, finished and checked to your specifications.

4 READY FOR INSTALLATION

Delivered ready to install. Less work on site, more time for what matters.

TRANSLEVEL®

TL-1010



ENGINEERED IN GERMANY

In floor mount | **TL-1010** – Public use (medium crowd)

Are you looking for a glass balustrade without a visible bottom profile? Profile TL-1010 makes this possible.

Unlike other profiles in our range, TL-1010 is designed to be cast directly into the concrete floor, creating a seamless and minimalist finish. It can be used in both prefabricated elements and in-situ poured floors, making it suitable for both new builds and renovation projects.


The system is complemented by a range of components, including connectors, end caps with drainage hose connections, and extension pin channels—ensuring a complete, efficient, and reliable installation.

Essential features

- Slimline, elegant design and low-maintenance
- FlexFit Glass Adjustment Tool
- Extension pin channels
- With integrated drainage
- Concrete casting support profile (optional)
- Suited for Top Cover and Floor Connect connection profiles
- For glass thicknesses between 12 - 21,52 mm

Country-specific approvals for TL-1010

Region	Line load	Certification / calculated / tested / pending
CH		
DE		AbP
FR		
NL	1,0 kN/m	NEN2608 calculated
UK		
World wide:		On request




For further details, see the certification/calculations (table above).

In floor mount | **TL-1010** – Public use (medium crowd)

Glass profile



- 4 extension pins needed per connection
- Sales unit: 1 piece




Model 1010	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	10.1010.005.10	10.1010.005.11	10.1010.005.13/16/18/19

Concrete casting support profile (optional)



- Please use with glass profile 10.1010.005.11 to avoid deformations
- Sales unit: 1 piece




Model 1010	Aluminium natural anodised
Length	Art. no.
5 m	10.1010.205.11

Inside corner / outside corner 90°



- Side length inside: 112.5 mm
- Side length outside: 200 mm
- Sales unit: 1 piece




Model 1010	Aluminium natural anodised
	Art. no.
	10.1010.390.11

End cap, left/right with drainage connection



- for use on the left and right
- Drainage connection Ø 19 mm
- Sales unit: 2 pieces




Model 1010	Plastic
Application	Art. no.
left/right	10.1010.490.41

In floor mount | **TL-1010** – Public use (medium crowd)

Connector with drainage outlet



- Outlet Ø 19 mm
- Sales unit: 2 pieces




Model 1010	Plastic
	Art. no.
	10.1010.790.41

Extension pin



- Length 40 mm
- Diameter Ø 5 mm
- Sales unit: 8 pieces



Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.540.31

FlexFit glass mounting set for straight profiles



- Fine adjustment of glass panes
- For glass thicknesses between 12 - 21,52 mm
- Adjustment of up to 34 mm in relation to the vertical axis - Pay attention to the right glass thickness!

Model 0502 / 0505 / 0525	12 mm	6/6/2 (12,76 mm)	6/6/4 (13,52 mm)	8/8/2 (16,76 mm)	8/8/4 (17,52 mm)	10/10/2 (20,76 mm)	10/10/4 (21,52 mm)
Wedge colour	Black	Red	Grey	Red	Green	Red	Green
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
2,5 m	–	90.0502.113.00	–	90.0502.117.00	90.0502.118.00	90.0502.121.00	90.0502.122.00
5 m	90.0505.112.00	90.0505.113.00	90.0505.114.00	90.0505.117.00	90.0505.118.00	90.0505.121.00	90.0505.122.00
25 m	–	90.0525.113.00	–	90.0525.117.00	90.0525.118.00	90.0525.121.00	90.0525.122.00

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised


10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL




See pages 8 and 19 for more information and order options.

In floor mount | **TL-1010** – Public use (medium crowd)

Prefab concrete casting (up side down)



In-situ concrete casting



In floor mount | **TL-1010** – Public use (medium crowd)



FULL GLASS BALUSTRADES

Point fixings

For simple constructions
in individual applications

Available with
different diameters



Adjustable versions
available

ENGINEERED IN GERMANY

Point fixings

One Point Goes To...

ONLEVEL point fixing systems make the difference. ONLEVEL always attaches great importance to simple mounting and an unobtrusive design. With our point fixings, realising constructive special solutions becomes very easy. Here as well, practical relevance is our maxim. Tested in innumerable projects. For this purpose, our products are tested for different requirements by independent institutions.




Point fixings

Point fixing Ø 30 mm



| Sales unit: 2 pieces




Model 2030	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	10.2030.200.21	10.2030.200.31

Point fixing Ø 30 mm



| Sales unit: 2 pieces




Model 2230	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	10.2230.000.21	10.2230.000.31

Point fixing Ø 30 mm



| Connector: round 42,4 mm
| Sales unit: 2 pieces




Model 2030	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	10.2030.420.21	10.2030.420.31

Point fixing Ø 50 mm



| Sales unit: 2 pieces




Model 2050		AISI 304 (indoor)	AISI 316 (outdoor)
T	Length	Art. no.	Art. no.
10 mm	60 mm	10.2050.100.21	10.2050.100.31
20 mm	70 mm	10.2050.200.21	10.2050.200.31
30 mm	80 mm	10.2050.300.21	10.2050.300.31
40 mm	80 mm	10.2050.400.21	10.2050.400.31
50 mm	90 mm	10.2050.500.21	10.2050.500.31

Point fixings

Point fixing Ø 50 mm



| Connector: round 42,4 mm
| Sales unit: 2 pieces




Model 2050	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	10.2050.420.21	10.2050.420.31

Point fixing Ø 50 mm



| Sales unit: 2 pieces




Model 2850	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	10.2850.000.21	10.2850.000.31

Point fixing Ø 50 mm, adjustable



| Sales unit: 2 pieces




Model 2550	AISI 304 (indoor)	AISI 316 (outdoor)
T	Art. no.	Art. no.
30 mm	10.2550.300.21	10.2550.300.31
40 mm	10.2550.400.21	10.2550.400.31
50 mm	10.2550.500.21	10.2550.500.31

Point fixing Ø 60 mm



| Sales unit: 2 pieces




Model 2060		AISI 304 (indoor)	AISI 316 (outdoor)
T	Length	Art. no.	Art. no.
10 mm	120 mm	10.2060.100.21	10.2060.100.31
20 mm	130 mm	10.2060.200.21	10.2060.200.31
30 mm	140 mm	10.2060.300.21	10.2060.300.31
40 mm	150 mm	10.2060.400.21	10.2060.400.31
50 mm	160 mm	10.2060.500.21	10.2060.500.31

Point fixings

Point fixing Ø 70 mm



| Sales unit: 2 pieces




Model 2070		AISI 304 (indoor)	AISI 316 (outdoor)
T	Length	Art. no.	Art. no.
10 mm	120 mm	10.2070.100.21	10.2070.100.31
20 mm	130 mm	10.2070.200.21	10.2070.200.31
30 mm	140 mm	10.2070.300.21	10.2070.300.31
40 mm	150 mm	10.2070.400.21	10.2070.400.31
50 mm	160 mm	10.2070.500.21	10.2070.500.31

Point fixings Ø 80 mm



| Sales unit: 2 pieces




Model 2080	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	10.2080.100.21	10.2080.100.31

Point fixings Tool




| Suitable for TL-20 systems
| Sales unit: 1 piece




Model 0201	Zinc-plated steel
Diameter	Art. no.
20	93.0201.020.00
30	93.0201.030.00
40	93.0201.040.00
50	93.0201.050.00
60	93.0201.060.00
70	93.0201.070.00
80	93.0201.080.00

Point fixings


Model 2030/2230




Model 2050




Model 2850



Model 2060



Model 2080




Point fixings

Point fixings Ø 50 mm | Glass remains adjustable even after it has been fitted



This unique glass adapter is an addition to ONLEVEL's complete range. The adapter with a diameter of 50 mm has the feature to be adjustable after the glass has been fitted. This adjustability is done with a special tool.

| for glass thickness 16,76-21,52 mm
| Sales unit: 1 piece




Model 2750	
Surface	Art. no.
AISI 304	10.2750.025.21
AISI 304 RAL shining	10.2750.025.23
AISI 304 RAL structure	10.2750.025.26
AISI 304 RAL matt	10.2750.025.28
AISI 316	10.2750.025.31
AISI 316 RAL shiny	10.2750.025.33
AISI 316 RAL structure	10.2750.025.36
AISI 316 RAL matt	10.2750.025.38

Glass adapter mounting tool




By turning the adapter, the glass panel can be precisely aligned by up to ± 1° after installation.

| For 12 mm and 14 mm fittings



Model 0100	
Tool	Art. no.
	90.0100.250.00

How does the mounting tool work?




Point fixings

Point fixings



- Distance to the wall 22-32 mm
- Finish outdoor: AISI 316
- Height: 181 mm
- Distance between drill holes: 120 mm
- Sales unit: 2 pieces




Model 2160	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
60	10.2160.100.21	10.2160.100.31

Anchor for concrete (mechanical)




- Required number per adapter: 1 piece
- Sales unit: 25 pieces



Model 3511	Zinc-plated steel (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	91.3511.515.81	91.3511.515.30

Model 2160



FULL GLASS BALUSTRADES

Connection profiles

TOP COVER




ENGINEERED IN GERMANY

Connection profiles

The Top Cover Profiles

The application versatility of all-glass balustrades in diverse construction projects almost equals the variety of the projects themselves. We have developed the Top Cover Profile for a seamless connection to your individual project. This profile can simply be clipped onto all ONLEVEL all-glass balustrade profiles and can be used for an almost infinite range of connections. The costs involved are reduced and possible special applications for the connection to your facade or your floor become standardised.




Connection profiles

Top Cover Slim, 3 mm



- Panel thickness 1-2 mm
- E.g. for steel sheets
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 8010	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8010.035.10	90.8010.035.11	90.8010.035.13/16/18/19

Top Cover Slim, 10 mm



- Panel thickness 3-8 mm
- e.g. for glass
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 8010	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8010.105.10	90.8010.105.11	90.8010.105.13/16/18/19

Top Cover Slim, 15 mm




- Panel thickness 9-13 mm
- e.g. Rigips plasterboard or Trespa panels
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece



Model 8010	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8010.155.10	90.8010.155.11	90.8010.155.13/16/18/19

Glass profiles for Top Cover Slim




Top mount
TL-3010
TL-4010
TL-5010
TL-6500

Side mount
TL-3011
TL-6501


In floor mount
TL-1010

Connection profiles

Top Cover Slim, 20 mm



- Panel thickness 14-18 mm
- e.g. for wood
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 8010	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8010.205.10	90.8010.205.11	90.8010.205.13/16/18/19

Top Cover Slim, 120 mm



- Covering width 100-110 mm
- e.g. for clinker or stone
- Sales unit: 1 piece




Model 8011	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8011.205.10	90.8011.205.11	90.8011.205.13/16/18/19

Top Cover Slim horizontal, 2 mm



- Width 2 mm
- e.g. for steel sheets
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece



Model 8310	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8310.025.10	90.8310.025.11	90.8310.025.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL




See pages 8 and 19 for more information and order options.

Connection profiles

Top Cover Plus, 3 mm




- Panel thickness 1-2 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 8030	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8030.035.10	90.8030.035.11	90.8030.035.13/16/18/19

Top Cover Plus, 10 mm




- Panel thickness 3-8 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 8030	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8030.105.10	90.8030.105.11	90.8030.105.13/16/18/19

Top Cover Plus, 15 mm




- Panel thickness 3-8 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece



Model 8030	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8030.155.10	90.8030.155.11	90.8030.155.13/16/18/19

Glass profiles for Top Cover Plus




Top mount	Side mount
TF-3620	TF-3621
TF-6620	TF-6621
TL-3080	TL-3031
TL-3120	TL-3121
TL-6020	TL-6021
TL-6030	TL-6081
TL-6080	

Top Cover Plus, 20 mm



- Panel thickness 14-18 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 8030	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8030.205.10	90.8030.205.11	90.8030.205.13/16/18/19

Top Cover Plus horizontal, 2 mm



- Width 2 mm
- e.g. for steel sheets
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece



Model 8310	Mill finish	Aluminium natural anodised	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8330.025.10	90.8330.025.11	90.8330.025.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

FULL GLASS BALUSTRADES

Connection profiles

FLOOR CONNECT

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Connection profiles

Floor Connect Slim



- Width 20 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 8110	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8110.205.10	90.8110.205.11	90.8110.205.13/16/18/19

Floor Connect Plus




- Width 20 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece



Model 8130	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	90.8130.205.10	90.8130.205.11	90.8130.205.13/16/18/19

Glass profiles for Floor Connect Slim | Plus



Floor Connect Slim

Top mount
TL-3010
TL-4010
TL-5010
TL-6500

Side mount
TL-3011
TL-6501

In floor mount
TL-1010

Floor Connect Plus

Top mount
TF-3620
TF-6620
TL-3080
TL-3120
TL-6020
TL-6030
TL-6080

Side mount
TF-3621
TF-6621
TL-3031
TL-3121
TL-6021
TL-6081

FULL GLASS BALUSTRADES

Glass edge protection

ONLEVEL

ADVANCED RAILING TECHNOLOGY


Glass edge protection

STAINLESS STEEL - brushed

Profile



- Height: 6 mm
- Thickness: 1 mm
- Self-adhesive
- Sales unit: 1 piece




Model 2111/2110/2112/2113/2114	AISI 316 brushed			
Width (B)	**14 mm**	**16 mm**	**20 mm**	**24 mm**
Glass thickness (G)	**10,76 – 11,52 mm**	**12,76 – 13,52 mm**	**16,76 – 17,52 mm**	**20,76 - 21,52 mm**
Length	Art. no.	Art. no.	Art. no.	Art. no.
1 m	12.2111.141.31	12.2111.161.31	12.2111.201.31	12.2111.241.31
1,5 m	12.2110.141.31	12.2110.161.31	12.2110.201.31	12.2110.241.31
2 m	12.2112.141.31	12.2112.161.31	12.2112.201.31	12.2112.241.31
3 m	12.2113.141.31	12.2113.161.31	12.2113.201.31	12.2113.241.31
4 m	12.2114.141.31	12.2114.161.31	12.2114.201.31	12.2114.241.31

Profile connector - 90°



- Height 6 mm
- Thickness 1 mm
- Center axis length each 370 mm
- Self-adhesive
- Sales unit: 1 piece




Model 2210	AISI 316 brushed			
Width (B)	**14 mm**	**16 mm**	**20 mm**	**24 mm**
Glass thickness (G)	**10,76 – 11,52 mm**	**12,76 – 13,52 mm**	**16,76 – 17,52 mm**	**20,76 - 21,52 mm**
	Art. no.	Art. no.	Art. no.	Art. no.
	12.2210.141.31	12.2210.161.31	12.2210.201.31	12.2210.241.31

Profile connection cover



- Height 7 mm
- Length 30 mm
- Thickness 1 mm
- Self-adhesive
- Sales unit: 2 pieces




Model 2200	AISI 316 brushed			
Width (B)	**14 mm**	**16 mm**	**20 mm**	**24 mm**
Glass thickness (G)	**10,76 – 11,52 mm**	**12,76 – 13,52 mm**	**16,76 – 17,52 mm**	**20,76 - 21,52 mm**
	Art. no.	Art. no.	Art. no.	Art. no.
	12.2200.141.31	12.2200.161.31	12.2200.201.31	12.2200.241.31

Glass edge protection

ALUMINIUM

Profile






- Height: 7 mm
- Thickness: 1 mm
- Self-adhesive
- The adhesive tape is supplied separately (.10)
- Sales unit: 1 piece

Model 2111/2110/2112/2113/2114			Mill finish	Aluminium natural anod.	RAL coloured
Length	Width (B)	Glass thickness (G)	Art. no.	Art. no.	Art. no.
1 m	14 mm	10,76 – 11,52 mm	11.2111.141.10	11.2111.141.11	11.2111.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2111.161.10	11.2111.161.11	11.2111.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2111.201.10	11.2111.201.11	11.2111.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2111.241.10	11.2111.241.11	11.2111.241.13/16/18/19
1,5 m	14 mm	10,76 – 11,52 mm	11.2110.141.10	11.2110.141.11	11.2110.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2110.161.10	11.2110.161.11	11.2110.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2110.201.10	11.2110.201.11	11.2110.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2110.241.10	11.2110.241.11	11.2110.241.13/16/18/19
2 m	14 mm	10,76 – 11,52 mm	11.2112.141.10	11.2112.141.11	11.2112.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2112.161.10	11.2112.161.11	11.2112.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2112.201.10	11.2112.201.11	11.2112.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2112.241.10	11.2112.241.11	11.2112.241.13/16/18/19
3 m	14 mm	10,76 – 11,52 mm	11.2113.141.10	11.2113.141.11	11.2113.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2113.161.10	11.2113.161.11	11.2113.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2113.201.10	11.2113.201.11	11.2113.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2113.241.10	11.2113.241.11	11.2113.241.13/16/18/19
4 m	14 mm	10,76 – 11,52 mm	11.2114.141.10	11.2114.141.11	11.2114.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2114.161.10	11.2114.161.11	11.2114.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2114.201.10	11.2114.201.11	11.2114.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2114.241.10	11.2114.241.11	11.2114.241.13/16/18/19

Profile connector - 90°





- Height 7 mm
- Thickness 1 mm
- Center axis length each 370 mm
- For glass thickness 10,76 - 11,52 mm
- Self-adhesive
- Sales unit: 1 piece

Model 2210		Mill finish	Aluminium natural anod.	RAL coloured
Width (B)	Glass thickness (G)	Art. no.	Art. no.	Art. no.
14 mm	10,76 – 11,52 mm	11.2210.141.10	11.2210.141.11	11.2210.141.13/16/18/19
16 mm	12,76 – 13,52 mm	11.2210.161.10	11.2210.161.11	11.2210.161.13/16/18/19
20 mm	16,76 – 17,52 mm	11.2210.201.10	11.2210.201.11	11.2210.201.13/16/18/19
24 mm	20,76 - 21,52 mm	11.2210.241.10	11.2210.241.11	11.2210.241.13/16/18/19
28 mm	25 - 25,52 mm	11.2210.281.10	11.2210.281.11	11.2210.281.13/16/18/19

Glass edge protection


ALUMINIUM

Profile connection cover



.10

- Height 8 mm
- Length 30 mm
- Thickness 1 mm
- Self-adhesive
- Sales unit: 2 pieces





.11



.13/16/18/19

Model 2200		Mill finish	Aluminium natural anod.	RAL coloured
Width (B)	Glass thickness (G)	Art. no.	Art. no.	Art. no.
14 mm	10,76 – 11,52 mm	11.2200.141.10	11.2200.141.11	11.2200.141.13/16/18/19
16 mm	12,76 – 13,52 mm	11.2200.161.10	11.2200.161.11	11.2200.161.13/16/18/19
20 mm	16,76 – 17,52 mm	11.2200.201.10	11.2200.201.11	11.2200.201.13/16/18/19
24 mm	20,76 - 21,52 mm	11.2200.241.10	11.2200.241.11	11.2200.241.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

FULL GLASS BALUSTRADES

U-profiles | parts

ONLEVEL

ADVANCED RAILING TECHNOLOGY


U-profiles | Mounted on top of glass

ALUMINIUM

U-profile, 26 mm



- 26 x 23 x 2 mm
- U 22 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- For glass thicknesses up to 17,5 mm
- Sales unit: 1 piece




Model 2115	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	11.2115.262.10	11.2115.262.11	11.2115.262.13/16/18/19

U-profile connection cover, 26 mm



- Length 40 mm
- For handrail 26 x 20 x 2 mm
- For glass thicknesses up to 17,5 mm
- Sales unit: 1 piece




Model 2201	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	11.2201.262.10	11.2201.262.11	11.2201.262.13/16/18/19

End cap, flat



- Suitable for the 2115 U-profile
- Sales unit: 2 pieces




Model 2300	Mill finish	Aluminium natural anodised	RAL coloured
Height x width	Art. no.	Art. no.	Art. no.
26 x 23	11.2300.262.10	11.2300.262.11	11.2300.262.13/16/18/19

U-profile wall connector



- Sales unit: 2 pieces




Model 2220	Mill finish	Aluminium natural anodised	RAL coloured
B x H	Art. no.	Art. no.	Art. no.
26 x 23	11.2220.262.10	11.2220.262.11	11.2220.262.13/16/18/19

Glass rubber, 22 mm



- U handrail rubber seals for 22 mm



Model 6526	8 – 11 mm	11,5 - 13,5 mm	16 - 17,5 mm
Length	Art. no.	Art. no.	Art. no.
5 m	90.6526.508.60	90.6526.511.60	90.6526.516.60
25 m	90.6526.208.60	90.6526.211.60	90.6526.216.60


U-profiles | Mounted on top of glass

ALUMINIUM

U-profile, 30 mm



- 30 x 28 x 2 mm
- U 26 mm
- For glass thicknesses up to 21,5 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 2115	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	11.2115.302.10	11.2115.302.11	11.2115.302.13/16/18/19

U-profile connection cover, 30 mm



- Length 40 mm
- For handrail 30 x 25 x 2 mm
- For glass thicknesses up to 21,5 mm
- Sales unit: 1 piece




Model 2201	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	11.2201.302.10	11.2201.302.11	11.2201.302.13/16/18/19

End cap, flat



- Suitable for the 2115 U-profile
- Sales unit: 2 pieces




Model 2300	Mill finish	Aluminium natural anodised	RAL coloured
Height x width	Art. no.	Art. no.	Art. no.
30 x 28	11.2300.302.10	11.2300.302.11	11.2300.302.13/16/18/19

U-profile wall connector



- Sales unit: 2 pieces



Model 2220	Mill finish	Aluminium natural anodised	RAL coloured
B x H	Art. no.	Art. no.	Art. no.
30 x 28	11.2220.302.10	11.2220.302.11	11.2220.302.13/16/18/19

Glass rubber, 26 mm



- U handrail rubber seals for 26 mm



Model 6530	8 – 11 mm	11,5 - 13,5 mm	15 mm	16 - 17,5 mm	19 mm	20 - 21,5 mm
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.6530.508.60	90.6530.511.60	90.6530.515.60	90.6530.516.60	90.6530.519.60	90.6530.520.60
25 m	90.6530.208.60	90.6530.211.60	90.6530.215.60	90.6530.216.60	90.6530.219.60	90.6530.220.60


U-profiles | Mounted on top of glass

ALUMINIUM

U-profile, 42 mm



- 42 x 34 x 3 mm
- U 36 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- For glass thicknesses up to 31,51 mm
- Sales unit: 1 piece




Model 2115	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	11.2115.423.10	11.2115.423.11	11.2115.423.13/16/18/19

U-profile connection cover, 42 mm



- Length 40 mm
- For handrail 40 x 30 x 2 mm
- For glass thicknesses up to 31,51 mm
- Sales unit: 1 piece




Model 2201	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	11.2201.423.10	11.2201.423.11	11.2201.423.13/16/18/19

End cap, flat



- Suitable for the 2115 U-profile
- Sales unit: 2 pieces




Model 2300	Mill finish	Aluminium natural anodised	RAL coloured
Height x width	Art. no.	Art. no.	Art. no.
42 x 34	11.2300.423.10	11.2300.423.11	11.2300.423.13/16/18/19

U-profile wall connector



- Sales unit: 2 pieces




Model 2220	Mill finish	Aluminium natural anodised	RAL coloured
B x H	Art. no.	Art. no.	Art. no.
42 x 34	11.2220.423.10	11.2220.423.11	11.2220.423.13/16/18/19

Glass rubber, 36 mm



- U handrail rubber seals for 36 mm



Model 6540	20,5 – 21,5 mm	24,5 – 25,5 mm	30,5 – 31,5 mm
Length	Art. no.	Art. no.	Art. no.
5 m	90.6540.520.60	90.6540.524.60	90.6540.530.60
25 m	90.6540.220.60	90.6540.224.60	90.6540.230.60


U-profiles | Mounted on top of glass

ALUMINIUM

U-profile connector - 90°



- Suitable for the 2115 U-profile
- Center axis length each 370 mm
- Use connectors 11.2200.xxx.30
- Sales unit: 1 piece




Model 2210	Mill finish	Aluminium natural anodised	RAL coloured
Height x width	Art. no.	Art. no.	Art. no.
26 x 23	11.2210.262.10	11.2210.262.11	11.2210.262.13/16/18/19
30 x 28	11.2210.302.10	11.2210.302.11	11.2210.302.13/16/18/19
42 x 34	11.2210.423.10	11.2210.423.11	11.2210.423.13/16/18/19

U-profile straight connector



- Suitable for the 2115 U-profile
- Sales unit: 2 pieces




Model 2200	AISI 316 (indoor & outdoor)
Width	Art. no.
U 22 mm	11.2200.262.30
U 26 mm	11.2200.302.30
U 36 mm	11.2200.423.30

U-profile corner connector



- Suitable for the 2115 U-profile
- Sales unit: 2 pieces



Model 2210	AISI 316 (indoor & outdoor)
Width	Art. no.
U 22 mm	11.2210.262.30
U 26 mm	11.2210.302.30
U 36 mm	11.2210.423.30

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.


U-profiles | Mounted on top of glass

STAINLESS STEEL

U-profile, 26 mm



- 26 x 20 x 2 mm
- U 22 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- For glass thicknesses up to 17,5 mm
- Sales unit: 1 piece




Model 2114	AISI 304 (indoor)	AISI 316 (outdoor)
Length	Art. no.	Art. no.
4 m	12.2114.262.21	12.2114.262.31

U-profile connection cover, 26 mm



- Length 40 mm
- For handrail 26 x 20 x 2 mm
- For glass thicknesses up to 17,5 mm
- Sales unit: 1 piece




Model 2114	AISI 316 (outdoor)
Length	Art. no.
	12.2200.262.31

Glass rubber, 22 mm



- U handrail rubber seals for 22 mm



Model 6526	8 – 11 mm	11,5 - 13,5 mm	16 - 17,5 mm
Length	Art. no.	Art. no.	Art. no.
5 m	90.6526.508.60	90.6526.511.60	90.6526.516.60
25 m	90.6526.208.60	90.6526.211.60	90.6526.216.60


U-profiles | Mounted on top of glass

STAINLESS STEEL

U-profile, 30 mm



- 30 x 25 x 2 mm
- U 26 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- For glass thicknesses up to 21,5 mm
- Sales unit: 1 piece




Model 2114	AISI 304 (indoor)	AISI 316 (outdoor)
Length	Art. no.	Art. no.
4 m	12.2114.302.21	12.2114.302.31

U-profile connection cover, 30 mm



- Length 40 mm
- For handrail 30 x 25 x 2 mm
- For glass thicknesses up to 21,5 mm
- Sales unit: 1 piece




Model 2114	AISI 316 (outdoor)
	Art. no.
	12.2200.302.31

Glass rubber, 26 mm



- U handrail rubber seals for 26 mm



Model 6530	8 – 11 mm	11,5 - 13,5 mm	15 mm	16 - 17,5 mm	19 mm	20 - 21,5 mm
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.6530.508.60	90.6530.511.60	90.6530.515.60	90.6530.516.60	90.6530.519.60	90.6530.520.60
25 m	90.6530.208.60	90.6530.211.60	90.6530.215.60	90.6530.216.60	90.6530.219.60	90.6530.220.60


Quick & easy

For further helpful information, please see our ONLEVEL website. Here you will find explanatory and installation videos, photos and downloads, as well as a configurator to help you with the glass calculations.


U-profiles | Mounted on top of glass

STAINLESS STEEL

U-profile, 40 mm




- 40 x 30 x 2 mm
- U 36 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- For glass thicknesses up to 31,5 mm
- Sales unit: 1 piece




Model 2114	AISI 304 (indoor)	AISI 316 (outdoor)
Length	Art. no.	Art. no.
4 m	12.2114.402.21	12.2114.402.31

U-profile connection cover, 40 mm



- Length 40 mm
- For handrail 40 x 30 x 2 mm
- For glass thicknesses up to 31,5 mm
- Sales unit: 1 piece




Model 2114	AISI 316 (outdoor)
	Art. no.
	12.2200.402.31

Glass rubber, 36 mm



- U handrail rubber seals for 36 mm




Model 6540	20,5 – 21,5 mm	24,5 – 25,5 mm	30,5 – 31,5 mm
Length	Art. no.	Art. no.	Art. no.
5 m	90.6540.520.60	90.6540.524.60	90.6540.530.60
25 m	90.6540.220.60	90.6540.224.60	90.6540.230.60

U-profile end piece



- Length: 390 mm
- Sales unit: 1 piece




Model 2301	AISI 304 (indoor)	AISI 316 (outdoor)
Height x width	Art. no.	Art. no.
26 x 20	12.2301.262.21	12.2301.262.31
30 x 25	12.2301.302.21	12.2301.302.31
40 x 30	12.2301.402.21	12.2301.402.31

U-profile connector - 90°



- Length 370 x 370 mm
- Sales unit: 1 piece




Model 2210	AISI 304 (indoor)	AISI 316 (outdoor)
Height x width	Art. no.	Art. no.
26 x 20	12.2210.262.21	12.2210.262.31
30 x 25	12.2210.302.21	12.2210.302.31
40 x 30	12.2210.402.21	12.2210.402.31

U-profiles | Mounted on top of glass

U-profile - rectangular



| 40 x 30 x 1 mm
| U handrail rubber seals, 24 mm
| Sales unit: 1 piece




Model 2106	AISI 304 (indoor)	AISI 316 (outdoor)
Length	Art. no.	Art. no.
5 m	12.2105.401.21	12.2105.401.31

U-profile end cap - rectangular



| 40 x 30 x 1 mm
| Sales unit: 1 piece




Model 2300	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	12.2300.401.21	12.2300.401.31

U-profile wall connector - rectangular



| 40 x 30 x 1 mm
| Sales unit: 1 piece




Model 2220	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	12.2220.401.21	12.2220.401.31

Glass rubber, 24 mm




| U handrail rubber seals for 24 mm




Model 6542	8 – 11 mm	11,5 - 13,5 mm	15 mm	16 - 17,5 mm	19 mm	20 - 21,5 mm
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.6542.008.60	90.6542.011.60	90.6542.015.60	90.6542.016.60	90.6542.019.60	90.6542.020.60
25 m	90.6542.208.60	90.6542.211.60	90.6542.215.60	90.6542.216.60	90.6542.219.60	90.6542.220.60

U-profiles | Mounted on top of glass

U-profile corner connector - rectangular



| 40 x 30 x 1 mm
| Sales unit: 1 piece




Model 2210	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	12.2210.401.21	12.2210.401.31

U-profile corner connector, horizontally adjustable - rectangular



| For handrail 40 x 30 x 1 mm
| Sales unit: 1 piece




Model 2212		AISI 304 (indoor)	AISI 316 (outdoor)
Direction		Art. no.	Art. no.
horizontal	90° - 180°	12.2212.401.21	12.2212.401.31

U-profile corner connector, vertically adjustable - rectangular




| For handrail 40 x 30 x 1 mm
| Sales unit: 1 piece




Model 2213		AISI 304 (indoor)	AISI 316 (outdoor)
Direction		Art. no.	Art. no.
vertical	90° - 135°	12.2213.401.21	12.2213.401.31

U-profile straight connector - rectangular



| 40 x 30 x 1 mm
| Sales unit: 1 piece




Model 2200	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	12.2200.401.21	12.2200.401.31

U-profiles | Mounted on top of glass

U-profile - Ø 42,4 mm



- Diameter Ø 42,4 x 1,5 mm
- U 24 mm
- For glass thicknesses up to 21,52 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 2105	AISI 304 (indoor)	AISI 316 (outdoor)
Length	Art. no.	Art. no.
5 m	12.2105.421.21	12.2105.421.31

End cap



- Sales unit: 1 piece




Model 2300	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4	12.2300.421.21	12.2300.421.31

U-profile wall connector



- Sales unit: 1 piece




Model 2220	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4	12.2220.421.21	12.2220.421.31

Glass rubber, 24 mm



- U handrail rubber seals for 24 mm




Model 6542	8 – 11 mm	11,5 - 13,5 mm	15 mm	16 - 17,5 mm	19 mm	20 - 21,5 mm
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.6542.008.60	90.6542.011.60	90.6542.015.60	90.6542.016.60	90.6542.019.60	90.6542.020.60
25 m	90.6542.208.60	90.6542.211.60	90.6542.215.60	90.6542.216.60	90.6542.219.60	90.6542.220.60

U-profiles | Mounted on top of glass

U-profile straight connector - round



| Sales unit: 1 piece




Model 2200	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4	12.2200.421.21	12.2200.421.31

U-profile corner connector - round



| Sales unit: 1 piece




Model 2210	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4	12.2210.421.21	12.2210.421.31

U-profile corner connector - round



| Sales unit: 1 piece




Model 2211	AISI 304 (indoor)	AISI 316 (outdoor)
For diameter	Art. no.	Art. no.
42,4	12.2211.421.21	12.2211.421.31

U-profile corner connector, upward adjustable - round



| Upwards = 25° - 55°
| Sales unit: 1 piece




Model 2115	AISI 304 (indoor)	AISI 316 (outdoor)
For diameter	Art. no.	Art. no.
42,4	12.2215.421.21	12.2215.421.31


U-profile corner connector, downward adjustable - round



| Downwards = 25° - 55°
| Sales unit: 1 piece



Model 2116	AISI 304 (indoor)	AISI 316 (outdoor)
For diameter	Art. no.	Art. no.
42,4	12.2216.421.21	12.2216.421.31



FULL GLASS BALUSTRADES

U-profiles with LED | parts

LAZORTRACK®

U-profiles with LED | Mounted on top of glass / against the wall

LEDs get ready to rumble.
Inspired by the permanent onward development of LED illumination, many new light installation possibilities and applications keep appearing in architecture. Whether discreet, soft or lightfast – LEDs not only stand out due to their amazing unobtrusiveness but also consume less energy, generate less heat and in this way contribute to a sustainable energy footprint.


Watch Installation Video:

Essential features
- Modern design
- Available for wall and glass mounting
- Aluminium and wood
- Available in RAL
- Protection class: IP66
- LED strip: Can be cut to size (every 55 mm)
- Voltage: 24 V
- LEDs per metre: 144
- Beam angle: 80°
- Dimmable: yes
- Colour temperature: 4000 K
- Light colour: Neutral white
- Rated output per metre: 6 W
- Luminous flux per metre: 180 lm
- Light output: 337 lm/m
- Input power: 220-240V AC 50/60Hz
- 2 handrail holders at 2,5 m
- 4 handrail holders at 5 m

Glass handrail - complete set



- Width: 42 mm, height: 48 mm
- Incl. end caps, transformer, LED strip and cable
- Pre-assembled for connection wiring on site
- Suitable for indoor and outdoor use
- Sales unit: 1 piece




Model 2002 / 2005 / 2020		Mill finish	Aluminium natural anod.	RAL coloured
Glass thickness	Profile length	Art. no.	Art. no.	Art. no.
8 - 11 mm	2,5 m	18.2002.421.10	18.2002.421.11	18.2002.421.13/16/18/19
	5 m	18.2005.421.10	18.2005.421.11	18.2005.421.13/16/18/19
	10 m	18.2010.421.10	18.2010.421.11	18.2010.421.13/16/18/19
12 - 13,5 mm	2,5 m	18.2002.422.10	18.2002.422.11	18.2002.422.13/16/18/19
	5 m	18.2005.422.10	18.2005.422.11	18.2005.422.13/16/18/19
	10 m	18.2010.422.10	18.2010.422.11	18.2010.422.13/16/18/19
16 - 17,5 mm	2,5 m	18.2002.423.10	18.2002.423.11	18.2002.423.13/16/18/19
	5 m	18.2005.423.10	18.2005.423.11	18.2005.423.13/16/18/19
	10 m	18.2010.423.10	18.2010.423.11	18.2010.423.13/16/18/19
20 - 21,5 mm	2,5 m	18.2002.424.10	18.2002.424.11	18.2002.424.13/16/18/19
	5 m	18.2005.424.10	18.2005.424.11	18.2005.424.13/16/18/19
	10 m	18.2010.424.10	18.2010.424.11	18.2010.424.13/16/18/19

U-profiles with LED | Mounted on top of glass / against the wall

U-profile - rectangular



- Width: 42 mm, height: 48 mm
- U 27 mm
- For glass thicknesses up to 21,52 mm
- Bending possible: minimal radius 1,5 m
- After bending, 500 mm remains straight on both sides
- Sales unit: 1 piece




Model 2102 / 2105	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
2,5 m	18.2102.420.10	18.2102.420.11	18.2102.420.13/16/18/19
5 m	18.2105.420.10	18.2105.420.11	18.2105.420.13/16/18/19

Inside corner - 90°



- LED strip inside
- Side length outside 380 mm
- 48 x 42 mm
- Sales unit: 1 piece




Model 2210	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	18.2210.420.10	18.2210.420.11	18.2210.420.13/16/18/19

Outside corner - 90°



- LED strip outside
- Side length outside 380 mm
- 48 x 42 mm
- Sales unit: 1 piece




Model 2214	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	18.2214.420.10	18.2214.420.11	18.2214.420.13/16/18/19

End cap



- 48 x 42 mm
- Sales unit: 1 piece




Model 2300 / 2305	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
Left	18.2300.420.10	18.2300.420.11	18.2300.420.13/16/18/19
Right	18.2305.420.10	18.2305.420.11	18.2305.420.13/16/18/19

U-profiles with LED | Mounted on top of glass / against the wall

Wall connector



| 48 x 42 mm
| Sales unit: 2 pieces




Model 2220	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	18.2220.420.10	18.2220.420.11	18.2220.420.13/16/18/19

Glass rubber, 27 mm



| U handrail rubber seals for 27 mm



Model 6548	8 – 11 mm	11,5 - 13,5 mm	15 mm	16 - 17,5 mm	19 mm	20 - 21,5 mm
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.6548.008.60	90.6548.011.60	90.6548.015.60	90.6548.016.60	90.6548.019.60	90.6548.020.60
25 m	90.6548.208.60	90.6548.211.60	90.6548.215.60	90.6548.216.60	90.6548.219.60	90.6548.220.60

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

U-profiles with LED | Mounted against the wall

Wall handrail - complete set




| Width: 42 mm
| Height: 34 mm
| Incl. handrail support, end caps, transformer, LED strip and cable
| Pre-assembled for connection wiring on site
| Suitable for indoor and outdoor use
| Sales unit: 1 piece

	Mill finish	Aluminium natural anodised	RAL coloured
length	Art. no.	Art. no.	Art. no.
2.5 m	18.4002.420.10	18.4002.420.11	18.4002.420.13/16/18/19
5 m	18.4005.420.10	18.4005.420.11	18.4005.420.13/16/18/19
10 m	18.4010.420.10	18.4010.420.11	18.40010.420.13/16/18/19

Handrail



| Width: 42 mm
| Height: 34 mm
| Sales unit: 1 piece




	Mill finish	Aluminium natural anodised	RAL coloured
length	Art. no.	Art. no.	Art. no.
2.5 m	18.4102.420.10	18.4102.420.11	18.4102.420.13/16/18/19
5 m	18.4105.420.10	18.4105.420.11	18.4105.420.13/16/18/19

Inside corner - 90°



| LED strip inside
| Side length outside 380 mm
| 42 x 34 mm
| Sales unit: 1 piece




Model 4210	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	18.4210.420.10	18.4210.420.11	18.4210.420.13/16/18/19

Outside corner - 90°



| LED strip outside
| Side length outside 380 mm
| 42 x 34 mm
| Sales unit: 1 piece




Model 4214	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	18.4214.420.10	18.4214.420.11	18.4214.420.13/16/18/19

U-profiles with LED | Mounted against the wall

End cap, left + right



| 42 x 34 mm
| Sales unit: 1 piece




Model 4300	Mill finish	Aluminium natural anodised	RAL coloured
	Art. no.	Art. no.	Art. no.
	18.4300.420.10	18.4300.420.11	18.4300.420.13/16/18/19

Wall connector



| Sales unit: 2 pieces




Model 2220	Mill finish	Aluminium natural anodised	RAL coloured
Width x Height	Art. no.	Art. no.	Art. no.
42 x 34	18.4220.420.10	18.4220.420.11	18.4220.420.13/16/18/19

Wall handrail support - round



A cable with a maximum diameter of 8 mm fits through the handrail support.

| 3 handrail holders at 2.5 meters
| 6 handrail holders at 5.0 meters
| Sales unit: 2 pieces




Model 4400	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	18.4400.000.21	18.4400.000.31

Straight connector



| Sales unit: 1 piece



Model 4200	
	Art. no.
	18.4200.420.15

FULL GLASS BALUSTRADES

Handrail tubes | parts


ONLEVEL
ADVANCED RAILING TECHNOLOGY

Handrail tubes | Mounted against glass or wall

Handrail tube, Ø 42,4 mm



| Length: 5 m
| Sales unit: 1 piece




Model 0105	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4 x 2 mm	12.0105.422.21	12.0105.422.31

Handrail tube straight connector - round



| Sales unit: 1 piece




Model 0200	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4 x 2	12.0200.422.21	12.0200.422.31

Handrail tube corner connector - round



| Sales unit: 1 piece




Model 0210		AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Length	Art. no.	Art. no.
42,4 x 2	30	12.0210.422.21	12.0210.422.31

Handrail tube end cap - round



| Sales unit: 1 piece




Model 0300	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4 x 2	12.0300.422.21	12.0300.422.31

Handrail tube end cap - round + curved



| Sales unit: 1 piece




Model 0310	AISI 304 (indoor)	AISI 316 (outdoor)
Diameter	Art. no.	Art. no.
42,4 x 2	12.0310.422.21	12.0310.422.31

Handrail tubes | Mounted against glass or wall

Glass handrail support - round



| For glass thicknesses between 12 mm and 26 mm
| Drill hole in glass Ø 18 mm
| Sales unit: 1 piece




Model 0420	AISI 304 (indoor)	AISI 316 (outdoor)
Connector	Art. no.	Art. no.
flat	12.0420.000.21	12.0420.000.31
for Ø 42,4	12.0420.420.21	12.0420.420.31

Wall handrail support - round



| M8 inner thread
| Sales unit: 1 piece




Model 0400	AISI 304 (indoor)	AISI 316 (outdoor)
Connector	Art. no.	Art. no.
flat	12.0400.000.21	12.0400.000.31
for Ø 42,4	12.0400.420.21	12.0400.420.31

Wall handrail support - round



| 3 mounting holes
| Sales unit: 1 piece




Model 0410	AISI 304 (indoor)	AISI 316 (outdoor)
Connector	Art. no.	Art. no.
flat	12.0410.000.21	12.0410.000.31
for Ø 42,4	12.0410.420.21	12.0410.420.31

Wall handrail support - for welding



| 3 mounting holes
| Sales unit: 1 piece



Model 0450	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	12.0450.000.21	12.0450.000.31

FULL GLASS BALUSTRADES

Accessories | additionals

TURBOFLEX®

TRANSLEVEL®

LAZORTRACK®

ONLEVEL

ADVANCED RAILING TECHNOLOGY

Optional: Mounting console


This steel mounting console (zinc plated) is designed for securely installing glass railing profiles at a distance from the mounting surface. It ensures structural stability while allowing for precise alignment and clean aesthetics, especially in scenarios where direct fixing is not possible.

Product highlights:

- Strong construction: Engineered to handle high loads with minimal deflection
- Fast installation: Pre-drilled for standard bolts or anchors

Ideal applications:

- Balcony and terrace balustrades with insulation or cladding
- Façade installations with uneven or recessed mounting surfaces
- Projects requiring visual spacing or drainage clearance




Top mount **Side mount**

Mounting console



- Finish: hit-dip galvanised
- Material: steel, zinc, galvanised
- Distance: every 400 mm
- Distance (height) = 110 - 150 mm
- Static calculation




Model 9007	Zinc-plated steel (indoor)
	Art. no.
	90.9007.110.81

Mounting set for concrete (mechanical)



- Required number per 2,5 m: 7 mounting consoles
- M10
- Sales unit: 20 pieces




Model 3501	AISI 316 (outdoor)
	Art. no.
	91.3501.050.30 fischer

Mounting set for steel



- Required number per 2,5 m: 7 mounting consoles
- M10 x 45 mm
- Sales unit: 14 pieces



Model 6620	AISI 316 (outdoor)
	Art. no.
	91.6620.045.30

Accessories


TURBOFLEX Torque Tool 6 Nm



Adapter for tightening TURBOFLEX to 6 Nm. Use in conjuction with mounting tool.

| Sales unit: 1 piece

Model 0100	
Tool	Art. no.
	90.0100.285.00




TURBOFLEX mounting tool



Easy to handle and an indispensable helper during assembly. The round head enables you to fix the screw in the TURBOFLEX wedge or clamps in an angle, so you will not touch and damage the glass.

Model 0100	
Tool	Art. no.
	90.0100.280.00



TURBOFLEX glass clamping tool



Optional tool for clamping and aligning two glass panels with each other.

Model 0100	
Tool	Art. no.
	90.0100.230.41



Height adjuster




AbP LGA

| Height adjustment of ± 3 mm
| Sales unit: 2 pieces

Add the optional height adjuster components to each glass panel to allow precise vertical adjustment.

Model 3500	
Height adjuster	Art. no.
	90.3500.100.00




Optional height adjustment for TURBOFLEX

ALWAYS ON LEVEL

| Optional height adjustment
| ± 3 mm vertical adjustment range

TURBOFLEX



Demos

TURBOFLEX glass profile - demo



| Without glass
| Length: 200 mm

Top mount

	Aluminium natural anodised
	Art. no.
TF-3620	81.3620.000.11
TF-6620	81.6620.000.11


Side mount

	Aluminium natural anodised
	Art. no.
TF-3621	81.3621.000.11
TF-6621	81.6621.000.11

Demobox



The demo box contains:
| A profile (l = 200 mm)
| Glass panel
| Installation instructions
| Installation tool (90.0100.280.00)




Model 6620	
Demobox	Art. no.
	81.6620.001.11

Anchors - for concrete (mechanical)

Mounting set for concrete (mechanical)



| M12
| Sales unit Fischer: 20 pieces | MKT: 25 pieces




Model 3501 / 3601			Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	For profile	L	Art. no.		Art. no.	
Without spacer	**TF-6620, TF-3621, TF-6621, TL-6020**	110 mm	91.3501.210.81	fischer	91.3501.210.30	fischer
			91.3601.210.81	MKT	91.3601.210.30	MKT
	TF-3620, TL-3010, TL-3080, TL-3120	120 mm	91.3501.220.81	fischer	91.3501.220.30	fischer
			91.3601.220.81	MKT	91.3601.220.30	MKT
With spacers	**TF-6620, TF-3621, TF-6621, TL-6020**	130 mm	91.3501.230.81	fischer	91.3501.230.30	fischer
			91.3601.230.81	MKT	91.3601.230.30	MKT
	TF-3620, TL-3010	140 mm	91.3501.240.81	fischer	91.3501.240.30	fischer
			91.3601.240.81	MKT	91.3601.240.30	MKT

Mounting set for concrete (mechanical)



| Ø12
| Sales unit: 50 pieces




Model 3521 / 3621			Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	For profile	L	Art. no.		Art. no.	
Without spacers	**TL-6080, TL-6021, TL-6081**	90 mm	91.3521.210.81	fischer	91.3521.210.30	fischer
			91.3621.210.81	MKT	91.3621.210.30	MKT
With spacers		110 mm	91.3521.230.81	fischer	91.3521.230.30	fischer
			91.3621.230.81	MKT	91.3621.230.30	MKT

Mounting set for concrete (mechanical)



| Sales unit: 25 pieces




Model 3511 / 3611			Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	For profile	L	Art. no.		Art. no.	
Without spacers	**TL-6030**	90 mm	91.3511.215.81	fischer	91.3511.215.30	fischer
			91.3611.215.81	MKT	91.3611.215.81	MKT

Anchors - for concrete (mechanical)

Mounting set for concrete (mechanical)



| Sales unit: 50 pieces




Model 3521 / 3621			Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	For profile	L	Art. no.		Art. no.	
Without spacers	TL-6500, TL-6501	70 mm	91.3521.010.81	fischer	91.3521.010.30	fischer
			91.3621.010.81	MKT	91.3621.010.30	MKT
With spacers		90 mm	91.3521.030.81	fischer	91.3521.030.30	fischer
			91.3621.030.81	MKT	91.3621.030.30	MKT

Mounting screw for concrete



| Suitable for our profiles without countersinking
| Tangential screwdriver required
| Sales unit: 50 pieces




Model 3701			Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	For profile	L	Art. no.		Art. no.	
Without spacers	TL-6020, TL-6021	90 mm (.81) 95 mm (.30)	91.3701.090.81	fischer	91.3701.095.30	fischer

Anchors - for concrete (chemical)

Mounting set for concrete (chemical)



| M10
| Suitable injection mortar: 91.3000.010.00 is sufficient for ± 22 anchors
| Sales unit: 10 pieces




Model 3541 / 3641			Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	For profile	L	Art. no.		Art. no.	
Without spacer	TF-3621, TL-6020, TL-3011, TL-3031, TL-3121,	190 mm	91.3541.019.81	fischer	91.3541.019.30	fischer
			91.3641.019.81	MKT	91.3641.019.30	MKT
	TL-4010	150 mm	91.3541.015.81	fischer	91.3541.015.30	fischer
			91.3641.015.81	MKT	91.3641.015.30	MKT
With spacers	TF-3621, TL-4010, TL-6020, TL-3011, TL-3031, TL-3121	190 mm	91.3541.019.81	fischer	91.3541.019.30	fischer
					91.3641.019.30	MKT

Anchors - for steel

Mounting set for steel



| M12
| Sales unit: 7 pieces




Model 3010 / 6620 / 3120			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TF-3620, TF-3621, TL-3010, TL-3080**	50 mm	91.3010.050.81	91.3010.050.30
	TF-6620, TF-6621		91.6620.050.81	91.6620.050.30
	TL-3120		91.3120.050.81	91.3120.050.30

Mounting set for steel



| M10
| Sales unit: 7 pieces




Model 3011			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TL-3011**	60 mm	91.3011.060.81	91.3011.060.30

Mounting set for steel



| M10
| Sales unit: 10 pieces




Model 3031 / 3121 / 6501			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TL-3031**	60 mm	91.3031.060.81	91.3031.060.30
	TL-3121		91.3121.060.81	91.3121.060.30

Mounting set for steel



| M10
| Sales unit: 13 pieces




Model 4010 / 6020			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TL-4010**	60 mm	91.4010.060.81	91.4010.060.30
	TL-6020		91.6020.060.81	91.6020.060.30

Anchors - for steel

Mounting set for steel



| M12
| Sales unit: 10 pieces




Model 6080 / 6081			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TL-6080**	60 mm	91.6080.040.81	91.6080.040.30
	TL-6081		91.6081.040.81	91.6081.040.30

Mounting set for steel



| M12
| Sales unit: 13 pieces




Model 6021			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TL-6021**	60 mm	91.6021.060.81	91.6021.060.30

Mounting set for steel



| M10 x 40 mm
| Sales unit: 17 pieces




Model 6030			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TL-6030**	40 mm	91.6030.040.81	91.6030.040.30

Mounting set for steel



| M10
| Sales unit: 10 pieces




Model 6500 / 6501			Zinc-plated steel (indoor)	AISI 316 (outdoor)
	For profile	L	Art. no.	Art. no.
Without spacers	**TL-6500**	60 mm	91.6500.060.81	91.6500.060.30
	TL-6501		91.6501.060.81	91.6501.060.30

Anchors - for wood

Mounting set for wood



| M12
| Pilot holes: softwood: Ø 19 mm
hardwood: Ø 19.5 mm
| Sales unit: 7 pieces




Model 3010			Zinc-plated steel (indoor)
	For profile	L	Art. no.
With and without spacers	**TF-3620, TF-3621, TL-3010**	100 mm	91.3010.800.81

Mounting set for wood



| M10
| Pilot holes: softwood: Ø 15,5 mm
hardwood: Ø 16 mm
| Sales unit: 14 pieces




Model 3011			Zinc-plated steel (indoor)
	For profile	L	Art. no.
With and without spacers	**TL-3011**	70 mm	91.3011.800.81

Mounting set for wood



| M12
| Pilot holes: softwood: Ø 19 mm
hardwood: Ø 19.5 mm
| Sales unit: 13 pieces




Model 6621 / 6021 / 4010				Zinc-plated steel (indoor)
	For profile	Sales unit	L	Art. no.
With and without spacers	**TF-6621**	13	100 mm	91.6621.800.81
	TL-6021	13		91.6021.800.81
	TL-4010	25		91.4010.800.81

Mounting set for wood



| M10
| Pilot holes: softwood: Ø 15,5 mm
hardwood: Ø 16 mm
| Sales unit: 10 pieces



Model 6500 / 6501			Zinc-plated steel (indoor)
	For profile	L	Art. no.
With and without spacers	**TL-6500, TL-6501**	70 mm	91.6500.800.81
			91.6501.800.81

Mounting on wood

Watch the installation video.

Accessories

Mortar



- For chemical bonding of anchors
- Including 2 mixers
- Sales unit: 1 piece

Model 3000	
	Art. no.
	91.3000.010.00

Dispensing device



- For use with mortar (91.3000.010.00)
- Sales unit: 1 piece

Model 3002	Plastic
	Art. no.
Gun	91.3002.010.00
Mixer	91.3002.011.00

Airpump



- For blowing out the drill holes
- Sales unit: 1 piece

Model 3001	Plastic
	Art. no.
	91.3001.010.00

Anchor hole brush



- For cleaning the drill holes
- Ø 12 mm
- Sales unit: 1 piece

Model 3002	Plastic
	Art. no.
	91.3002.012.00

Anchor hole fillings per mortar cartridge

TURBOFLEX® + TRANSLEVEL®

Anchors	91.3541.015.30 91.3541.015.81	91.3541.019.30 91.3541.019.81	91.3541.218.30 91.3541.218.81	91.3551.015.30 91.3551.015.81	91.3551.017.30 91.3551.017.81	91.3551.212.30	91.3551.221.30 91.3551.221.81
Mortar 390 ml (91.3000.010.00)	37	37	26	37	37	46	23

Anchors	91.3641.015.30 91.3641.015.81	91.3641.019.30 91.3641.019.81	91.3641.218.30 91.3641.218.81	91.3651.015.30 91.3651.015.81	91.3551.017.30 91.3551.017.81	91.3691.290.30 91.3691.290.81
Mortar 280 ml (91.3600.010.00)	26	26	18	26	26	32


ONLEVEL
ADVANCED RAILING TECHNOLOGY


Accessories

Gap filler



Fills the gaps between two glass panels. Please observe a maximum distance of 30 mm. However, the rubber seal can also easily be trimmed to the desired length

| Length: 200 mm



Model 7010	12-13,5 mm	15 mm	16-17,5 mm	19 mm	20-21,5 mm	24-25,5 mm	30-31,5 mm	
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
200 mm	90.7010.012.60	90.7010.015.60	90.7010.016.60	90.7010.019.60	90.7010.020.60	90.7010.024.60	90.7010.030.60	

Shims (plastic)



| Material: plastic

Model 7034 (Set of 50 pieces of each thickness)	
Thicknesses	Art. no.
1, 2, 3, 4, 5, 10 mm	90.7034.000.40


Model 7034 (50 pieces per thickness)					
Thickness	Art. no.	Thickness	Art. no.	Thickness	Art. no.
1 mm	90.7034.001.40	3 mm	90.7034.003.40	5 mm	90.7034.00540
2 mm	90.7034.002.40	4 mm	90.7034.004.40	10 mm	90.7034.010.40

Shims (aluminium)



Unique stepped design for a more flexible height and side adjustment

| Suitable for adjustments of 1 - 6.5 mm
| Material: Aluminium
| Sales unit: 20 pieces




Model 7012	Mill finish
	Art. no.
	90.7012.012.10

Shims

Use shims for more flexibility in height and side adjustment. **Mounting tip:** for perfect levelling, place shims beneath the glass profile



90.7012.012.10



Accessories | Demos

Glass stop



| For applications on stairs
| Includes self-tapping countersunk screws Ø 4,2 x 19 mm
| Mounting aid, not required when mounted on stairs.
| Max. weight 80 kg
| Sales unit: 2 pieces

Model 7009	Plastic
Strength	Art. no.
1.0kN	90.7009.001.41
2,0kN/3,0kN	90.7009.003.41



Rubber seal



Do you want to mount your profiles but not yet the glass?
The construction site is dirty and you would like to save cleaning time?
Then simply use our rubber seals. In this way, for sure no dirt will reach your profile.

| Sales unit: 1 piece

Model 2002/2005		Plastic
Length	KN	Art. no.
5 m	1	90.2005.100.60
5 m	3	90.2005.300.60

Top Cover Slim / Plus - demo



| Length: 200 mm

Top Cover Slim

Model 8010	Aluminium natural anod.
Width	Art. no.
3 mm	81.8010.030.11
10 mm	81.8010.100.11
15 mm	81.8010.150.11
20 mm	81.8010.200.11
120 mm	81.8011.200.11

Top Cover Plus

Model 8030	Aluminium natural anod.
Width	Art. no.
3 mm	81.8030.030.11
10 mm	81.8030.100.11
20 mm	81.8030.200.11

Floor Connect Slim / Plus - demo



| Length: 200 mm

Floor Connect Slim

Model 8110	Aluminium natural anod.
Width	Art. no.
20 mm	81.8110.200.11

Floor Connect Plus

Model 8130	Aluminium natural anod.
Width	Art. no.
20 mm	81.8130.200.11

Accessories for assembly with DOWSIL 993

These products are particularly suitable for mounting bent profiles.

BendFit silicone adhesive



- 2-component adhesive
- Forms a bond with glass
- No bonding over the entire length required
- A 300-gram cartridge is required per metre (bonded on two sides)
- Colour: black

Model 0200	
Content	Art. no.
300 g	90.0200.300.00
545 g	90.0200.545.00

BendFit mixing spindle



- reusable
- The mixing spindle serves for mixing the adhesive with the 2nd component directly in the cartridge.
- Sales unit: 1 piece

Model 7060	
	Art. no.
	90.7060.020.00

BendFit application gun



- Sales unit: 1 piece

Model 0201	
For cartridge	Art. no.
300 g	90.0201.300.00
545 g	90.0201.545.00

BendFit hand cleaning wipes



- For cleaning the mixing spindle
- Sales unit: 90 pieces

Model 7060	
	Art. no.
	90.7060.010.00

BendFit surface cleaner



- Degreases glass and profile before bonding
- Contents 1000 ml

Model 7060	
	Art. no.
	90.7060.015.00

Accessories for assembly with DOWSIL 993

BendFit silicone cartridge holder



- Reusable
- For fixing the adhesive cartridge during mixing
- Sales unit: 1 piece

Model 7060	
	Art. no.
	90.7060.021.00


BendFit multi-purpose disassembly tool



- Tool for de-mounting
- Not required for mounting
- Sales unit: 1 piece

Model 7061	black
	Art. no.
	90.7061.000.00

ASSEMBLY WITH DOWSIL 993




Silicone adhesive DOWSIL 993
Mounting: punctual
Art.no.: 90.0200.300.00
Width: min. 100 mm
Height: min. 20 mm
Quantity: min. 8x / 2,5 m
Distance: min. 212,5 mm

Accessories | Demos

FlexFit glass adjustment tool



- For FlexFit glass mounting set
- Zinc-plated steel




Model 0100	Art. no.	H
0,5 kN	90.0100.112.00	105 mm
1,0 & 2,0 kN	90.0100.110.00	140 mm

Combi tool



- For FlexFit glass mounting set
- Zinc-plated steel



Model 0100	Art. no.
	90.0100.100.00

TRANSLEVEL glass profile - demo



- Without glass
- Length: 200 mm

Top mount

	Aluminium natural anodised
	Art. no.
TL-3010	81.3010.000.11
TL-3080	81.3080.000.11
TL-3120	81.3120.000.11
TL-4010	81.4010.000.11
TL-5010	81.5010.000.11
TL-6020	81.6020.000.11
TL-6030	81.6030.000.11
TL-6080	81.6080.000.11
TL-6500	81.6500.000.11

Side mount

	Aluminium natural anodised
	Art. no.
TL-3011	81.3011.000.11
TL-3031	81.3031.000.11
TL-3121	81.3121.000.11
TL-6021	81.6021.000.11
TL-6081	81.6081.000.11
TL-6501	81.6501.000.11

In floor mount

TL-1010	81.1010.000.11

Accessories

Transformer



| 24 V
| Sales unit: 1 piece

Model 3000		
Watts	up to a length of	Art. no.
100 W	10 m	18.3000.100.00

LED strip, warm white



| 24 V
| 6 W/m
| Sales unit: 1 piece

Model 3106	
length	Art. no.
2.5 m	18.3106.002.00
5 m	18.3106.005.00
10 m	18.3106.010.00

Cable



| 230 V
| Sales unit: 1 piece

Model 9001	
length	Art. no.
10 m	18.9001.010.00
20 m	18.9001.020.00

| 24 V
| Sales unit: 1 piece

Model 9001	
length	Art. no.
6 m	18.9017.006.00
11 m	18.9017.011.00

Y cable



Do you need LED illumination on more than 10 m? No problem at all! With this Y cable, you can extend your LAZORTRACK by up to 50 m. Simply connect the next mains adapter together with the LED to the power supply and your illumination is there.


| Sales unit: 1 piece

Model 9003	
	Art. no.
	18.9003.010.00

Cable cover



| Length: 4 m
| 30 x 28 x 2 mm
| U 26 mm
| For glass thicknesses up to 21,5 mm
| Sales unit: 1 piece



Model 2115	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
5 m	11.2115.302.10	11.2115.302.11	11.2115.302.13/16/18/19


Accessories

Straight connector



| Sales unit: 1 piece


Model 4200	
	Art. no.
	18.2200.420.15



Glass rubber, 26 mm




| U handrail rubber seals for 26 mm



Model 6530	8 – 11 mm	11,5 - 13,5 mm	15 mm	16 - 17,5 mm	19 mm	20 - 21,5 mm
Length	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
5 m	90.6530.508.60	90.6530.511.60	90.6530.515.60	90.6530.516.60	90.6530.519.60	90.6530.520.60
25 m	90.6530.208.60	90.6530.211.60	90.6530.215.60	90.6530.216.60	90.6530.219.60	90.6530.220.60

How to extend the LED strip:



Stainless steel adhesive



Suitable for plug connections (e.g. handrail – handrail support) which are adjusted to each other in diameter.


| Colour: green
| Sales unit: 1 piece

Model 7005	
Contents	Art. no.
50 ml	90.7005.000.11

U-profile - demo (AISI 316)



| Length: 200 mm




Model 2105	**AISI 316 (outdoor)**
Diameter	Art. no.
Ø 42,4 mm	81.2105.421.31

U-profile - demo (aluminium)



| Length: 200 mm




Model 2115	**Aluminium natural anodised**
H x W	Art. no.
26 x 23 mm	81.2115.262.11
30 x 28 mm	81.2115.302.11

U-profile - demo (AISI 316)



| Length: 200 mm



Model 2115	**AISI 316 (outdoor)**
H x W	Art. no.
26 x 20 mm	81.2115.262.31
30 x 25 mm	81.2115.302.31
40 x 30 mm	81.2115.402.31

2



POST GLASS BALUSTRADES

Posts | parts

GUARDIAN OF THE UNIVERSE®

ENGINEERED IN GERMANY

Top mount | Side mount | Public use (medium crowd)

GUARDIAN OF THE UNIVERSE
A strong and secured fall protection balcony system for your home.

Our Railings are a range of innovative railing systems designed to be fully modular. The pre-assembled aluminium posts have a stunning satin anodised finish and are available in square profiles ready to install.

Fully engineered to meet the requirements of most applications, the systems can be installed with or without a top rail to provide an economical solution for a post and glass panel design. Each system can be fully fitted using basic equipment.

Essential features
- Aluminum-glass balustrade system
- Pre-assembled aluminium posts
- Strong, stable, secured
- Slick and elegant
- Aluminium & satin anodised finish
- High safety standards
- Fully modular
- Quick and simple, plug and play installation method
- Suitable for 10,76 mm
- Post centre to centre distance 1200 mm
- Maximum glass width 1175 mm
- Suitable for indoor & outdoor installations
- Posts available in bolt-down & side-fix

Country-specific approvals for GUARDIAN OF THE UNIVERSE

Region	Line load	Certification / calculated
DE	1,0 kN/m	AbP / DIN18008 calculated
NL	1,0 kN/m	NEN2608 calculated

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.



ONLEVEL
ADVANCED RAILING TECHNOLOGY

Top mount | Public use (medium crowd)

End post, top closed



- **Pre-assembled post with end cap and cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5011.110.10	13.5011.110.11	13.5011.110.13/16/18/19

Mid post, top closed



- **Pre-assembled post with end cap and cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5021	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5021.110.10	13.5021.110.11	13.5021.110.13/16/18/19


Corner post, top closed



- **Pre-assembled post with end cap and cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece



Anchor quantity per post	Model 5031	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5031.110.10	13.5031.110.11	13.5031.110.13/16/18/19





ONLEVEL
ADVANCED RAILING TECHNOLOGY

Top mount | Public use (medium crowd)

End post, top open



- **Pre-assembled post with end cap and cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5012	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5012.110.10	13.5012.110.11	13.5012.110.13/16/18/19

Mid post, top open



- **Pre-assembled post with end cap and cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5022	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5022.110.10	13.5022.110.11	13.5022.110.13/16/18/19


Corner post, top open



- **Pre-assembled post with end cap and cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece



Anchor quantity per post	Model 5032	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5032.110.10	13.5032.110.11	13.5032.110.13/16/18/19



ONLEVEL

ADVANCED RAILING TECHNOLOGY




Top mount | Public use (medium crowd)

End post, handrail



- **Pre-assembled post with cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5013	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5013.110.10	13.5013.110.11	13.5013.110.13/16/18/19

Mid post, handrail



- **Pre-assembled post with cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5023	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5023.110.10	13.5023.110.11	13.5023.110.13/16/18/19


Corner post, handrail



- **Pre-assembled post with cover cap**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1100 mm
- Sales unit: 1 piece



Anchor quantity per post	Model 5033	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5033.110.10	13.5033.110.11	13.5033.110.13/16/18/19





ONLEVEL
ADVANCED RAILING TECHNOLOGY

Side mount | Public use (medium crowd)

End post, top closed



- **Pre-assembled post with end cap and end cap bottom**
- Glass thickness 10,76 mm
- 58 x 65 mm, length: 1400 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5511.140.10	13.5511.140.11	13.5511.140.13/16/18/19

Mid post, top closed



- **Pre-assembled post with end cap and end cap bottom**
- Glass thickness 10,76 mm
- 58 x 65 mm, length: 1400 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5521.140.10	13.5521.140.11	13.5521.140.13/16/18/19


Corner post, top closed




- **Pre-assembled post with end cap and end cap bottom**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1400 mm
- Sales unit: 1 piece



Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
4	1,1 m	13.5531.140.10	13.5531.140.11	13.5531.140.13/16/18/19



CUTTING DRILLING BENDING POWDER COATING



ONLY YOU

LESS WORK. LESS WASTE. READY TO INSTALL.

With ONLY YOU, we customize ONLEVEL products to your exact project requirements – precisely, efficiently and ready to install. From cutting and drilling to bending and powder coating, we deliver exactly what you need, reducing work and waste on site and giving you more time for what matters: installation.

HOW IT WORKS

Use **ONLEVEL Studio** to create your project configuration. We will review your configuration, check the feasibility and provide you with a quote and delivery time.

WE NEED FROM YOU

A sketch, your **ONLEVEL Studio** configuration, dimensions, quantities, finish (e.g. RAL colour) and delivery deadline.

studio.onlevel.com

FROM STANDARD PROFILE TO YOUR PROJECT-READY PRODUCT

1 → 2 → 3 → 4

1 STANDARD ONLEVEL PROFILE

High quality standard profile from our range.

2 ONLY YOU CUSTOMIZATION



CUT TO SIZE
Profiles cut to the lengths your project requires.



DRILLING
Additional or project-specific machining according to your requirements.



BENDING
Profiles shaped to suit bent and individual designs.



POWDER COATING
In the RAL colour you specify.

3 FINISHED ACCORDING TO YOUR SPECIFICATIONS

Customized, finished and checked to your specifications.

4 READY FOR INSTALLATION


Delivered ready to install. Less work on site, more time for what matters.

Side mount | Public use (medium crowd)

End post, top open



- **Pre-assembled post with end cap and end cap bottom**
- Glass thickness 10,76 mm
- 58 x 65 mm, length: 1400 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5512.140.10	13.5512.140.11	13.5512.140.13/16/18/19

Mid post, top open



- **Pre-assembled post with end cap and end cap bottom**
- Glass thickness 10,76 mm
- 58 x 65 mm, length: 1400 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5522.140.10	13.5522.140.11	13.5522.140.13/16/18/19


Corner post, top open



- **Pre-assembled post with end cap and end cap bottom**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1400 mm
- Sales unit: 1 piece



Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
4	1,1 m	13.5532.140.10	13.5532.140.11	13.5532.140.13/16/18/19





ONLEVEL
ADVANCED RAILING TECHNOLOGY

Side mount | Public use (medium crowd)

End post, top handrail



- **Pre-assembled post with end cap bottom**
- Glass thickness 10,76 mm
- 58 x 65 mm, length: 1400 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5513.140.10	13.5513.140.11	13.5513.140.13/16/18/19

Mid post, top handrail



- **Pre-assembled post with end cap bottom**
- Glass thickness 10,76 mm
- 58 x 65 mm, length: 1400 mm
- Sales unit: 1 piece




Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
2	1,1 m	13.5523.140.10	13.5523.140.11	13.5523.140.13/16/18/19


Corner post, top handrail



- **Pre-assembled post with end cap bottom**
- Glass thickness 10,76 mm
- 58 x 58 mm, length: 1400 mm
- Sales unit: 1 piece



Anchor quantity per post	Model 5011	Mill finish	Aluminium natural anod.	RAL coloured
	Length	Art. no.	Art. no.	Art. no.
4	1,1 m	13.5533.140.10	13.5533.140.11	13.5533.140.13/16/18/19



POST GLASS BALUSTRADES

Glass edge protection

GUARDIAN OF THE UNIVERSE®

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Glass edge protection

Profile



STAINLESS STEEL - brushed




- For glass thickness 10,76 - 11,52 mm
- Thickness: 1 mm
- Self-adhesive
- Sales unit: 1 piece

Model 2111/2110/2112/2113/2114			AISI 316 brushed
Length	Width (B)	Glass thickness (G)	Art. no.
1 m	14 mm	10,76 – 11,52 mm	12.2111.141.31
1,5 m	14 mm	10,76 – 11,52 mm	12.2110.141.31
2 m	14 mm	10,76 – 11,52 mm	12.2112.141.31
3 m	14 mm	10,76 – 11,52 mm	12.2113.141.31
4 m	14 mm	10,76 – 11,52 mm	12.2114.141.31

Corner 90°






- Height 6 mm
- Thickness 1 mm
- Center axis length each 370 mm
- For glass thickness 10,76 - 11,52 mm
- Self-adhesive
- Sales unit: 1 piece

Model 2210	AISI 316 brushed
	Art. no.
	11.2210.141.31

Profile



ALUMINIUM




- For glass thickness 10,76 - 11,52 mm
- Thickness: 1 mm
- Self-adhesive
- The adhesive tape is supplied separately (.10)
- Sales unit: 1 piece

Model 2111/2110/2112/2113/2114			Mill finish	Aluminium natural anod.	RAL coloured
Length	Width (B)	Glass thickness (G)	Art. no.	Art. no.	Art. no.
1 m	14 mm	10,76 – 11,52 mm	11.2111.141.10	11.2111.141.11	11.2111.141.13/16/18/19
1,5 m	14 mm	10,76 – 11,52 mm	11.2110.141.10	11.2110.141.11	11.2110.141.13/16/18/19
2 m	14 mm	10,76 – 11,52 mm	11.2112.141.10	11.2112.141.11	11.2112.141.13/16/18/19
3 m	14 mm	10,76 – 11,52 mm	11.2113.141.10	11.2113.141.11	11.2113.141.13/16/18/19
4 m	14 mm	10,76 – 11,52 mm	11.2114.141.10	11.2114.141.11	11.2114.141.13/16/18/19

Corner 90°





- Height 7 mm
- Thickness 1 mm
- Center axis length each 370 mm
- For glass thickness 10,76 - 11,52 mm
- Self-adhesive
- Sales unit: 1 piece

Model 2210	Mill finish	Plain aluminium	Aluminium RAL
	Art. no.	Art. no.	Art. no.
	11.2210.141.10	11.2210.141..11	11.2210.141..13/16/18/19

ONLEVEL surface finishes
11.2111.141.**10/11/13/16/18/19**

See pages 8 and 19 for more information and order options.

POST GLASS BALUSTRADES

Handrails | parts

GUARDIAN OF THE UNIVERSE®

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Handrails

Handrail



- 79 x 37 mm
- Sales unit: 1 piece




Model 2102	2,5 m	5 m
Colour	Art. no.	Art. no.
mill finish	13.2102.070.10	13.2105.070.10
natural anodised	13.2102.070.11	13.2105.070.11
RAL shiny	13.2102.070.13	13.2105.070.13
RAL struct.	13.2102.070.16	13.2105.070.16
RAL matt	13.2102.070.18	13.2105.070.18
ARMOR RAL	13.2102.070.19	13.2105.070.19

Handrail corner 90°



- 79 x 37 mm
- Length: 380 mm
- Sales unit: 1 piece




Model 2210	
Colour	Art. no.
mill finish	13.2210.070.10
natural anodised	13.2210.070.11
RAL shiny	13.2210.070.13
RAL struct.	13.2210.070.16
RAL matt	13.2210.070.18
ARMOR RAL	13.2210.070.19

Handrail wall connector



- 79 x 37 mm
- Sales unit: 2 pieces




Model 2220	
Colour	Art. no.
mill finish	13.2220.070.10
natural anodised	13.2220.070.11
RAL shiny	13.2220.070.13
RAL struct.	13.2220.070.16
RAL matt	13.2220.070.18
ARMOR RAL	13.2220.070.19

Handrail end cap



- 79 x 37 mm
- Sales unit: 2 pieces



Model 2300	
Colour	Art. no.
mill finish	13.2300.070.10
natural anodised	13.2300.070.11
RAL shiny	13.2300.070.13
RAL struct.	13.2300.070.16
RAL matt	13.2300.070.18
ARMOR RAL	13.2300.070.19

Handrails

Extension pin



- Length: 40 mm
- Diameter: Ø 6 mm
- Sales unit: 8 pieces




Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31

Inline connector



- For use with rectangular handrails
- Internal fix. Supplied with four screws.
- Sales unit: 1 piece




Model 4200	Plain aluminium
	Art. no.
	18.4200.420.15


Handrail corner connector, horizontally adjustable




- For use with rectangular handrails
- Internal fix. Supplied with four screws.
- Sales unit: 1 piece



Model 4210	Plain aluminium
	Art. no.
	18.4210.420.15





ONLEVEL
STUDIO

SMART DESIGN AND ORDERING



How it works

studio.onlevel.com

PDF DXF IFC STEP

ONLEVEL Studio is our online configurator. It lets you design and organise the installation of your glass balustrade free of charge. Available 24/7, whenever it suits you best.

Design your project. Visualise it in 3D. Configure different system setups. Compare product options. Automatically calculate which materials you need and how much, as well as the total costs, including transport. Create technical drawings and quotations. And order your materials directly.

Less calculating. Fewer mistakes. More control.

ONLEVEL Studio helps you automate complex work preparation. Get from idea to installation faster.

POST GLASS BALUSTRADES

Accessories | additionals

GUARDIAN OF THE UNIVERSE®

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Anchors

Mounting set for concrete (mechanical)




| M12
| Sales unit: 20 pieces




Model 3501 / 3601	Zinc-plated steel (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	91.3501.220.81 fischer	91.3501.220.30 fischer
	91.3601.220.81 MKT	91.3601.220.30 MKT

Mounting set for concrete (chemical)



| M12
| Sales unit: 10 pieces




Model 3551	Zinc-plated steel (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	91.3551.221.81 fischer	91.3551.221.30 fischer

Mounting set for steel (top mount)



| M12 x 50 mm
| Sales unit: 12 pieces




Model 5000	Zinc-plated steel (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	91.5000.050.81	91.5000.050.30

Mounting set for steel (side mount)



| M12 x 75 mm
| Sales unit: 12 pieces



Model 5000	Zinc-plated steel (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	91.5000.075.81	91.5000.075.30

Quick & easy

For further helpful information, please see our ONLEVEL website. Here you will find explanatory and installation videos, photos and downloads, as well as a configurator to help you with the glass calculations.

Accessories

Mortar



- For chemical bonding of anchors
- Including 2 mixers
- Sales unit: 1 piece

Model 3000	
	Art. no.
	91.3000.010.00

Dispensing device



- For use with mortar (91.3000.010.00)
- Sales unit: 1 piece

Model 3002	Plastic
	Art. no.
Gun	91.3002.010.00
Mixer	91.3002.011.00

Airpump



- For blowing out the drill holes
- Sales unit: 1 piece

Model 3001	Plastic
	Art. no.
	91.3001.010.00

Anchor hole brush



- For cleaning the drill holes
- Ø 12 mm
- Sales unit: 1 piece

Model 3002	Plastic
	Art. no.
	91.3002.012.00

Anchor hole fillings per mortar cartridge

GUARDIAN OF THE UNIVERSE®


Anchors	91.3551.221.30 91.3551.221.81
Mortar 390 ml (91.3000.010.00)	23

Accessories

Drill positioning tool for handrail



- For handrail 79x37 mm
- Sales unit: 1 piece




Model 9005	Plastic
	Art. no.
	13.9005.070.41


Roof insulation post




- 58 x 58 mm
- Height: 200 mm
- Incl. rain cover
- Sales unit: 2 piecess



Model 9010	Zinc-plated steel
	Art. no.
	13.9010.200.81





End post, top closed - demo



Demo	Art. No.
	81.5011.000.11

POST GLASS BALUSTRADES

Mounting examples


GUARDIAN OF THE UNIVERSE®

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Mounting examples


Top mount, top closed




Side mount, top closed




Top mount, top open




Side mount, top open



Top mount, handrail



Side mount, handrail



3



GLASS WALLS

Profiles | parts

KAZIWALL®


Top mount | Public use (medium crowd)

Room height fall protection for indoor and outdoor use
The ONLEVEL KAZIWALL system is a premium glass partition solution engineered for environments where fall protection is essential. Combining robust stability with a sleek, minimalist design, KAZIWALL delivers both safety and aesthetic appeal.

Supplied as a prefabricated system, KAZIWALL ensures fast, efficient installation—saving time on site without compromising quality.

Available in both top-mount and side-mount configurations, the system accommodates glass thicknesses of 10,76, 12,76, 16,76, 17,52 and 21,52 mm, offering flexibility to meet a wide range of project requirements.


Essential features
- Easy and safe installation for single glass fixation method
- Max ceiling height 3,0 m
- Top mount and side mount
- For glass thickness 16,76 mm, 17,52 mm and 21,52 mm
- Standard glass width ≥ 1000 mm.
- Customized glass width also possible.
- Prefabricated system




Top mount | Public use (medium crowd)

1-part top and bottom profile






| Prefabricated System
| Sales unit: 1 piece



		Mill finish	Aluminium natural anod.	RAL coloured
Length	Glass thickness	Art. no.	Art. no.	Art. no.
2,5 m	10,76 mm / 12,76 mm	20.4002.011.10	20.4002.011.11	20.4002.011.13/16/18/19
5 m	10,76 mm / 12,76 mm	20.4005.011.10	20.4005.011.11	20.4005.011.13/16/18/19
2,5 m	16,76 mm / 17,52 mm	20.4002.017.10	20.4002.017.11	20.4002.017.13/16/18/19
5 m	16,76 mm / 17,52 mm	20.4005.017.10	20.4005.017.11	20.4005.017.13/16/18/19
2,5 m	21,52 mm	20.4002.022.10	20.4002.022.11	20.4002.022.13/16/18/19
5 m	21,52 mm	20.4005.022.10	20.4005.022.11	20.4005.022.13/16/18/19


2-part top and bottom profile





| Prefabricated System
| Sales unit: 1 piece

Note: Intermediate profiles in L = 900 mm
to secure each glass panel separately




		Mill finish	Aluminium natural anod.	RAL coloured
Length	Glass thickness	Art. no.	Art. no.	Art. no.
2,5 m	10,76 mm / 12,76 mm	20.4502.011.10	20.4502.011.11	20.4502.011.13/16/18/19
5 m	10,76 mm / 12,76 mm	20.4505.011.10	20.4505.011.11	20.4505.011.13/16/18/19
2,5 m	16,76 mm / 17,52 mm	20.4502.017.10	20.4502.017.11	20.4502.017.13/16/18/19
5 m	16,76 mm / 17,52 mm	20.4505.017.10	20.4505.017.11	20.4505.017.13/16/18/19
2,5 m	21,52 mm	20.4502.022.10	20.4502.022.11	20.4502.022.13/16/18/19
5 m	21,52 mm	20.4505.022.10	20.4505.022.11	20.4505.022.13/16/18/19

Endcap



| Sales unit: 8 pieces




Model 9010	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	20.9010.000.10	20.9010.000.11	20.9010.000.13/16/18/19

Top mount | Public use (medium crowd)

Wall profile



| Prefabricated System
| Length: 3 m
| Sales unit: 1 piece



	Mill finish	Aluminium natural anodised	RAL coloured
Glass thickness	Art. no.	Art. no.	Art. no.
10,76 mm / 12,76 mm	20.5003.011.10	20.5003.011.11	20.5003.011.13/16/18/19
16,76 mm / 17,52 mm	20.5003.017.10	20.5003.017.11	20.5003.017.13/16/18/19
21,52 mm	20.5003.022.10	20.5003.022.11	20.5003.022.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

Side mount | Public use (medium crowd)

Side profile, 1 piece



| Prefabricated System
| Sales unit: 1 piece

		Mill finish	Aluminium natural anod.	RAL coloured
Length	Glass thickness	Art. no.	Art. no.	Art. no.
2.5 m	10,76 mm / 12,76 mm	20.4102.011.10	20.4102.011.11	20.4102.011.13/16/18/19
5 m	10,76 mm / 12,76 mm	20.4105.011.10	20.4105.011.11	20.4105.011.13/16/18/19
2.5 m	16,76 mm / 17,52 mm	20.4102.017.10	20.4102.017.11	20.4102.017.13/16/18/19
5 m	16,76 mm / 17,52 mm	20.4105.017.10	20.4105.017.11	20.4105.017.13/16/18/19
2.5 m	21,52 mm	20.4102.022.10	20.4102.022.11	20.4102.022.13/16/18/19
5 m	21,52 mm	20.4105.022.10	20.4105.022.11	20.4105.022.13/16/18/19

Side profile, 2 pieces



| Prefabricated System
| Sales unit: 1 piece


Note: Intermediate profiles in L = 900 mm to secure each glass panel separately

		Mill finish	Aluminium natural anod.	RAL coloured
Length	Glass thickness	Art. no.	Art. no.	Art. no.
2.5 m	10,76 mm / 12,76 mm	20.4602.011.10	20.4602.011.11	20.4602.011.13/16/18/19
5 m	10,76 mm / 12,76 mm	20.4605.011.10	20.4605.011.11	20.4605.011.13/16/18/19
2.5 m	16,76 mm / 17,52 mm	20.4602.017.10	20.4602.017.11	20.4602.017.13/16/18/19
5 m	16,76 mm / 17,52 mm	20.4605.017.10	20.4605.017.11	20.4605.017.13/16/18/19
2.5 m	21,52 mm	20.4602.022.10	20.4602.022.11	20.4602.022.13/16/18/19
5 m	21,52 mm	20.4605.022.10	20.4605.022.11	20.4605.022.13/16/18/19

Endcap



| Sales unit: 8 pieces



Model 9010	Mill finish	Aluminium natural anod.	RAL coloured
	Art. no.	Art. no.	Art. no.
	20.9010.000.10	20.9010.000.11	20.9010.000.13/16/18/19

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

GLASS WALLS

Accessories | additionals

KAZIWALL®

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Anchors

Mounting set for concrete (mechanical)



| Sales unit: 50 pieces




Model 3521 / 3621	Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	Art. no.		Art. no.	
	91.3521.010.81	fischer	91.3521.010.30	fischer
	91.3621.010.81	MKT	91.3621.010.30	MKT

Mounting anchor for concrete (mechanical) - wall profile



| Sales unit: 50 pieces



Model 3581	Zinc-plated steel (indoor)		AISI 316 (outdoor)	
	Art. no.		Art. no.	
	91.3581.060.81	fischer	91.3581.060.30	fischer

Accessories

Joining tape



- Particularly suitable for applications where a transparent, flexible bond is required.
- For indoor use
- Length: 12 m, Thickness: 3 mm
- Sales unit: 1 piece

Model 7025		
Width	Glass thickness	Art. no.
5 mm	8 - 8,76 mm	90.7025.008.03
7 mm	10 - 10,76 mm	90.7025.010.03
9 mm	12 - 12,76 mm	90.7025.012.03
13 mm	16,76 - 17,52 mm	90.7025.016.03
17 mm	20,76 - 21,52 mm	90.7025.020.03

Mounting tool for joining tape




- Sales unit: 1 piece

Model 0100	
Glass thickness	Art. no.
8 - 8,76 mm	90.0100.170.08
10 - 10,76 mm	
12 - 12,76 mm	90.0100.170.12
16,76 - 17,52 mm	
20,76 - 21,52 mm	90.0100.170.16


Mounting tool




- Sales unit: 1 piece



Art. no.
90.0100.190.00



Function 1:
Support tool to hammer-in the intermediate profile




Function 2:
Demounting cover profile

4

JULIET BALCONIES

Profile sets

SKYFORCE®



ENGINEERED IN GERMANY

Public use (medium crowd)

With simple tools and just a few steps, you can easily and perfectly conceal the fall protection system behind the roller shutter guide rail. Naturally, SKYFORCE is compatible with every window profile. Thanks to the unique and purpose-designed slide-clip technology, it can be mounted directly onto the window frame or the masonry. And the best part is: with just one profile, all glass thicknesses, heights, and widths are covered.

The design?
Can you already picture it? Clean lines, elegant shapes – a system that not only protects but also inspires. SKYFORCE combines safety with style. Take a deep breath and enjoy the moment: feel the sense of freedom, openness, and space – along with the confidence that you can rely on maximum stability. SKYFORCE stands firm when it matters most – strong, reliable, and flawlessly beautiful. A protection system that doesn't limit your home, but expands it.

SKYFORCE – Safety in its most beautiful form.

Colour reimagined
No matter how far worlds may be apart – colours connect.
With our new range, you can turn your visions into reality: available in all RAL colours, individually and infinitely combinable. Give your project personality – from classic to modern, from subtle to expressive – the choice is yours.

SKYFORCE – Where safety meets colour dive


Tested systems
We from ONLEVEL strive to test your individual window/profile system. The huge variety of profile systems and frame designs throughout Europe, however, makes this task very hard for us. That´s why on your profile system, we have listed the profile criteria for a SKYFORCE installation according to the General Building Inspection Test Certificate for you.

If you take these criteria into account, an additional inspection will not be required – always provided that the window has also been installed as per fall protection requirements using our tested fixing anchors.

For an overview of the up-to-date tests, please see the supplementary sheet or get in touch with us.

Essential features
- Easy ordering thanks to packaging sets of 500, 700, 900, 1000, 1100, and 1200 mm.
- ONLEVEL prefabricated pystem Installation advantage of up to 30 minutes per set.
- Storage lengths of 5 m available.
- The only system with a drainage option as a protection against mould and breakage.
- Nearly tool-free installation.
- Colour design possible according to RAL.
- Suitable for plastic, aluminium, wooden and metal frames.
- General Building Inspection Test Certificate (AbP).
- Depending on the on-site situation, the glass can be installed either from the inside or the outside.

CUTTING DRILLING BENDING POWDER COATING



ONLY YOU

LESS WORK. LESS WASTE. READY TO INSTALL.

With ONLY YOU, we customize ONLEVEL products to your exact project requirements – precisely, efficiently and ready to install. From cutting and drilling to bending and powder coating, we deliver exactly what you need, reducing work and waste on site and giving you more time for what matters: installation.

HOW IT WORKS

Use **ONLEVEL Studio** to create your project configuration. We will review your configuration, check the feasibility and provide you with a quote and delivery time.

WE NEED FROM YOU

A sketch, your **ONLEVEL Studio** configuration, dimensions, quantities, finish (e.g. RAL colour) and delivery deadline.

studio.onlevel.com

FROM STANDARD PROFILE TO YOUR PROJECT-READY PRODUCT

1 → 2 → 3 → 4

1 STANDARD ONLEVEL PROFILE

High quality standard profile from our range.

2 ONLY YOU CUSTOMIZATION



CUT TO SIZE
Profiles cut to the lengths your project requires.



DRILLING
Additional or project-specific machining according to your requirements.



BENDING
Profiles shaped to suit bent and individual designs.



POWDER COATING
In the RAL colour you specify.

3 FINISHED ACCORDING TO YOUR SPECIFICATIONS

Customized, finished and checked to your specifications.

4 READY FOR INSTALLATION

Delivered ready to install. Less work on site, more time for what matters.

Glass dimensions

For glass dimensions, see the QR code below:

SKYFORCE TOP **SKYFORCE SLIM** **SKYFORCE SIDE**

Standard finishes and colours

ONLEVEL surface finish codes

10.3620.002.**10** → **.10** Aluminium mill finish
10.3620.002.**11** → **.11** Aluminium natural anodised
10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



Your preferred colour?
We will of course deliver your desired RAL colour.

ALUMINIUM



.10 Aluminium mill finish




.11 Aluminium anodised



.13 RAL glossy



.16 RAL structured matt




.18 RAL matt



.19 Armor RAL


Powder coated profiles (.13/.16/.18/.19) Warranty: The current ONLEVEL General Warranty Conditions apply. Please refer to these conditions for the applicable warranty periods.

Profile sets



Profile sets


Mounting distances for different lengths




Glass height (H)	500	700	900	1000	1100	1200
A	100	200	200	200	200	300
B	200	400	400	400	500	600
C	300	500	600	700	800	900
D	400	600	700	800	900	1000
E	-	-	800	900	1000	1100

Dimensions in mm

Glass dimensions complete set



Glass dimensions Centre piece



2-part complete set



| For edge protection, see page 231.
| Screws not included. For suitable fixing options, see the installation examples from page 221.

Glass height (H)	500 mm	700 mm	900 mm	1000 mm	1100 mm	1200 mm
Rubber set for	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
10,76 - 12,76 mm	16.1005.011.xx*	16.1007.011.xx*	16.1009.011.xx*	16.1010.011.xx*	16.1011.011.xx*	16.1012.011.xx*
17,52 - 21,52 mm	16.1005.018.xx*	16.1007.018.xx*	16.1009.018.xx*	16.1010.018.xx*	16.1011.018.xx*	16.1012.018.xx*

Centre piece, top mount




| For edge protection, see page 231.
| Screws not included. For suitable fixing options, see the installation examples from page 221.

Glass height (H)	500 mm	700 mm	900 mm	1000 mm	1100 mm	1200 mm
Rubber set for	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
10,76 - 12,76 mm	16.1505.011.xx*	16.1507.011.xx*	16.1509.011.xx*	16.1510.011.xx*	16.1511.011.xx*	16.1512.011.xx*
17,52 - 21,52 mm	16.1505.018.xx*	16.1507.018.xx*	16.1509.018.xx*	16.1510.018.xx*	16.1511.018.xx*	16.1512.018.xx*

* xx = surface finishes

SKYFORCE aluminium profiles are available in a range of surface finishes. In addition, you can choose from a variety of powder coatings in different RAL colours. See pages 210 and 211 for more information and order options.


Profile sets, 2-sided cover




Profile sets, 2-sided cover

Mounting distances for different lengths

Installation from the outside (façade side)




Installation from the inside (room side)




Glass dimensions

Glass installation from the outside (façade side)



Glass installation from the inside (room side)



Quick tip: Keep a distance of at least 5 mm between SKYFORCE Slim and the wall to clip on the cover after mounting.

2-part complete set, 2-sided




- SKYFORCE SLIM now with a reduced width from 37 mm, which makes SLIM especially suitable for narrow window frames
- Glass mounting can optionally be done either from outside or from inside.
- Heights of 500, 700, 900, 1000, 1100 and 1200 mm available in stock.
- For edge protection, see page 231.
- Screws not included. For suitable fixing options, see the installation examples from page 221.

Glass height (H)	500 mm	700 mm	900 mm	1000 mm	1100 mm	1200 mm
Rubber set for	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
10,76 - 12,76 mm	16.3005.011.xx*	16.3007.011.xx*	16.3009.011.xx*	16.3010.011.xx*	16.3011.011.xx*	16.3012.011.xx*
17,52 - 21,52 mm	16.3005.018.xx*	16.3007.018.xx*	16.3009.018.xx*	16.3010.018.xx*	16.3011.018.xx*	16.3012.018.xx*

* xx = surface finishes

SKYFORCE aluminium profiles are available in a range of surface finishes. In addition, you can choose from a variety of powder coatings in different RAL colours. See pages 210 and 211 for more information and order options.


Profile sets, 1-sided cover




Profile sets, 1-sided cover

Mounting distances for different lengths

Installation from the outside (façade side)




Installation from the inside (room side)




Glass dimensions

Glass installation from the outside (façade side)



Glass installation from the inside (room side)



Quick tip: Keep a distance of at least 5 mm between SKYFORCE Slim and the wall to clip on the cover after mounting.

2-part complete set, 1-sided




- SKYFORCE SLIM now with a reduced width from 37 mm, which makes SLIM especially suitable for narrow window frames
- Glass mounting can optionally be done either from outside or from inside.
- Heights of 500, 700, 900, 1000, 1100 and 1200 mm available in stock.
- For edge protection, see page 231.
- Screws not included. For suitable fixing options, see the installation examples from page 221.

Glass height (H)	500 mm	700 mm	900 mm	1000 mm	1100 mm	1200 mm
Rubber set for	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
10,76 - 12,76 mm	16.3105.011.xx*	16.3107.011.xx*	16.3109.011.xx*	16.3110.011.xx*	16.3111.011.xx*	16.3112.011.xx*
17,52 - 21,52 mm	16.3105.018.xx*	16.3107.018.xx*	16.3109.018.xx*	16.3110.018.xx*	16.3111.018.xx*	16.3112.018.xx*

* xx = surface finishes


SKYFORCE aluminium profiles are available in a range of surface finishes. In addition, you can choose from a variety of powder coatings in different RAL colours. See pages 210 and 211 for more information and order options.

Profile sets




Profile sets

Mounting distances for different lengths



Glass dimensions



Glass height (H)	500	700	900	1000	1100	1200
A	100	100	200	200	300	300
B	200	300	400	500	600	600
C	300	500	700	800	900	1000
D	400	600	800	900	1000	1100

Dimensions in mm

2-part complete set



- For edge protection, see page 231.
- Screws not included. For suitable fixing options, see the installation examples from page 221.

Glass height (H)	500 mm	700 mm	900 mm	1000 mm	1100 mm	1200 mm
Rubber set for	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.	Art. no.
10,76 - 12,76 mm	16.2005.011.xx*	16.2007.011.xx*	16.2009.011.xx*	16.2010.011.xx*	16.2011.011.xx*	16.2012.011.xx*
17,52 - 21,52 mm	16.2005.018.xx*	16.2007.018.xx*	16.2009.018.xx*	16.2010.018.xx*	16.2011.018.xx*	16.2012.018.xx*

* xx = surface finishes

SKYFORCE aluminium profiles are available in a range of surface finishes. In addition, you can choose from a variety of powder coatings in different RAL colours. See pages 210 and 211 for more information and order options.


ONLEVEL
ADVANCED RAILING TECHNOLOGY

JULIET BALCONIES

Mounting examples


SKYFORCE®


ONLEVEL

ADVANCED RAILING TECHNOLOGY

Mounting on the cover frame - **Plastic**


SKYFORCE Top





SKYFORCE Slim






Quick tip: Keep a distance of at least 5 mm between SKYFORCE Slim and the wall to clip on the cover after mounting.

Mounting on the cover frame - **Overlapping**

SKYFORCE Slim






Lmin. (screw) = H (frame) + 5 mm

Installation shutter guide profile

SKYFORCE Top





As an option, installation with a distance sleeve is also possible. For distance sleeve, see page 233.

Lmin. (screw) = B + 25 mm


Fixation - **Plastic**

Self-tapping fixing screw



SKYFORCE TOP SKYFORCE SLIM

- Plastic frame: The screw needs a 1,5 mm steel core in the frame profile.
- Material: steel, Zinc-plated
- The number of fixings can be taken from the test report.




Model 9005			**Steel, Zinc-plated**	
L	B	C (min.)	Art. no. – sales unit **12**	Art. no. – sales unit **100**
45 mm	0 - 14 mm	35 mm	16.9005.604.81	16.9015.604.81
55 mm	15 - 24 mm	45 mm	16.9005.605.81	16.9015.605.81
65 mm	25 - 34 mm	55 mm	16.9005.606.81	16.9015.606.81
75 mm	35 - 44 mm	65 mm	16.9005.607.81	16.9015.607.81
85 mm	45 - 54 mm	75 mm	16.9005.608.81	16.9015.608.81
95 mm	55 - 64 mm	85 mm	16.9005.609.81	16.9015.609.81
105 mm	65 - 74 mm	95 mm	16.9005.610.81	16.9015.610.81
125 mm	85 - 94 mm	115 mm	16.9005.612.81	16.9015.612.81
150 mm	110 - 119 mm	140 mm	16.9005.615.81	16.9015.615.81

Fixing screw



SKYFORCE TOP

- The anchors are not self-tapping and must be pre-drilled (16.9011.05x.00).
- Finish outdoor application: AISI 304
- Ø 6,3 mm
- Sales unit: 12 pieces



Model 9012		**AISI 304**
Length	B	Art. no.
50 mm	0 - 25 mm	16.9012.605.20
64 mm	25 - 40 mm	16.9012.606.20
75 mm	40 - 50 mm	16.9012.607.20
82 mm	50 - 55 mm	16.9012.608.20

Model 9012		**AISI 304**
Length	B	Art. no.
92 mm	55 - 65 mm	16.9012.609.20
102 mm	65 - 75 mm	16.9012.610.20
115 mm	75 - 90 mm	16.9012.611.20

Drill



For pre-drilling holes for mounting stainless steel screw 16.9012.6xx.20

- Ø 5 mm (for 1,5 mm wall thickness)
- Ø 5.3 mm (for 2,0 – 4,0 mm wall thickness)
- Sales unit: 1 piece

Model 9011	
Ø	Art. no.
5,0 mm	16.9011.050.00
5,3 mm	16.9011.053.00

Self-tapping fixing screw




SKYFORCE SLIM


- Plastic frame: The screw needs a 1,5 mm steel core in the frame profile.
- Material: AISI 304
- Ø 5,5 mm

Model 9031/32		**AISI 304**
Length	B	Art. no. – **VE 12**
32 mm	0 – 12 mm	16.9032.632.20
50 mm	0 - 30 mm	16.9032.650.20


Mounting on the cover frame - **Aluminium**


SKYFORCE Top





SKYFORCE Slim





Quick tip: Keep a distance of at least 5 mm between SKYFORCE Slim and the wall to clip on the cover after mounting.


Fixation - **Aluminium**

Self-tapping fixing screw



SKYFORCE TOP

- Aluminium frame: screw length max. 45 mm
- Material: steel, Zinc-plated
- The number of fixings can be taken from the test report.




Model 9005			**Steel, Zinc-plated**	
L	B	C (min.)	Art. no. – sales unit **12**	Art. no. – sales unit **100**
45 mm	0 - 14 mm	35 mm	16.9005.604.81	16.9015.604.81
55 mm	15 - 24 mm	45 mm	16.9005.605.81	16.9015.605.81

Fixing anchor



SKYFORCE TOP

- Surface finish outdoor application: AISI 316 (outdoor)
- Sales unit: 12 pieces



Model 9006	**AISI 316 (outdoor)**
	Art. no.
	16.9006.835.30

Self-tapping fixing screw




SKYFORCE SLIM


- Material: AISI 304
- Ø 5,5 mm

Model 9031/32		**AISI 304 (indoor)**
Length	B	Art. no. – sales unit **12**
32 mm	0 – 12 mm	16.9032.632.20
50 mm	0 - 30 mm	16.9032.650.20

Mounting on the cover frame - **Wood**


SKYFORCE Top







SKYFORCE TOP – central post





SKYFORCE Slim






Quick tip: Keep a distance of at least 5 mm between SKYFORCE Slim and the wall to clip on the cover after mounting.

Fixation - **Wood**

Shutter guide rail




Fixing screw



SKYFORCE TOP | SKYFORCE SLIM | SKYFORCE SIDE


- Finish outdoor application: AISI 316 (outdoor)
- Ø 5,5 mm
- Sales unit: 12 pieces




Model 9007	AISI 316 (outdoor)
L	Art. no.
60 mm	16.9007.660.30
80 mm	16.9007.680.30
100 mm	16.9007.699.30


Mounting on the cover frame - **Wood–aluminium**


SKYFORCE Top







SKYFORCE TOP – central post





SKYFORCE Slim





Quick tip: Keep a distance of at least 5 mm between SKYFORCE Slim and the wall to clip on the cover after mounting.


Mounting on the cover frame - **Wood–aluminium**

Fixing screw



SKYFORCE TOP | SKYFORCE SLIM | SKYFORCE SIDE

- Finish exterior application: AISI 316 (outdoor)
- Ø 5,5 mm
- Sales unit: 12 pieces



Model 9007	AISI 316 (outdoor)
L	Art. no.
60 mm	16.9007.660.30
80 mm	16.9007.680.30
100 mm	16.9007.699.30

Quick & easy

For further helpful information, please see our ONLEVEL website. Here you will find explanatory and installation videos, photos and downloads, as well as a configurator to help you with the glass calculations.

Mounting on **concrete**

SKYFORCE Side



Mounting on **solid stone**

SKYFORCE Side




Mounting set (mechanical)



SKYFORCE SIDE

For solid stone with a dense texture

| Sales unit: 10 pieces



Model 9029	AISI 316 (outdoor)
	Art. no.
	16.9029.835.30

JULIET BALCONIES

Glass edge protection

SKYFORCE®

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Glass edge protection

Profile



STAINLESS STEEL - brushed




- Height: 6 mm
- Thickness: 1 mm
- Self-adhesive
- Sales unit: 1 piece

Model 2111/2110/2112/2113/2114	AISI 316 brushed			
Width (B)	**14 mm**	**16 mm**	**20 mm**	**24 mm**
Glass thickness (G)	**10,76 – 11,52 mm**	**12,76 – 13,52 mm**	**16,76 – 17,52 mm**	**20,76 - 21,52 mm**
Length	Art. no.	Art. no.	Art. no.	Art. no.
1 m	12.2111.141.31	12.2111.161.31	12.2111.201.31	12.2111.241.31
1,5 m	12.2110.141.31	12.2110.161.31	12.2110.201.31	12.2110.241.31
2 m	12.2112.141.31	12.2112.161.31	12.2112.201.31	12.2112.241.31
3 m	12.2113.141.31	12.2113.161.31	12.2113.201.31	12.2113.241.31
4 m	12.2114.141.31	12.2114.161.31	12.2114.201.31	12.2114.241.31

Profile



ALUMINIUM



- Height: 7 mm
- Thickness: 1 mm
- Self-adhesive
- The adhesive tape is supplied separately (.10)
- Sales unit: 1 piece

Model 2111/2110/2112/2113/2114			Mill finish	Aluminium natural anod.	RAL coloured
Length	Width (B)	Glass thickness (G)	Art. no.	Art. no.	Art. no.
1 m	14 mm	10,76 – 11,52 mm	11.2111.141.10	11.2111.141.11	11.2111.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2111.161.10	11.2111.161.11	11.2111.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2111.201.10	11.2111.201.11	11.2111.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2111.241.10	11.2111.241.11	11.2111.241.13/16/18/19
	28 mm	25 - 25,52 mm	–	11.2111.281.11	–
1,5 m	14 mm	10,76 – 11,52 mm	11.2110.141.10	11.2110.141.11	11.2110.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2110.161.10	11.2110.161.11	11.2110.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2110.201.10	11.2110.201.11	11.2110.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2110.241.10	11.2110.241.11	11.2110.241.13/16/18/19
	28 mm	25 - 25,52 mm	–	11.2110.281.11	–
2 m	14 mm	10,76 – 11,52 mm	11.2112.141.10	11.2112.141.11	11.2112.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2112.161.10	11.2112.161.11	11.2112.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2112.201.10	11.2112.201.11	11.2112.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2112.241.10	11.2112.241.11	11.2112.241.13/16/18/19
	28 mm	25 - 25,52 mm	–	11.2112.281.11	–
3 m	14 mm	10,76 – 11,52 mm	11.2113.141.10	11.2113.141.11	11.2113.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2113.161.10	11.2113.161.11	11.2113.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2113.201.10	11.2113.201.11	11.2113.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2113.241.10	11.2113.241.11	11.2113.241.13/16/18/19
	28 mm	25 - 25,52 mm	–	11.2113.281.11	–
4 m	14 mm	10,76 – 11,52 mm	11.2114.141.10	11.2114.141.11	11.2114.141.13/16/18/19
	16 mm	12,76 – 13,52 mm	11.2114.161.10	11.2114.161.11	11.2114.161.13/16/18/19
	20 mm	16,76 – 17,52 mm	11.2114.201.10	11.2114.201.11	11.2114.201.13/16/18/19
	24 mm	20,76 - 21,52 mm	11.2114.241.10	11.2114.241.11	11.2114.241.13/16/18/19
	28 mm	25 - 25,52 mm	–	11.2114.281.11	–

ONLEVEL surface finishes
11.2111.141.**10/11/13/16/18/19**

See pages 210 and 211 for more information and order options.



JULIET BALCONIES

Accessories | additionals

SKYFORCE®

ONLEVEL


ADVANCED RAILING TECHNOLOGY

Accessories

Overlap mounting strips

Without cover cap





With cover cap



SKYFORCE SLIM

- The mounting strip must be adapted to the height of SKYFORCE
- Material: AISI 304
- Sales unit: 2 mounting strips
- Screws need be ordered separately fitting to the window/door overlap thickness


Model 9036	AISI 304		
	Width x length	Art. no.	Cover cap colour
Without cover cap	15 x 1100 mm	16.9036.011.20	–
With cover cap	15 x 1100 mm	16.9036.011.42	White
With cover cap	15 x 1100 mm	16.9036.011.47	Grey


Fill profile set



If the window frame profile slopes, you can use the fill profile to fill the gap.

- H = 1100 mm
- Material: Plastic white
- fitting to article no. 16.9036.011.20






Model 9037	Plastic
	Art. no.
	16.9037.011.42

Fixing screws for overlap mounting strips



SKYFORCE SLIM

- Low round head screw
- Sales unit: 22 pieces




Model 1190	AISI 304
M x L	Art. no.
M6 x 10 mm	91.1190.610.20-22
M6 x 20 mm	91.1190.620.20-22
M6 x 22 mm	91.1190.616.20-22
M6 x 25 mm	91.1190.625.20-22
M6 x 30 mm	91.1190.630.20-22
M6 x 35 mm	91.1190.635.20-22



Overlap mounting strip

Cover cap




Accessories | Demos

Distance sleeve for fixing anchor



- Suitable for use with the shutter guide rail and wooden and aluminium frames (can be trimmed to size on site)
- Ø 16 mm
- Aluminium
- Sales unit: 10 pieces



Model 9320	Black anodised	RAL coloured
Length	B	Art. no.
10,5 mm	16.9320.010.15	16.9320.010.13/16/18
16 mm	16.9320.016.15	16.9320.016.13/16/18
20,5 mm	16.9320.020.15	16.9320.020.13/16/18
65 mm	16.9320.065.15	16.9320.065.13/16/18

Mounting tool



- Mounting aid for rubber seal
- Sales unit: 1 piece

Model 0100	
	Art. no.
	90.0100.105.00

Demo box



Model 1600	Aluminium natural anodised
	Art. no.
SKYFORCE Top	81.1600.100.11
SKYFORCE Side	81.1600.200.11
SKYFORCE Slim	81.1600.300.11

5

GLASS CANOPY

System

AIRFORCE®



ENGINEERED IN GERMANY

System

AIRFORCE on Roofing Surveillance Mission

The ONLEVEL AIRFORCE system keeps you protected from the rain—without compromising on style. Its sleek, beautifully designed wall-mounted profile, crafted from high-grade aluminium, creates a clean floating effect for your canopy glass.


Engineered for effortless installation, the system features integrated height adjustability, a self-triggering cover cap, and high-pressure insulation – making it perfectly suited for mounting on insulated façades. Every detail is designed to ensure a smooth, efficient installation process while delivering a premium architectural finish.


This system is supplied fully assembled, thus enabling a super fast installation.

Essential features

- Securing the glass from the side
- Height adjustable with integrated, self-triggering cover
- Simple mounting
- Concealed fastening
- One-sided fastening, no drawbars required
- Several profiles can be connected to each other
- Slight glass processing for securing glass panes
- Only the lower pane requires glass processing, therefore no drilling offset for laminated safety glass
- Max. glass width 3000 mm
- 10° inclination

AbZ Bauart geprüft





Profile

Glass profile



- For 17,52 mm (8/8/4) and 21,52 mm (10/10/4) laminated safety glass made of thermally toughened glass with PVB or SGP film
- Sales unit: 1 piece

Anchor distance	Anchor quantities									
Profile length	1,4	1,6	2	2,4	2,8	3,2	3,5	4	4,5	5
200 mm	7	8	10	12	14	16	17	20	22	25
400 mm	4	4	5	6	7	8	8	10	11	13

Anchor distances: see calculation / test report


Model 6620	Mill finish	Aluminium natural anod.	RAL coloured
Length	Art. no.	Art. no.	Art. no.
1,4 m	17.1014.020.10	17.1014.020.11	17.1014.020.13/16/18.19
1,6 m	17.1016.020.10	17.1016.020.11	17.1016.020.13/16/18.19
2 m	17.1020.020.10	17.1020.020.11	17.1020.020.13/16/18.19
2,4 m	17.1024.020.10	17.1024.020.11	17.1024.020.13/16/18.19
2,8 m	17.1028.020.10	17.1028.020.11	17.1028.020.13/16/18.19
3,2 m	17.1032.020.10	17.1032.020.11	17.1032.020.13/16/18.19
3,5 m	17.1035.020.10	17.1035.020.11	17.1035.020.13/16/18.19
4 m	17.1040.020.10	17.1040.020.11	17.1040.020.13/16/18.19
4,5 m	17.1045.020.10	17.1045.020.11	17.1045.020.13/16/18.19
5 m	17.1050.020.10	17.1050.020.11	17.1050.020.13/16/18.19

Extension pin




- Infinite extensions?
  No problem, we remove the end cap for you
- Length: 40 mm
- Diameter Ø 6 mm
- Sales unit: 8 pieces


Model 7001	AISI 316 (indoor & outdoor)
	Art. no.
	90.7001.640.31



Glass cut-out



Glass thickness (G)
8/8/4 (17,52 mm)
10/10/4 (21,52 mm)



For glass dimensions: see AbZ

ONLEVEL surface finishes

10.3620.002.**10** → **.10** Aluminium mill finish

10.3620.002.**11** → **.11** Aluminium natural anodised

10.3620.002.**13**/**16**/**18**/**19** → **.13** RAL glossy, **.16** RAL structured matt, **.18** RAL matt, **.19** Armor RAL



See pages 8 and 19 for more information and order options.

GLASS CANOPY

Accessories | additionals

AIRFORCE®

ONLEVEL

ADVANCED RAILING TECHNOLOGY

Accessories

Mortar



- For chemical bonding of anchors
- Including 2 mixers
- Sales unit: 1 piece

Model 3000	
	Art. no.
	91.3000.010.00

Dispensing device



- For use with mortar (91.3000.010.00)
- Sales unit: 1 piece

Model 3002	Plastic
	Art. no.
Gun	91.3002.010.00
Mixer	91.3002.011.00

Airpump



- For blowing out the drill holes
- Sales unit: 1 piece

Model 3001	Plastic
	Art. no.
	91.3001.010.00

Anchor hole brush



- For cleaning the drill holes
- Ø 12 mm
- Sales unit: 1 piece

Model 3002	Plastic
	Art. no.
	91.3002.012.00

Anchor hole fillings per mortar cartridge

AIRFORCE®

	17.9005.012.20 17.9005.012.30
Mortar 390 ml (91.3000.010.00)	26

	17.9005.012.20 17.9005.012.30
Mortar 280 ml (91.3600.010.00)	18

GLASS CANOPY


Mounting examples

AIRFORCE®

ONLEVEL

ADVANCED RAILING TECHNOLOGY


Mounting on **concrete**



Mounting set for concrete (mechanical)



- M12
- Sales unit: 20 pieces




Model 3501 / 3601	AISI 316 (outdoor)	
	Art. no.	
	91.3501.220.30	fischer
	91.3601.220.30	MKT

Mounting set for concrete (mechanical)




- AISI 316 (outdoor)
- Sales unit: 2 pieces



Model 3501 / 3601		AISI 316 (outdoor)	
Ø	L	Art. no.	
8 mm	160 mm	91.3580.816.30	
10 mm	200 mm	91.3581.020.30	
10 mm	230 mm	91.3581.023.30	fischer
10 mm	260 mm	91.3581.026.30	
10 mm	290 mm	91.3581.029.30	

Mounting on **concrete**


Mounting with insulation



Mounting set for concrete (chemical)



- Set for pressure-resistant insulation
- Sales unit: 8 pieces




Model 9005	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	17.9005.012.20	17.9005.012.30

Pressure-resistant insulation




- Length 600 or 1200 mm
- Including signal pin for flush-mounted installation (1/hole)
- Sales unit: 1 piece



Model 9006	600 mm	1200 mm
Thickness (t)	Art. no.	Art. no.
10 mm	17.9006.016.00	17.9006.010.00
100 mm	17.9006.106.00	17.9006.100.00
150 mm	17.9006.156.00	17.9006.150.00
200 mm	17.9006.206.00	17.9006.200.00

The wall construction must be statically tested on site.


Mounting on **wood**



Mounting set on wood M12 x 200 mm




| Sales unit: 8 pieces



Model 9004	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	91.9004.012.81	91.9004.012.20

Mounting on **steel**




In some use cases mounting distances of 400 mm are allowed (see calculation / test report).

Mounting set for steel



- M12 x 50 mm
- Sales unit: 4 pieces



Model 9003	AISI 304 (indoor)	AISI 316 (outdoor)
	Art. no.	Art. no.
	17.9003.012.20	17.9003.012.30

The wall construction must be statically tested on site.

ONLEVEL

ADVANCED RAILING TECHNOLOGY



6

GENERAL TERMS AND CONDITIONS

ONLEVEL
ADVANCED RAILING TECHNOLOGY

GENERAL TERMS AND CONDITIONS

1. Scope

These General Terms and Conditions shall apply to all contracts which ONLEVEL concludes with their customers – hereinafter referred to as entrepreneurs – on the purchase of goods and other services, including application-oriented advice and counselling. Additional, partly deviant or extended conditions, overriding the present General Terms and Conditions, shall apply for the installation of products by ONLEVEL employees; for all other cases, these conditions shall apply exclusively. ONLEVEL shall not accept any adverse or deviant conditions of the entrepreneur without explicit written consent. These conditions shall apply even if ONLEVEL delivers services without reservation in the knowledge of conflicting conditions of the entrepreneur or conditions that deviate from these General Terms and Conditions. These General Terms and Conditions shall apply only to entrepreneurs, legal persons under public law and special funds under public law as per § 14 BGB (German Civil Code). They are applicable in the respective current version also to all future transactions with the entrepreneur.

2. Contract, reservation of changes, quotation documents, etc.

2.1 All information and specifications in catalogues, flyers or other documents are non-binding and do not represent quotations. They are intended to support the entrepreneur when submitting a binding quotation.

2.2 The entrepreneur may submit the quotation by phone, fax, e-mail, or in writing. If an order form is delivered with the catalogue, the entrepreneur may use this form to submit their quotation. For this purpose, they must fill in the form and return it to ONLEVEL by post, fax, or e-mail.

2.3 Contracts between ONLEVEL and their entrepreneurs shall be deemed concluded as soon as an order confirmation is sent by ONLEVEL in written or electronic form, by e-mail or fax. The order confirmation is decisive for the content of the contract. If ONLEVEL delivers services without prior order confirmation, the contract shall be deemed effective upon the beginning of the service or delivery of the ordered goods.

2.4 ONLEVEL may accept the entrepreneur´s quotation within seven days by sending the entrepreneur a written order confirmation or an order confirmation in text form (fax or e-mail) with the receipt of order confirmation by the entrepreneur being decisive, or by delivering the ordered goods to the entrepreneur with the receipt of the ordered goods being decisive, or with ONLEVEL demanding payment from the entrepreneur after placing their order.

2.5 If the ordered goods are no longer available or have been replaced, ONLEVEL reserves the right to deliver deviating products of unchanged or improved quality.

2.6 ONLEVEL retains all property rights, copyrights and other protected rights to submitted quotations, cost estimates as well as drawings, figures, calculations, flyers, catalogues, models and other documents made available. The above-mentioned documents must not be made available to third parties without explicit written consent. This applies, in particular, to confidential documents.

2.7 If the parties have agreed on special conditions, these generally do not apply to any concurrent or future contractual relationships with the entrepreneur.

2.8 In the event of the entrepreneur's economic inability to fulfil their obligations to ONLEVEL, ONLEVEL shall be entitled to withdraw from all existing exchange contracts with the entrepreneur without further notice. The same applies in the event of an insolvency petition by the entrepreneur. § 321 BGB and § 112 InsO (German Insolvency Act) shall remain unaffected thereof. The entrepreneur shall inform ONLEVEL in good time of any impending inability to pay.

3. Prices, terms of payment

3.1 If not indicated otherwise in the order confirmation, all prices are quoted "ex works" in Emmerich (Manchester, Viby J). All indicated prices are net prices plus statutory VAT. Shipping and freight charges, packaging costs and possible installation costs are not included. A handling fee of € 30.00 per shipment shall apply for orders with a (net) goods value below € 250.00.

3.2 Changes to prices indicated in the price list are reserved. The respective list prices at the time of the order are binding. Modified prices shall be considered accepted if the entrepreneur does not object immediately after receiving the order confirmation.

3.3 For deliveries to countries outside the European Union, further costs may be incurred on a case-by-case basis which ONLEVEL is not responsible for, and which shall be borne by the entrepreneur. These include, for example, costs for money transfer by credit institutions (e. g. transfer fees, exchange rate fees) or import duties or taxes (e. g. customs duties). Such money transfer fees may also be incurred if delivery does not take place in a country outside the European Union, but the entrepreneur makes the payment from a country outside the European Union.

3.4 ONLEVEL shall be entitled to issue a partial invoice if they have the right to make a partial delivery in accordance with the following conditions under 4) – Delivery and shipping terms.

3.5 The entrepreneur can choose between different payment options, detailed in the ONLEVEL catalogue.

3.6 The purchase price is due and payable immediately, unless indicated otherwise in the order confirmation. If the entrepreneur is overdue in making the payment, ONLEVEL shall be entitled to demand default interest pursuant to § 288 BGB. ONLEVEL reserves the right to prove and assert a higher damage caused by default.

3.7 The entrepreneur shall only be entitled to withhold payments or to offset with counterclaims if their counterclaims have been legally established or are undisputed.

3.8 ONLEVEL reserves the right to supply their goods only on pre-payment or by cash on delivery. Unless otherwise agreed in the order confirmation, the first three deliveries shall be generally subject to pre-payment.

3.9 ONLEVEL invoices the first 3 orders to new customers as advance payment.

4. Delivery, delivery time

4.1 Delivery is “FCA, Free Carrier” to Budberger Straße 5, Emmerich, Germany, on the basis of the latest Incoterms®.

4.2 Partial deliveries are possible if not all ordered goods are in stock, and the entrepreneur can be reasonably expected to accept such partial delivery; the entitlement to issue a partial invoice as per 3.4 is explicitly pointed out.

4.3 Unless otherwise agreed, the goods shall be delivered via the indicated shipping route to the delivery address indicated by the entrepreneur. Delivery dates and times are only binding if they are explicitly confirmed in writing as binding between ONLEVEL and the entrepreneur.

4.4 Agreed delivery periods are extended by a reasonable period of time – also within primary delay – in the event of force majeure, epidemics, pandemics, diseases, illnesses or quarantine measures, and all unforeseeable impediments that have occurred after the conclusion of contract and are beyond the control of ONLEVEL, regardless of whether the impediments are suffered by ONLEVEL or their suppliers. In this case, both parties shall be entitled to withdraw from the contract. In case of non-supply, ONLEVEL shall attempt to acquire the goods in a reasonable manner. If the goods are not or only partially available, ONLEVEL shall inform the entrepreneur accordingly and provide any applicable consideration for the non-deliverable goods.

4.5 Force majeure shall include all events that are unforeseeable for the parties or that lie outside the control of the parties – even if they were foreseeable – and whose effects on contract fulfilment cannot be impeded by reasonable efforts of the parties. Any further statutory claims shall remain unaffected thereof.

4.6 Decisive for the observance of the delivery date is the day when the (partial) delivery is made available for collection or shipment or the day when the goods are handed over to the forwarding agent.

4.7 If delivery is not possible for reasons that can be attributed to the entrepreneur, they shall bear the costs for the unsuccessful delivery and shall be liable to pay a lump-sum compensation for delay. The lump-sum compensation for delay is based on the value of the overall delivery and the delay occurred, whereby each commenced week of delay shall be calculated with one percent of the value of the overall delivery, totalling a maximum of eight percent. The gross value shall be decisive. The parties are free to prove a higher or lower damage which replaces the lump-sum compensation for delay.

5. Passing of risk, shipment

5.1 Any and all deliveries shall be carried out without prejudice to whether the shipment was organised for the entrepreneur by ONLEVEL at the entrepreneur´s risk and expense. This shall also apply if shipping costs are omitted. The passing

of risk shall take place upon handover to the forwarding agent or, in the event of collection, upon handover to the person commissioned with the collection. This shall also apply if ONLEVEL bears the costs of transport. Transport insurance is only concluded upon special request at the entrepreneur's expense. If the shipment of goods is delayed due to reasons which the entrepreneur is responsible for, the passing of risk already takes place upon notification of the entrepreneur of readiness for shipment. Any incurred storage costs after passing of risk shall be borne by the entrepreneur.
5.2 If the entrepreneur defaults in accepting the performance or if they violate further obligations to cooperate, the risk of accidental loss or accidental deterioration of the purchased item shall be transferred to the entrepreneur from the point in time where the delay of acceptance commences.
5.3 ONLEVEL reserves the right to choose the shipping method and the means of packaging and transport. No claim of the entrepreneur against ONLEVEL shall be derived from this choice.

6. Packaging

All packaging shall be recycled or disposed of in an environmentally friendly way in accordance with the German Packaging Ordinance. If the entrepreneur themselves carries out the disposal, ONLEVEL shall not be held liable for the resulting costs. If the entrepreneur sends back the packaging material to ONLEVEL for disposal, the despatch shall be done at the entrepreneur´s expenses; any packaging material reaching ONLEVEL with the postage unpaid, shall be refused.

7. Return of goods

7.1 Goods ordered incorrectly or in excess can be returned by the entrepreneur as long as the goods have not been used, are in their original packing and in good and resalable condition. The return of goods will be charged with 20% of the net invoice amount, however, minimum € 100.
7.2 Return consignments are mandatorily required to have a return reference number affixed to them and cannot be accepted without this number.
7.3 Return consignments shall only be taken back if their acceptance has been previously agreed in writing with ONLEVEL.
7.4 Return consignments shall only be accepted if the reasons for their return are indicated upon returning the consignment including a return reference number.

8. Warranty

8.1 In the event of a defect attributable to ONLEVEL, the statutory provisions shall apply. By way of derogation, the following applies.
8.2 Rights and claims on the grounds of defects shall be excluded for used goods. New goods shall be excluded from warranty if defects and damage do not result from natural wear and tear, and especially if the defects have occurred after passing of risk due to improper and careless handling, excessive use, unsuitable operating equipment or due to extraordinary external influences which are not assumed under the contract. If improper modifications or repairs are made by the entrepreneur or third parties, no claims for defects shall exist for such and the results thereof, unless the entrepreneur can prove that the reported defect does not result from such modifications or repairs. Recourse claims shall be excluded pursuant to § 445a BGB.
8.3 ONLEVEL reserves the right to choose between remedy of defects and replacement delivery. In the event of remedy of defects, ONLEVEL shall bear any and all resulting costs and expenses, especially transportation, travelling, work and material expenses, to the extent that these expenses are not increased because the goods have been transported to a place other than the place of fulfilment.
8.4 If supplementary performance is done by replacement delivery, the entrepreneur shall be obliged to return the initially delivered goods to ONLEVEL within 30 days. The return consignment must include the reason for return, the customer´s name and the purchase number assigned to the defective goods which enables ONLEVEL to assign the returned goods. As long and insofar as the assignment of the return consignment is not possible due to reasons attributable to the entrepreneur, ONLEVEL shall not be obliged to accept the returned goods and to refund the purchase price. The costs of renewed shipment shall be borne by the entrepreneur.
8.5 Should ONLEVEL not be willing or not be able to remedy the defect or make a replacement delivery, the entrepreneur shall be entitled, at their own choice, to withdraw from the contract or demand an appropriate reduction of the purchase price. This is also applicable in the event of delays beyond reasonable periods on grounds for which ONLEVEL can be held responsible.
8.6 Claims concerning material defects shall become statute-barred one year after the risk has passed. A supplementary performance (new delivery or repair) shall affect exclusively the period of limitation of the defect giving rise to the supplementary performance.
8.7 The entrepreneur's warranty rights are subject to the entrepreneur's due compliance with inspection and notification stipulations in accordance with § 377 HGB (German Commercial Code). If the entrepreneur refrains from the obligation to notify stipulated therein, the goods shall be deemed to have been approved, unless the defect was not identifiable during the inspection.
8.8 Any and all indications and descriptions in illustrations, flyers, catalogues and advertisements are mere product descriptions and cannot be regarded as quality description of the goods. Such indications are only binding if they have been expressly agreed to define the quality of the goods.
8.9 All technical data, especially information on dimensions, have been thoroughly compiled. They comply with the current state of the art at the time of publication. Changes might result from necessary technical amendments. Liability for damage caused by wrong dimensions is expressly denied. Production-related deviations in dimensions, contents, weights, thicknesses, and colours are permissible within the scope of normal industry tolerances. All published and distributed technical data, explanations and instructions concerning conditions of use and installation, are to be observed by the entrepreneur.

9. Advice

If application-oriented advice by ONLEVEL staff is required, this advice always complies with the current state of development. The advice will be given by qualified ONLEVEL staff or authorised partners observing the principles of proper execution of work. The selection of the appointed employees and service partners shall be reserved to ONLEVEL. A guarantee of successful performance is not given – unless agreed otherwise in writing – as the successful performance depends on different factors which are usually not verifiable through application-oriented advice. The advice does not exempt the entrepreneur from testing the suitability of the product for the intended purposes and processes.

10. Liability

10.1 ONLEVEL shall be liable towards the entrepreneur for all contractual, quasi-contractual, and tortious claims for damage and reimbursement of expenses as follows:
- ONLEVEL shall be liable on any legal ground and without limitation for: damage caused by intent or gross negligence; in derogation thereof, also for the deliberate or slightly negligent violation of life, body, or health and/or violation of a material contractual obligation (a so-called cardinal obligation) whose fulfilment is a prerequisite for the proper implementation of the contract and on the fulfilment of which the entrepreneur regularly relies and may rely; without limitation based on a warranty promise, unless otherwise agreed, and in accordance with the Product Liability Act;
- These liability provisions shall also apply for the liability of ONLEVEL towards their legal representatives and/or agents.
10.2 Insofar as ONLEVEL is liable for slight negligence, this liability shall be limited to typical contractual and foreseeable damage for property damage and financial losses. The liability for remote consequential damage shall be excluded.

11. Retention of title

11.1 ONLEVEL shall retain title of the delivered goods until complete fulfilment of all obligations resulting from the relationship with the entrepreneur.
11.2 The entrepreneur is entitled to sell goods subject to retention of title within the course of ordinary business; however, the entrepreneur hereby assigns to ONLEVEL in advance any claims to the amount of the invoice total (including value added tax) which the entrepreneur may have against their clients or third parties, irrespective of whether the goods subject to retention of title were resold without or after processing. The entrepreneur shall remain entitled to collect this

claim even after assignment. The authorisation of ONLEVEL to collect the debts themselves, shall remain unaffected. However, ONLEVEL undertakes not to collect the claims as long as the entrepreneur meets their payment obligations, is not in default of payment, no insolvency proceedings are instituted over their assets, or payments are suspended. In this case, the entrepreneur shall be obliged to disclose to ONLEVEL the receivables assigned and their debtors, give all information required for collection, surrender associated documentation, and notify the debtors (third parties) about the assignment.

11.3 The entrepreneur is entitled to process the reserved goods. This authorisation ends with the definite suspension of payments by the entrepreneur, or if insolvency proceedings are instituted over their assets. Any processing or transformation of the goods is always done for ONLEVEL. If the reserved goods are processed with other objects, ONLEVEL shall be entitled to co-ownership of the new object in a ratio equal to the value of the purchased item to the other goods that were processed at the time of processing. For the object arising from such processing the same applies as for the goods delivered subject to retention of title. If the goods supplied under retention of title are inseparably combined or mixed with other goods not belonging to ONLEVEL, then ONLEVEL shall acquire co-ownership of the new item created in the ratio of the value of the purchased item to the value of the other goods combined or mixed at the time of mixing. If mixing is performed in such a manner that the item of the entrepreneur is to be regarded as the principal item, then it is deemed agreed that the entrepreneur transfers to ONLEVEL a proportional co-ownership. The entrepreneur shall hold the sole or joint ownership for ONLEVEL.

11.4 If the entrepreneur defaults in payment or fails to fulfil their obligations under the retention of title, ONLEVEL may set a reasonable extension of time for performance or subsequent performance. In the event of this period expiring without result, ONLEVEL shall be entitled to withdraw from the contract and to take back the delivered goods. For this purpose, the entrepreneur shall send an accurate statement of all goods that have been delivered to them subject to retention of title, separate the goods and hand them over to ONLEVEL. After a warning with a reasonable time limit, the goods may be sold for the best possible price on the open market, setting off the price charged to the entrepreneur.

11.5 The entrepreneur shall be obliged to treat the purchased item with care; they are especially obliged to insure it sufficiently at their own expense against fire, water, and theft damage to the replacement value. Should maintenance and inspection work be necessary, the entrepreneur must perform such work in good time and at their own expense. Seizure or other third-party interventions are to be notified immediately in writing.

11.6 Upon request of the entrepreneur, ONLEVEL shall release the delivered goods subject to retention of title and items or claims that have replaced them, insofar as the realisable value of the securities exceeds the obligations to be secured by more than 20%; ONLEVEL shall be responsible for the selection of securities to be released.

12. Place of jurisdiction, place of performance, applicable law

12.1 Place of jurisdiction, at ONLEVEL´s choice, shall be the court competent for their headquarters or for the entrepreneur, insofar as the entrepreneur is a trader, a legal entity under public law or special funds under public law.

12.2 The place of performance for delivery shall be the place where the goods are stored for the purpose of being despatched or handed over to the entrepreneur. The place of performance for paying the purchase price and for fulfilling all other contractual obligations of the entrepreneur shall be Emmerich (Manchester).

12.3 Any and all legal relationships and disputes between the contracting parties shall be exclusively handled by German law under exclusion of UN sales law.

Last update: 04/08/2023

INFORMATION ON DATA PRIVACY

13. Information on the collection of personal and contact data of the respon-si-ble person

13.1 In the following, we will inform you about how your personal data is handled. Personal data refers to all data which makes you personally identifiable.

13.2 The data controller responsible for data processing in line with the General Data Protection Regulation (GDPR) is ONLEVEL GmbH, Bud-berger Straße 5, 46446 Emmerich, Germany, Phone: +49 (0)2822 97514 0, e-mail: info@onlevel.com. The data controller responsible for the processing of personal data shall be the natural or legal person who alone or jointly with others determines the purposes and means of the processing of per-sonal data.

13.3 When you contact us (e. g. by phone, contact form or e-mail), we collect the personal data contained in the contact form. This data will be processed and used exclusively for the purpose of answering your query or getting in touch with you, and for the required technical ad-ministration in this context. The legal basis for the processing of data is our legitimate interest in answering your query pursuant to Art. 6 para. 1 lit. f GDPR. If you con-tact us for the purpose of concluding a contract with us, the additional legal basis for the processing of your personal data is Art. 6 para. 1 lit. b GDPR. Your data will be deleted once we have processed your request; this is the case if it is clear from the circum-stances that the issue in question has been conclusively clarified and no longer statutory retention periods are required by law.

14. Data processing for order handling

14.1 The personal data collected by us will be passed on to the transport company commissioned with delivery for the purposes of contract ful-filment, insofar as this is required for the delivery of the goods.

14.2 If, based on a corresponding contract, we owe you updates for goods with digital elements or for digital products, we will process the contact data provided by you when ordering (name, address, e-mail address) in order to inform you in person via a suitable communication channel (i. e. by post or e-mail) about upcoming updates within the statutory period, in this way fulfilling our legal obligation to inform pur-suant to Art. 6 para. 1 lit. c GDPR. In this context, your contact data will only be used strictly earmarked for notifications about updates owed by us and will only be processed for this purpose insofar as this is necessary for the information in question.

14.3 We will forward your payment data to the credit institution com-missioned with the handling of payments, insofar as this is necessary for payment processing. If payment providers are used, this will be explicitly pointed out in the following. In this case, the legal basis for the disclosure of data is Art. 6 para. 1 lit. b GDPR.

15. Data subject rights

15.1 The applicable data protection law provides you with comprehensive data subject rights (right to information and intervention) with respect to the processing of your personal data by the data controller, which will be specified in the following:

- Right to information according to art. 15 GDPR: In particular, you are entitled to a right to information about your personal data pro-cessed by us, about the processing purposes, the categories of per-sonal data processed, the recipients or categories of recipients whom your data will be or have been disclosed to, the planned re-tention period or criteria for determining the retention period, the existence of a right to correction, erasure, limitation of processing, to object to processing, to file a complaint with a supervisory au-thority, to know the origin of your data if it has not been collected from you by us, the existence of automated decision-making procedures, including profiling and, if applicable, conclusive information about the logics involved and the scope and effects of such processing for you, as well as your right to notifica-tion about the guarantees provided pursuant to Art. 46 GDPR upon transfer of your data to third countries;
- Right to rectification pursuant to Art. 16 GDPR: You have the right to immediate rectification of inaccurate data concerning you and/or the right to completion of incomplete data saved by us.
- Right to erasure pursuant to Art. 17 GDPR: You are entitled to de-mand the erasure of your personal data if all requirements of Art. 17 para. 1 GDPR are met. However, this right shall not apply, in particular, if the processing is required for exercising the right to freedom of expression and information, for meeting a legal obliga-tion, on grounds of public interest or for asserting, exercising or de-fending legal claims;

- Right to limitation of processing pursuant to Art. 18 GDPR: You have the right to demand the limitation of processing of your personal da-ta as long as the correctness of your personal data, which you deny, is being verified, if you reject the erasure of your data due to unau-thorised data processing and demand the limitation of processing of your data in-stead, if you need your data for asserting, exercising or defending legal claims, if we do not need this data any longer after the pro-cessing purpose has been served, or if you have filed an objection on grounds relating to your particular situation as long as it has not been determined whether our legitimate reasons prevail;
- Right to notification pursuant to Art. 19 GDPR: If you have asserted your right of rectification, erasure or limitation of processing to-wards the data controller, the data controller shall be obliged to no-tify all recipients whom the personal data concerning you have been disclosed to of this rectification or erasure or limitation of pro-cessing of the data concerned, unless this proves impossible or in-volves a disproportionate effort. You have the right to be informed about the correspond-ing recipients;
- Right to data portability pursuant to Art. 20 GDPR: You have the right to receive the personal data you provided to us in a structured, standard, and machine-read-able format, or to demand their transfer to another responsible person, where technically feasible;
- Right to revocation of consent already granted pursuant to Art. 7 para. 3 GDPR: You have the right to revoke a consent to data processing once granted at any time with effect for the future. In the event of such revocation, we will delete the data involved im-mediately, unless further processing can be based on a legal basis for processing without consent. The lawfulness of the data pro-cessing hav-ing taken place based on the consent granted before the revocation shall remain unaffected thereof;
- Right to file a complaint pursuant to Art. 77 GDPR: If you consider that the pro-cessing of the personal data concerning you constitutes a violation of the GDPR, you are entitled – notwithstanding any other administrative or legal appeal – to lodge a complaint with a supervi-sory authority, especially in your Member State of residence, work-place, or the location of the alleged violation.

RIGHT TO OBJECT

IF WE PROCESS YOUR PERSONAL DATA WHEN BALANCING THE INTERESTS INVOLVED ON GROUNDS OF OUR OVERRIDING LEGITIMATE INTEREST, YOU HAVE THE RIGHT TO OBJECT TO ANY FURTHER PROCESSING WITH EFFECT FOR THE FUTURE AT ANY TIME FOR REASONS RELATING TO YOUR PAR-TICULAR SITUATION. IF YOU EXERCISE YOUR RIGHT TO OBJECT, WE WILL TERMINATE THE PRO-CESSING OF THE CONCERNED DATA. FURTHER PROCESSING REMAINS RE-SERVED, HOWEVER, IF WE ARE ABLE TO PROVE LEGITIMATE AND COM-PELLING GROUNDS FOR PROCESSING WHICH OUTWEIGH YOUR INTERESTS, RIGHTS AND FREEDOMS, OR THE PROCESSING SERVES TO ASSERT, EXER-CISE OR DEFEND LEGAL CLAIMS. IF WE PROCESS YOUR PERSONAL DATA FOR DIRECT ADVERTISING PUR-POSES, YOU ARE ENTITLED TO OBJECT TO THE PROCESSING OF PERSONAL DATA CONCERNING YOU FOR SUCH ADVERTISING PURPOSES AT ANY TIME. YOU CAN EXERCISE YOUR OBJECTION AS DETAILED ABOVE. IF YOU EXERCISE YOUR RIGHT TO OBJECT, WE WILL TERMINATE THE PRO-CESSING OF THE CONCERNED DATA FOR DIRECT ADVERTISING PURPOSES.

16. Duration of storage for personal data

16.1 The storage duration of personal data depends on the applicable legal basis, the processing purpose and in addition – where relevant – the applicable statuto-ry retention period (e. g. retention periods under commercial and tax law).
16.2 When processing personal data on the basis of express consent in accordance with Art. 6 para. 1 lit. a GDPR, this data is stored until you revoke your consent.
16.3 If there are statutory retention periods for data that is processed in the context of legal or similar obligations on the basis of Art. 6 para. 1 lit. b GDPR, this data will be routinely erased upon expiry of the retention periods, where no longer needed for contract fulfilment or contract initiation and/or where we have no legitimate interest in further storage.
16.4 When processing personal data on the basis of Art. 6 para. 1 lit. f GDPR, this data is stored until you exercise your right to object pursuant to Art. 21 para. 1 GDPR, unless we are able to prove legitimate and compelling grounds for process-ing which outweigh your interests, rights and freedoms, or the processing serves to assert, exercise or defend legal claims.
16.5 When processing personal data for direct advertising purposes pur-suant to Art. 6 para. 1 lit. f GDPR, this data will be stored until you exercise your right to object in line with Art. 21 para. 2 GDPR.
16.6 Unless not otherwise provided in this statement, stored personal data will also be deleted if the purposes which they were collected or otherwise processed for no longer exist.

EUROGLAS.

EUROGLAS BORNEM

Puursesteenweg 377
2880 Bornem

+32 3 890 67 70

EUROGLAS FLEURUS

Avenue du Spirou 40
6220 Fleurus

+32 71 82 23 23

EUROGLAS MEER

Riyadhstraat 28
2321 Meer

+32 3 330 11 80

EUROGLAS VILLERS

Rue du Château d'Eau 18
4530 Villers-le-Bouillet

+32 85 27 08 00

info@euroglas.be | www.euroglas.be